Milky Way Chandelier Horizontal 120

MWCHHR120

CE IP20

Materials

Electroplated Aluminium, Hand blown Murano glass, Cathedral glass, Marble (Green Guatemala Cone) and Onyx (White Sphere)

Weight incl. canopy

Polished gold and nickel finished aluminium ~12.5 kg Brushed brass and blackened brass ~19.5 kg

Power Input

220-240V 50-60Hz

Light Source (included)

Strip LEDs. 66W, 5400 Lumens, 2700K warm white. CRI>90.

CONFIGURATION


STEP 1 - CHOOSE YOUR METAL FINISH





MILKY WAY CHANDELIER HORIZONTAL 120

SIZE (UNIT: CM)



STEP 2 - CHOOSE YOUR MURANO GLASS FINISH







STEP 3 - CHOOSE YOUR SUSPENSION TYPE

SUSPENSION TYPE

MURANO GLASS



Black Fabric Flex Cable

Drop height adjustable on site:

10M




White Fabric Flex Cable

Drop height adjustable on site:

+ STANDARD BUILTIN PHASECUT DRIVER

A. We provide a L1150 canopy with a builtin LED driver with **phasecut dimming** as standard.






+ OTHER BUILTIN DRIVERS AVAILABLE ON REQUEST

B. We can also provide builtin LED drivers with 1-10 Volt, Switch / Push or DALI dimming, if required by your electrician.





+ REMOTE DRIVERS AVAILABLE ON REQUEST

B. If your electrician can wire the LED Drivers remotely (rather than builtin to the canopy) we can provide the following options:





Milky Way Chandelier Horizontal 190

MWCHHR190

C€ IP20

Materials

Electroplated Aluminium, Hand blown Murano glass, Cathedral glass, Marble (Green Guatemala Cone) and Onyx (White Sphere)

Weight incl. canopy

Polished gold and nickel finished aluminium ~13.2 kg Brushed brass and blackened brass -22.5 kg

Power Input

220-240V 50-60Hz

Light Source (included)

Strip LEDs. 90.7W, 7430 Lumens, 2700K warm white. CRI>90.


CONFIGURATION

STEP 1 - CHOOSE YOUR METAL FINISH





SIZE (UNIT: CM)



STEP 2 - CHOOSE YOUR MURANO GLASS FINISH





MURANO GLASS

STEP 3 - CHOOSE YOUR SUSPENSION TYPE

SUSPENSION TYPE



Black Fabric Flex Cable

Drop height adjustable on site:

4M	
10M	



White Fabric Flex Cable

Drop height

adjustable on site:	
4 M	
10M	

+ STANDARD BUILTIN PHASECUT DRIVER

A. We provide a L850 canopy with a builtin LED driver with **phasecut dimming** as standard.






+ OTHER BUILTIN DRIVERS AVAILABLE ON REQUEST

B. We can also provide builtin LED drivers with 1-10 Volt, Switch / Push or DALI dimming, if required by your electrician.





+ REMOTE DRIVERS AVAILABLE ON REQUEST

B. If your electrician can wire the LED Drivers remotely (rather than builtin to the canopy) we can provide the following options:



