Milky Way Pendant **Infinity Elements 240**

MWPEIE240

IP20

Materials

Electroplated Aluminium or Hand finished brass, Hand blown Murano glass, Cathedral glass.

Weight incl. canopy

Polished gold and nickel finished aluminium ~15 kg Brushed brass and blackened brass -24 kg

Power Input

220-240V 50-60Hz

Light Source (included)

Strip LEDs. 53W, 4340 Lumens, 2700K warm white. CRI>90.




CONFIGURATION

STEP 1 - CHOOSE YOUR METAL FINISH



SIZE (UNIT: CM)



STEP 2 - CHOOSE YOUR MURANO GLASS FINISH



MURANO GLASS



STEP 3 - CHOOSE YOUR SUSPENSION TYPE

SUSPENSION TYPE



Black Fabric Flex Cable

Drop height adjustable on site:

10M



White Fabric Flex Cable

Drop height adjustable on site:

+ STANDARD BUILTIN PHASECUT DRIVER

A. We provide a multiple L850 canopy with a builtin LED driver with **phasecut dimming** as standard.







+ OTHER BUILTIN DRIVERS AVAILABLE ON REQUEST

B. We can also provide builtin LED drivers with 1-10 Volt, Switch / Push or DALI dimming for two L850 linear canopies and Phasecut, 1-10 Volt, Switch / Push, Dali dimming for four D200 circular canopies. These dimming and canopy combinations are available in the following dimensions:











+ REMOTE DRIVERS AVAILABLE ON REQUEST

B. If your electrician can wire the LED Drivers remotely (rather than builtin to the canopy) we can provide two L850 linear canopy or four D85 circular canopies. These dimming and canopy combinations are available as following:









Milky Way Pendant Infinity Elements 360

MWPEIE360

C€ IP20 UK

Materials

Electroplated Aluminium or Hand finished brass, Hand blown Murano glass, Cathedral glass.

Weight incl. canopy

Polished gold and nickel finished aluminium ~18.2 kg Brushed brass and blackened brass ~30.6 kg

Power Input

220-240V 50-60Hz

Light Source (included)

Strip LEDs. 53W, 4340 Lumens, 2700K warm white. CRI>90.




MILKY WAY PENDANT INFINITY ELEMENTS 360

CONFIGURATION

STEP 1 - CHOOSE YOUR METAL FINISH



SIZE (UNIT: CM)



STEP 2 - CHOOSE YOUR MURANO GLASS FINISH

BLACK SPOTS





STEP 3 - CHOOSE YOUR SUSPENSION TYPE

SUSPENSION TYPE

MURANO GLASS



Black Fabric Flex Cable

Drop height adjustable on site:

4M 10M



White Fabric Flex Cable

Drop height adjustable on site:

4M
10M

+ STANDARD BUILTIN PHASECUT DRIVER

A. We provide a multiple L850 canopy with a builtin LED driver with **phasecut dimming** as standard.







+ OTHER BUILTIN DRIVERS AVAILABLE ON REQUEST

B. We can also provide builtin LED drivers with 1-10 Volt, Switch / Push or DALI dimming for two L850 linear canopies and Phasecut, 1-10 Volt, Switch / Push, Dali dimming for four D200 circular canopies. These dimming and canopy combinations are available in the following dimensions:









+ REMOTE DRIVERS AVAILABLE ON REQUEST

B. If your electrician can wire the LED Drivers remotely (rather than builtin to the canopy) we can provide two L850 linear canopy or four D85 circular canopies. These dimming and canopy combinations are available as following:



