Milky Way Pendant Infinity Line 120

MWPEIL120

C€ IP20 UK

Materials

Electroplated Aluminium or Hand finished brass, Cathedral glass.

Weight incl. canopy

Polished gold and nickel finished aluminium ~6 kg Brushed brass and blackened brass ~10,5 kg

Power Input


220-240V 50-60Hz

Light Source (included)

Strip LEDs. 47.1W, 3870 Lumens, 2700K warm white. CRI>90.




STEP 1 - CHOOSE YOUR METAL FINISH





MILKY WAY PENDANT INFINITY LINE 120

SIZE (UNIT: CM)



STEP 2 - CHOOSE YOUR SUSPENSION TYPE

SUSPENSION TYPE






+ STANDARD BUILTIN PHASECUT DRIVER

A. We provide a L850 canopy with a builtin LED driver with **phasecut dimming** as standard.







+ OTHER BUILTIN DRIVERS AVAILABLE ON REQUEST

B. We can also provide builtin LED drivers with **1-10 Volt, Switch / Push or DALI** dimming for L850 single linear canopy and **Phasecut, 1-10 Volt, Switch / Push, Dali** dimming for two D200 circular canopies. These dimming and canopy combinations are available in the following dimensions:











+ REMOTE DRIVERS AVAILABLE ON REQUEST

B. If your electrician can wire the LED Drivers remotely (rather than builtin to the canopy) we can provide a single L850 linear canopy or two D85 circular canopies. These dimming and canopy combinations are available as following:









Milky Way Pendant Infinity Line 180

MWPEIL180

C€ IP20 UK

Materials

Electroplated Aluminium or Hand finished brass, Cathedral glass.

Weight incl. canopy

Polished gold and nickel finished aluminium ~7.6 kg Brushed brass and blackened brass ~13.8 kg

Power Input


220-240V 50-60Hz

Light Source (included)

Strip LEDs. 70.6W, 5790 Lumens, 2700K warm white. CRI>90.

CONFIGURATION


STEP 1 - CHOOSE YOUR METAL FINISH





MILKY WAY PENDANT INFINITY LINE 180

SIZE (UNIT: CM)



STEP 2 - CHOOSE YOUR SUSPENSION TYPE

SUSPENSION TYPE





+ STANDARD BUILTIN PHASECUT DRIVER

A. We provide a L850 canopy with a builtin LED driver with **phasecut dimming** as standard.




MATCHING FINISH
PHASECUT


+ OTHER BUILTIN DRIVERS AVAILABLE ON REQUEST

B. We can also provide builtin LED drivers with **1-10 Volt, Switch / Push or DALI** dimming for L850 single linear canopy and **Phasecut, 1-10 Volt, Switch / Push, Dali** dimming for two D200 circular canopies. These dimming and canopy combinations are available in the following dimensions:









+ REMOTE DRIVERS AVAILABLE ON REQUEST

B. If your electrician can wire the LED Drivers remotely (rather than builtin to the canopy) we can provide a single L850 linear canopy or two D85 circular canopies. These dimming and canopy combinations are available as following:



