Milky Way Pendant Infinity Line 240

MWPEIL240

CE IP20

Materials

Electroplated Aluminium or Hand finished brass, Cathedral glass.

Weight incl. canopy

Polished gold and nickel finished aluminium ~12 kg Brushed brass and blackened brass ~21 kg

Power Input 220-240V 50-60Hz

Light Source (included)

Strip LEDs. 94.2W, 7720 Lumens, 2700K warm white. CRI>90.




MILKY WAY PENDANT INFINITY LINE 240

CONFIGURATION

STEP 1 - CHOOSE YOUR METAL FINISH



SIZE (UNIT: CM)



4M


10M

STEP 2 · CHOOSE YOUR SUSPENSION TYPE



Black Fabric Flex Cable	
Drop height adjustable on site:	
4 M	

10M



SUSPENSION TYPE

+ STANDARD BUILTIN PHASECUT DRIVER

A. We provide a multiple L850 canopy with a builtin LED driver with **phasecut dimming** as standard.



+ OTHER BUILTIN DRIVERS AVAILABLE ON REQUEST

B. We can also provide builtin LED drivers with 1-10 Volt, Switch / Push or DALI dimming for two L850 linear canopies and Phasecut, 1-10 Volt, Switch / Push, Dali dimming for four D200 circular canopies. These dimming and canopy combinations are available in the following dimensions:



+ REMOTE DRIVERS AVAILABLE ON REQUEST

B. If your electrician can wire the LED Drivers remotely (rather than builtin to the canopy) we can provide two L850 linear canopies or four D85 circular canopies. These dimming and canopy combinations are available as following:



Milky Way Pendant Infinity Line 360

MWPEIL360

C€ IP20 UK

Materials

Electroplated Aluminium or Hand finished brass, Cathedral glass.

Weight incl. canopy

Polished gold and nickel finished aluminium ~15.2 kg Brushed brass and blackened brass ~27.6 kg

Power Input 220-240V 50-60Hz

Light Source (included)

Strip LEDs. 141.2W, 11580 Lumens, 2700K warm white. CRI>90.




MILKY WAY PENDANT INFINITY LINE 360

CONFIGURATION

STEP 1 - CHOOSE YOUR METAL FINISH





STEP 2 - CHOOSE YOUR SUSPENSION TYPE



Black Fabric Flex Cable	
Drop height adjustable on site:	

4M 10M



White Fabric Flex Cable

Drop height adjustable on site:

> 4M 10M

SUSPENSION TYPE

+ STANDARD BUILTIN PHASECUT DRIVER

A. We provide a L850 canopy with a builtin LED driver with **phasecut dimming** as standard.



+ OTHER BUILTIN DRIVERS AVAILABLE ON REQUEST

B. We can also provide builtin LED drivers with 1-10 Volt, Switch / Push or DALI dimming for two L850 linear canopies and Phasecut, 1-10 Volt, Switch / Push, Dali dimming for four D200 circular canopies. These dimming and canopy combinations are available in the following dimensions:



+ REMOTE DRIVERS AVAILABLE ON REQUEST

B. If your electrician can wire the LED Drivers remotely (rather than builtin to the canopy) we can provide two L850 linear canopies or four D85 circular canopies. These dimming and canopy combinations are available as following:

