# Softspot Pendant

SSPE

C€ IP20 UK

Materials

Hand finished or electroplated

Weight incl. canopy

~1 kg

**Power Input** 

220-240V 50-60Hz

Light Source (included)

Proprietary Softspot75 LED, 9W, 380 Lumens, 2700K warm white. CRI>95. 75% downwards and 25% upwards




SOFTSPOT PENDANT

CONFIGURATION


### STEP 1 - CHOOSE YOUR METAL FINISH



## SIZE (UNIT: CM)



## STEP 2 - CHOOSE YOUR SUSPENSION TYPE





Cable

Drop height adjustable on site:

10M

Black Fabric Flex



White Fabric Flex Cable

Drop height adjustable on site:

4M

10M



Metal tube
Specify your Drop
height in cm to our
sales team.
No cable showing
Not adjustable on site
Min. Drop H.: 15 cm

#### + STANDARD BUILTIN PHASECUT DRIVER

A. We provide a D95 canopy with a builtin LED driver with **phasecut dimming** as standard. This dimming and canopy combination is available in the following finishes:









## + OTHER BUILTIN DRIVERS AVAILABLE ON REQUEST

B. We can also provide builtin LED drivers with **1-10 Volt, Switch / Push or DALI** dimming, if required by your electrician. These drivers are larger and require a D135 canopy. These dimming and canopy combinations are available in the following finishes:









### + REMOTE DRIVERS AVAILABLE ON REQUEST

B. If your electrician can wire the LED Drivers remotely (rather than builtin to the canopy) we can provide a D70 canopy for solid ceilings or D50 for false ceilings. These dimming and canopy combinations are available in the following finishes:



