

Softspot Wall Horizontal

SSWAHR

CE IP20 UK CA

Materials

Hand finished or electroplated brass.

Weight incl. canopy

-1 kg

Power Input

220-240V 50-60Hz

Light Source (included)

Proprietary Softspot75 LED,
9W, 380 Lumens, 2700K warm white. CRI>95.
50% downwards and 50% upwards




SOFTSPOT WALL HORIZONTAL

CONFIGURATION

STEP 1 - CHOOSE YOUR METAL FINISH



SIZE (UNIT: CM)



STEP 2 - CHOOSE YOUR CANOPY AND DRIVER

CANOPY AND DRIVER

+ STANDARD BUILTIN PHASECUT DRIVER

A. We provide a D95 canopy with a builtin LED driver with **phasecut dimming** as standard.

D95 | Ø9.5 X 4CM

MATCHING FINISH



PHASECUT

+ OTHER BUILTIN DRIVERS AVAILABLE ON REQUEST

B. We can also provide builtin LED drivers with **1-10 Volt, Switch / Push or DALI** dimming, if required by your electrician.

D135 | Ø13.5 X 4.5CM



MATCHING FINISH

1-10 VOLT


SWITCH/PUSH

DALI

+ REMOTE DRIVERS AVAILABLE ON REQUEST

B. If your electrician can wire the LED Drivers remotely (rather than builtin to the canopy) we can provide the following options:

D95 | Ø9.5 X 4CM



MATCHING FINISH

PHASECUT

1-10 VOLT

SWITCH/PUSH

DALI

Softspot Wall Vertical

SSWAVR

CE IP20 UK
CA

Materials

Hand finished or electroplated brass.

Weight incl. canopy

-1 kg

Power Input

220-240V 50-60Hz

Light Source (included)

Proprietary Softspot75 LED,
9W, 380 Lumens, 2700K warm white. CRI>95.
75% downwards and 25% upwards

Custom structure dimensions available on request




SOFTSPOT WALL VERTICAL 27


CONFIGURATION

STEP 1 - CHOOSE YOUR MODEL

MODEL (UNIT: CM)



27 FIXED BEAM



27 ORIENTABLE BEAM

STEP 2 - CHOOSE YOUR METAL FINISH

METAL FINISH



BRUSHED BRASS



BLACKENED BRASS



BRUSHED BRONZE



BRUSHED NICKEL

STEP 3 - CHOOSE YOUR CANOPY AND DRIVER

CANOPY + DRIVER

+ STANDARD BUILTIN PHASECUT DRIVER

A. We provide a D95 canopy with a builtin LED driver with **phasecut dimming** as standard.

D95 | Ø9.5 X 4CM

MATCHING FINISH




PHASECUT

+ OTHER BUILTIN DRIVERS AVAILABLE ON REQUEST

B. We can also provide builtin LED drivers with **1-10 Volt, Switch / Push or DALI** dimming, if required by your electrician.

D135 | Ø13.5 X 4.5CM



MATCHING FINISH

1-10 VOLT


SWITCH/PUSH

DALI

+ REMOTE DRIVERS AVAILABLE ON REQUEST

B. If your electrician can wire the LED Drivers remotely (rather than builtin to the canopy) we can provide the following options:

D95 | Ø9.5 X 4CM



MATCHING FINISH

PHASECUT

1-10 VOLT

SWITCH/PUSH

DALI