

B24112-100

Nimi: **Energiamittari EQ**
3-vaihe, 6A 400VAC, MID, muuntajakytketty, Modbus, teräs

Tyyppi: B24112-100
EAN: 7392696001786
Snro: 6625041

Kuvaus: 3-vaihe, 6 A, 400 VAC, virtamuuntajakytketty, tarkkuusluokka B (1), MID. Pulssi-/hälytyslähde, max 40VDC. Instrumenttiarvot: teho, jännite, virta, taajuus ja tehokerroin. 4 DIN moduulia. Käyttölämpötila -40...+70 °C. Modbus (RS485).

Pakkaus: 1
Yksikkö: KPL



ETIM

ETIM 7 EC001506 (EC001506)
ETIM 8 EC001506 (EC001506)

ETIM 8

Type of meter	Electronic
Nominal current (I _n)	1 A
Max. current (I _{max})	6 A
Nominal voltage (U _n) N-L	176 ... 276 V
Nominal voltage (U _n) L-L	400 V
Frequency	47.5 ... 63 Hz
Accuracy class	B
Pole type	Four conductor
Model	Direct measurement
Energy type	Effective power
Suitable for	Purchase
Tariff type	One-tariff
Measurement type load profile	yes
Escapement mechanism	yes
Calibrated	yes
Approval	Measuring Instruments Directive
Pulse output	Electrical
Pulse type	S0
Pulse rate	1 ... 9999 Imp/kWh (kvarh)
Type of indication	Digital
Mounting method	DRA (DIN-rail adapter)

B24112-100

Width in number of modular spacings	4
Type of interface	RS-485
EEC40 signature	no
With lock code	no
Number of positions total (counter)	7
Degree of protection (IP)	IP20