



12500 WATT 3 PHASE DIESEL GENERATOR

₩ DG12S3

Max AC output:	12500* Watts
Noise Level:	68 dBA @ 7m
Running Watts:	11000 Watts
Warranty:	2 years
Certification:	ISO9001-2000, GS, TUV, CE Approved



DESCRIPTION

i

This standby generator is the ideal product during power cuts and for heavy duty working. The auto governor generator has a steady motor speed with excellent low emission rates which in turn creates an environmentally friendly generator. The standby generator has an added bonus of having reduced noise when in use.

The heavy-duty industrial frame design provides full protection and aids portability. Fitted with automatic voltage control, which protects the unit and provides higher efficiency, allowing the long running 50ltr fuel tank to give up to 24 hours running on a full tank (based on 50% Load).

With 415v Three Phase and 240v Single Phase output sockets as standard this powerful and reliable generator is also fitted with a maintenance-free alternator. Due to the advantage of having a silent enclosure this generator has a key start facility. Smooth running is ensured via the fitting of anti-vibration mountings for minimal vibration and a soundproof canopy for reduced noise. A low oil cut out feature and fuel gauge is also featured.

*Please note: When running single phase off a three phase generator you will only receive approx 30-35% of the full output power as the socket will only be running via one of the three phases available.

- Max 12500 Watts
- 415v Three Phase / 240v AC load
- Up to 24 hours run time at 50% load
- 68 dBA at 7m
- 3 in 1 Intelli Volt Meter
- Electric key start



Max Watts	12500
Rated Watts	11000
AC Load	1 x 240V 16 Amp (UK/EU) 1 x 240V 32 Amp (UK/EU) 1 x 415V 16 Amp (UK/EU)
Frequency	50Hz
Engine	290cc Twin Cylinder, Vertical, 4 stroke, Air Cooled Direct Injection
Fuel Capacity	50 Litres
Oil Capacity	3 Litres
Noise Level	68 dBA @ 7m
Start Type	Electric Key Start
RPM	3000
Dimensions (L*W*H)	116 x 65 x 89cm
Certification	ISO9001-2000, GS, TUV & CE Approved
Weight (Kg)	295
Operation capacity (hr)	>24 Hrs @ 50% load

Please note: images may differ slightly to actual product depending on UK or EU models.