

Adventures in Homebrewing - www.HomeBrewing.org 313 - 277 - 2739 (BREW)

Bucksnort Brown

All-Gra						
	The AHA's take on Moose Drool. An American Brown that is malty sweet with hints of chocolate					Original Gravity: 1.058
	and roast.					Final Gravity: 1.014
	All Grain Recipe	•				Color SRM: 34.88
	AG99-2012					Alcohol by Volume : 5.59
Procedure : Please rea	ad all the instructions before you begin brewing, to ensure you have all the ingredients and fully understand the proces					IBU : 44.03
Clean	It is important to thoroughly clean and sanitize all of your brewing equipment. Assemble your mash tun. Add 1 quart of 180°F water for every pound of grain to be mashed (add water first). By adding water first, you will pre-heat your mash tun. Stir water until your temperature hits 170°F. It is now time to add your CRUSHED grains to the cooler. Gently dough grains in until all grain is covered by water. Place lid on and continue to Mash.					Grains : 10 lbs 2 Row Malt - Malteuro 0.5 lbs Crystal Malt (80 °L+) 0.5 lbs Crystal Malt (60 °L) 0.375 lbs Chocolate Malt 0.0625 lbs Black Patent Malt
Mash	After 10 minutes you can check your temperature. You will be between 149°F and 156°F assuming you measured your water and grains correctly. Replace lid and "Mash" for 1 hour. Start to heat your sparge water at this point. You will need enough 200°F water your expected final volume (5 gallons if you want five gallons of brew).					
Conversion	After mashing for one hour, you will want to check for conversion of starch to sugar. This will be done by placing a small amount of grain free wort on a white plate or bowl. Add one drop of "Tincture of lodine" to the wort. If it quickly disappears or stays/remains red you are ready to move on. If the iodine turns black, starch is still present. Calibrate your thermometer. Recheck the temperature of the mash. If both are accurate, do another iodine test every 20 minutes until conversion is complete.					
Sparge	Conversion is now complete. Slowly drain 1/2 gallon of wort and pour it back on top of your mash. This process (Vorlauf) is used to clear your wort. You may need to run more than 1/2 gallon. When wort is clear, sparging is your next process. Sparging is no more than rinsing the sweet wort from the grains in your mash tun. You will want to gently pour 200°F water over your grains (try to keep an inch or so of clean water on top of the grain bed). SLOWLY collect your wort from the spigot at the bottom of your mash tun. This process should take ONE HOUR. If this is rushed, your gravity will be lowtake your time!					
Boil	After ONE HOUR and you have collected enough wort, it is time to start your boil. Keep in mind you will lose approximately 15% of your boil due to evaporation. If you want five gallons of beer, start with six gallons of wort. You are now on familiar ground. You will simply add your hops as scheduled in the recipe. No need to add specialty grains, they were in your mash. Be sure to add your wort chiller to the last 15 minutes of the boil.					
Hop & Additive Schedule		Ounces	Hop/Additives	Hop Addition	Boil Time (minutes)	
			5 HBU Pack	Boil/Bittering	60	_
			oz Willamette Hop Pellets	Boil/Bittering	30	_
			oz Mt Hood Hop Pellets	Flavor	15	_
			oz Willamette Hop Pellets	Aroma	5	
	Once the 60 minute boil is over, it is time to cool the wort. There are many ways to cool a wort, the AlH recommendation is a wor chiller. Cool the wort to approximately 100° F as quickly as possible. The fermenting equipment needs to be sanitized. This can be done while the wort is cooling. Be sure to clean and sanitize the fermenters, airlock, lid, hose, hydrometer and test jar and rubber stopper. Anything that may come into contact with the wort shou be sanitary. Transfer the wort into the primary fermenting vessel, then top off with cold water until a total of 5.125 gallons is in the primary fermenter. Aerate the wort at this point. This can be accomplished with an aeration stone or simply by rocking the fermenter bac forth once the lid is in place.					
	chiller. Cool the The fermenting e fermenters, airloo be sanitary. Transfer the word fermenter. Aerat	equipment need ck, lid, hose, hy t into the prima te the wort at th	imately 100° F as quickly as po ds to be sanitized. This can be ydrometer and test jar and rubb ry fermenting vessel, then top	e done while the per stopper. Ar off with cold wa	e wort is cooling. Be su hything that may come in hter until a total of 5.125	re to clean and sanitize the nto contact with the wort should gallons is in the primary
the fermentor	chiller. Cool the The fermenting e fermenters, airloo be sanitary. Transfer the wort fermenter. Aerat forth once the lid	equipment need ck, lid, hose, hy t into the prima te the wort at the is in place.	imately 100° F as quickly as po ds to be sanitized. This can be ydrometer and test jar and rubb ry fermenting vessel, then top	done while the per stopper. Ar off with cold wa ished with an a	e wort is cooling. Be sur hything that may come in tter until a total of 5.125 eration stone or simply	re to clean and sanitize the nto contact with the wort should gallons is in the primary by rocking the fermenter back ar
and preparing the fermentor Take the reading Pitch the yeast	chiller. Cool the The fermenting e fermenters, airloo be sanitary. Transfer the word fermenter. Aerat forth once the lid This is the time th Once the wort is of the type of year	equipment need ck, lid, hose, hy t into the prima te the wort at th is in place. hat you will wa cooled to 78° f ast you have. S th water. Ferr	imately 100° F as quickly as po ds to be sanitized. This can be ydrometer and test jar and rubb ry fermenting vessel, then top his point. This can be accompl	done while the per stopper. Ar off with cold wa ished with an a ding. Use a hy Pitch according n the sanitized	e wort is cooling. Be survively thing that may come in the until a total of 5.125 eration stone or simply drometer and record the the proper procedures airlock and stopper.	re to clean and sanitize the nto contact with the wort should gallons is in the primary by rocking the fermenter back ar e reading.
the fermentor	chiller. Cool the The fermenting e fermenters, airloo be sanitary. Transfer the word fermenter. Aerat forth once the lid This is the time th Once the wort is of the type of yea Fill the airlock wit fermentation is co During the ferme	equipment need ck, lid, hose, hy t into the prima te the wort at th is in place. hat you will wa cooled to 78° f ast you have. S th water. Ferr omplete. ntation process	imately 100° F as quickly as po ds to be sanitized. This can be ydrometer and test jar and rubb ry fermenting vessel, then top nis point. This can be accompl nt to take a specific gravity rea F, it is safe to pitch the yeast. I Seal the fermenter tight. Attack	done while the per stopper. Ar off with cold wa ished with an a ding. Use a hy Pitch according n the sanitized 24 - 48 hours. "	e wort is cooling. Be sun hything that may come in heter until a total of 5.125 eration stone or simply drometer and record the the proper procedures airlock and stopper. Do Not Disturb" until	re to clean and sanitize the nto contact with the wort should gallons is in the primary by rocking the fermenter back ar e reading. Suggested Yeast: California Ale Yeast 82-001 American Ale 67-1056
the fermentor Take the reading Pitch the yeast Fermenting -	chiller. Cool the The fermenting e fermenters, airloo be sanitary. Transfer the wort fermenter. Aerat forth once the lid This is the time th Once the wort is of the type of yea Fill the airlock wit fermentation is co During the ferme instructions and the	equipment need ck, lid, hose, hy t into the prima te the wort at th is in place. hat you will wa cooled to 78° f ast you have. S th water. Ferr omplete. ntation process recommended	imately 100° F as quickly as po ds to be sanitized. This can be ydrometer and test jar and rubb ry fermenting vessel, then top his point. This can be accompl nt to take a specific gravity rea F, it is safe to pitch the yeast. I Seal the fermenter tight. Attack nentation should begin within 2 s, CO2 will begin to escape the	done while the per stopper. Ar off with cold wa ished with an a ding. Use a hy Pitch according n the sanitized 24 - 48 hours. "	e wort is cooling. Be sun hything that may come in the until a total of 5.125 eration stone or simply drometer and record the the proper procedures airlock and stopper. Do Not Disturb" until w manufacturer's pitch	re to clean and sanitize the nto contact with the wort should gallons is in the primary by rocking the fermenter back ar e reading. Suggested Yeast: California Ale Yeast 82-001 American Ale 67-1056 US-05 Safale US-05
the fermentor Take the reading Pitch the yeast Fermenting - Primary Fermenting -	chiller. Cool the The fermenting e fermenters, airloo be sanitary. Transfer the wort fermenter. Aerat forth once the lid This is the time th Once the wort is of the type of yea Fill the airlock wit fermentation is co During the ferme instructions and n Once the Primary	equipment need ck, lid, hose, hy t into the prima te the wort at the is in place. That you will wa cooled to 78° f ast you have. S the water. Ferr complete. Intation process recommended y fermentation	imately 100° F as quickly as po ds to be sanitized. This can be ydrometer and test jar and rubb ry fermenting vessel, then top his point. This can be accompl nt to take a specific gravity rea F, it is safe to pitch the yeast. I Seal the fermenter tight. Attack nentation should begin within 2 s, CO2 will begin to escape the temperature for fermentation. is complete, approximately 1 to por Additives that need to go into	done while the per stopper. Ar off with cold wa ished with an a ding. Use a hy Pitch according n the sanitized 24 - 48 hours. " e airlock. Follow	e wort is cooling. Be sun hything that may come in the until a total of 5.125 eration stone or simply drometer and record the the proper procedures airlock and stopper. Do Not Disturb" until w manufacturer's pitch	re to clean and sanitize the nto contact with the wort should gallons is in the primary by rocking the fermenter back an e reading. Suggested Yeast: California Ale Yeast 82-001 American Ale 67-1056 US-05 Safale US-05
the fermentor	chiller. Cool the The fermenting e fermenters, airloo be sanitary. Transfer the word fermenter. Aerat forth once the lid This is the time th Once the wort is of the type of yea Fill the airlock wit fermentation is co During the ferme instructions and in Once the Primary If the recipe calls be complete with	equipment need ck, lid, hose, hy t into the prima te the wort at the is in place. That you will wa cooled to 78° f ast you have. S th water. Ferr complete. Intation process recommended y fermentation	imately 100° F as quickly as po ds to be sanitized. This can be ydrometer and test jar and rubb ry fermenting vessel, then top his point. This can be accompl nt to take a specific gravity rea F, it is safe to pitch the yeast. I Seal the fermenter tight. Attack nentation should begin within 2 s, CO2 will begin to escape the temperature for fermentation. is complete, approximately 1 to pr Additives that need to go into s.	done while the per stopper. Ar off with cold wa ished with an a ding. Use a hy Pitch according n the sanitized 24 - 48 hours. " e airlock. Follow o 2 weeks, rack o the secondar	e wort is cooling. Be sur hything that may come in her until a total of 5.125 eration stone or simply drometer and record the the proper procedures airlock and stopper. Do Not Disturb" until w manufacturer's pitch the beer into the secor y, add these now. The	re to clean and sanitize the nto contact with the wort should gallons is in the primary by rocking the fermenter back ar e reading. Suggested Yeast: California Ale Yeast 82-001 American Ale 67-1056 US-05 Safale US-05
Take the reading Pitch the yeast Pimary Fermenting - Secondary	chiller. Cool the The fermenting e fermenters, airloo be sanitary. Transfer the wort fermenter. Aerat forth once the lid This is the time th Once the wort is of the type of yea Fill the airlock with fermentation is co During the ferme instructions and n Once the Primary If the recipe calls be complete with Siphon finished but	equipment need ck, lid, hose, hy t into the prima te the wort at th is in place. hat you will wa cooled to 78° f ast you have. S th water. Ferr omplete. ntation process recommended y fermentation for Dry Hops of in 1 to 2 weeks over into a bott cket, add them	imately 100° F as quickly as po ds to be sanitized. This can be ydrometer and test jar and rubb ry fermenting vessel, then top his point. This can be accompl nt to take a specific gravity rea F, it is safe to pitch the yeast. I Seal the fermenter tight. Attack nentation should begin within 2 s, CO2 will begin to escape the temperature for fermentation. is complete, approximately 1 to pr Additives that need to go into s.	done while the per stopper. Ar off with cold wa ished with an a ding. Use a hy Pitch according n the sanitized 24 - 48 hours. " e airlock. Follow o 2 weeks, rack o the secondar	e wort is cooling. Be sur hything that may come in her until a total of 5.125 eration stone or simply drometer and record the the proper procedures airlock and stopper. Do Not Disturb" until w manufacturer's pitch the beer into the secor y, add these now. The	re to clean and sanitize the nto contact with the wort should gallons is in the primary by rocking the fermenter back an e reading. Suggested Yeast: California Ale Yeast 82-001 American Ale 67-1056 US-05 Safale US-05