

Adventures in Homebrewing - www.HomeBrewing.org 313 - 277 - 2739 (BREW)

Oskar Blues Beerito Mexican Lager Clone

		a light b	odied, amber Mexican lager , featu	ring a crisp accen	t from noble hops.	Original Gravity: 1.056
						Final Gravity: 1.014
	Extract Recipe					Color SRM: 17.77
						Alcohol by Volume : 5.37
Procedure : Please read all the instructions before you begin brewing, to ensure you have all the ingredients and fully understand the process					ly understand the process.	IBU : 12.14
Clean	It is important to	thoroughly clean	and sanitize all of your brew	ing equipment.		
Steep	Begin by heating 2.5 gallons of water in your brew pot. Add speciality grains and tie a knot at one end of the "Grain Bag" leaving room for the grains to be loose in the bag. Place the Grain Bag in the water. Slowly raise the temperature to 150° to 160°F (max temp.). Steep your grains at this temperature for 20 minutes. After 20 minutes, remove the "Grain Bag" from the pot. Do not squeeze the bag, just let the liquid drain from the bag into the pot. The water is now "Wort" at this point. Grains : 5 oz Munich Malt 11b Crystal 10L 1 oz Carafa 3 6 oz Crystal Malt (20 °L) 9 oz Melanoidin					
ermentables &	Bring the "Wort" to a boil. It should be a rolling boil, but be careful to avoid a "Boil Over". Once you					
Start of Boil - Begin 60 minutes of boiling	achieved a boil, remove the brew pot from the heat source.					Fermentables :
	It is time to add the fermentables :					rementables.
						6 lbs Liquid Malt Extract Pale
	Stir the extracts, and fermentables into the wort until it has all dissolved. It is important to make sure none of the extracts or fermentables are sitting on the bottom of the brew pot, as it will scorch when					
	returned to the heat source. Return the wort to a rolling boil and follow Hop Schedule :					
lop & Additive			J. J			
Schedule		Ounces	Hop/Additives	Hop Addition	Boil Time (minutes)	
			HBU Pack	Boil/Bittering	90	_
		1/2 o	z Sterling Hop Pellets	Flavor	10	
						-
		ute boil is over, i		ere are many w	Flame Out vays to cool a wort, the A	NH recommendation is a wort
ind preparing	chiller. Cool the The fermenting e fermenters, airloo sanitary. Transfer the wort	ute boil is over, i wort to approxim quipment needs k, lid, hose, hyd into the primary e the wort at this	t is time to cool the wort. The nately 100° F as quickly as po to be sanitized. This can be rometer and test jar and rubb p fermenting vessel, then top o	ere are many w pssible. done while the per stopper. Ar	e wort is cool a wort, the A e wort is cooling. Be su nything that may come in ater until a total of 5.125	e to clean and sanitize the nto contact with the wort should b gallons is in the primary
and preparing the fermentor Take the reading	chiller. Cool the The fermenting e fermenters, airloo sanitary. Transfer the wort fermenter. Aerat forth once the lid	ute boil is over, i wort to approxim quipment needs k, lid, hose, hyd into the primary e the wort at this is in place.	t is time to cool the wort. The nately 100° F as quickly as po to be sanitized. This can be rometer and test jar and rubb p fermenting vessel, then top o	re are many w sssible. done while the ser stopper. Ar off with cold wa ished with an a	ays to cool a wort, the A e wort is cooling. Be sur hything that may come in ater until a total of 5.125 heration stone or simply	te to clean and sanitize the nto contact with the wort should b gallons is in the primary by rocking the fermenter back and
Cooling the wort and preparing the fermentor Take the reading Pitch the yeast	chiller. Cool the The fermenting e fermenters, airloo sanitary. Transfer the wort fermenter. Aerat forth once the lid This is the time th Once the wort is of the type of yea Fill the airlock wit fermentation is co During the ferme	ute boil is over, i wort to approxim quipment needs k, lid, hose, hyd into the primary e the wort at this is in place. <u>That you will want</u> cooled to 78° F, ist you have. Se th water. Ferme pomplete. Intation process,	t is time to cool the wort. The hately 100° F as quickly as po- to be sanitized. This can be rometer and test jar and rubb r fermenting vessel, then top of s point. This can be accompli- to take a specific gravity read- it is safe to pitch the yeast. F all the fermenter tight. Attack entation should begin within 2 CO2 will begin to escape the	ere are many w ossible. done while the oer stopper. Ar off with cold wa ished with an a ding. Use a hy Pitch according the sanitized 4 - 48 hours. '	e wort is cool a wort, the A e wort is cooling. Be surnything that may come in ater until a total of 5.125 teration stone or simply redrometer and record the the proper procedures airlock and stopper. "Do Not Disturb' until	te to clean and sanitize the nto contact with the wort should b gallons is in the primary by rocking the fermenter back and e reading.
and preparing he fermentor Γake the reading Pitch the yeast	chiller. Cool the The fermenting e fermenters, airloo sanitary. Transfer the wort fermenter. Aerat forth once the lid This is the time th Once the wort is of the type of yea Fill the airlock wit fermentation is co During the ferme instructions and r	ute boil is over, i wort to approxim quipment needs ck, lid, hose, hyd into the primary e the wort at this is in place. nat you will want cooled to 78° F, ist you have. Se th water. Ferme complete. ntation process, recommended te	t is time to cool the wort. The nately 100° F as quickly as po- to be sanitized. This can be rometer and test jar and rubb refermenting vessel, then top of s point. This can be accompli- to take a specific gravity read- it is safe to pitch the yeast. Fe eal the fermenter tight. Attach entation should begin within 2	ere are many w ossible. done while the er stopper. Ar off with cold wa ished with an a ding. Use a hy Pitch according the sanitized 4 - 48 hours. '	e wort is cool a wort, the A e wort is cooling. Be sur hything that may come in ater until a total of 5.125 heration stone or simply rdrometer and record the the proper procedures airlock and stopper. "Do Not Disturb' until w manufacturer's pitch	te to clean and sanitize the nto contact with the wort should b gallons is in the primary by rocking the fermenter back an e reading. Suggested Yeast : Mexican Lager Yeast 82-940 Munich Lager 67-2308 S-23 Saflager
and preparing the fermentor Take the reading	chiller. Cool the The fermenting e fermenters, airloc sanitary. Transfer the wort fermenter. Aerat forth once the lid This is the time th Once the wort is of the type of yea Fill the airlock wit fermentation is co During the ferme instructions and r Once the Primary	ute boil is over, i wort to approxim quipment needs ck, lid, hose, hyd into the primary e the wort at this is in place. nat you will want cooled to 78° F, ist you have. Se the water. Ferme complete. ntation process, recommended te y fermentation is for Dry Hops or	t is time to cool the wort. The hately 100° F as quickly as po- to be sanitized. This can be rometer and test jar and rubb r fermenting vessel, then top of s point. This can be accompli- to take a specific gravity read- it is safe to pitch the yeast. F all the fermenter tight. Attack entation should begin within 2 CO2 will begin to escape the emperature for fermentation. complete, approximately 1 to	ere are many w ossible. done while the er stopper. Ar off with cold wa ished with an a ding. Use a hy Pitch according the sanitized 4 - 48 hours. ' e airlock. Follow	e wort is cool a wort, the A e wort is cooling. Be sur hything that may come in ater until a total of 5.125 heration stone or simply rdrometer and record the the proper procedures airlock and stopper. "Do Not Disturb' until w manufacturer's pitch k the beer into the secor	te to clean and sanitize the nto contact with the wort should b gallons is in the primary by rocking the fermenter back an e reading. Suggested Yeast : Mexican Lager Yeast 82-940 Munich Lager 67-2308 S-23 Saflager
and preparing the fermentor Fake the reading Pitch the yeast Fermenting - Primary Fermenting -	chiller. Cool the The fermenting e fermenters, airloo sanitary. Transfer the wort fermenter. Aerat forth once the lid This is the time th Once the wort is of the type of yea Fill the airlock wit fermentation is co During the ferme instructions and r Once the Primary If the recipe calls complete within 1	ute boil is over, i wort to approxim quipment needs ck, lid, hose, hyd into the primary e the wort at this is in place. nat you will want cooled to 78° F, ist you have. Se th water. Ferme complete. Intation process, recommended te y fermentation is for Dry Hops or to 2 weeks.	t is time to cool the wort. The hately 100° F as quickly as po- to be sanitized. This can be rometer and test jar and rubb r fermenting vessel, then top of s point. This can be accompli- to take a specific gravity read- it is safe to pitch the yeast. F all the fermenter tight. Attack- entation should begin within 2 CO2 will begin to escape the emperature for fermentation. complete, approximately 1 to additives that need to go into	rere are many we sssible. done while the per stopper. Ar off with cold wa ished with an a ding. Use a hy Pitch according the sanitized the sanitized a airlock. Follow o 2 weeks, rack	ays to cool a wort, the A e wort is cooling. Be surnything that may come in ater until a total of 5.125 theration stone or simply advant and record the proper procedures airlock and stopper. "Do Not Disturb' until w manufacturer's pitch the beer into the secor y, add these now. The s	te to clean and sanitize the nto contact with the wort should b gallons is in the primary by rocking the fermenter back an e reading. Suggested Yeast : Mexican Lager Yeast 82-940 Munich Lager 67-2308 S-23 Saflager

Adventures in Homebrewing - www.HomeBrewing.org 313 - 277 - 2739 (BREW)