

Adventures in Homebrewing - www.HomeBrewing.org 313 - 277 - 2739 (BREW)

80 Shilling Scottish Ale

A traditional Scottish Ale, perfect for windy nights on the moor.

Original Gravity: 1.049

Final Gravity: 1.012

Color SRM: 37.48 **Extract Recipe** Alcohol by Volume: 4.69 K99-2661

Clean It is important to thoroughly clean and sanitize all of your brewing equipment.

Begin by heating 2.5 gallons of water in your brew pot. Add speciality grains and tie a knot at one Steep end of the "Grain Bag" leaving room for the grains to be loose in the bag. Place the Grain Bag in the water. Slowly raise the temperature to 150° to 160°F (max temp.). Steep your grains at this

Procedure: Please read all the instructions before you begin brewing, to ensure you have all the ingredients and fully understand the process.

temperature for 20 minutes. After 20 minutes, remove the "Grain Bag" from the pot. Do not squeeze the bag, just let the liquid drain from the bag into the pot. The water is now "Wort" at this point.

0.6875 lbs Crystal Malt (60 °L) 0.625 lbs Black Patent Malt 0.25 lbs Aromatic Malt

IBU: 19.86

Fermentables & Start of Boil -Begin 60 minutes of boiling

Bring the "Wort" to a boil. It should be a rolling boil, but be careful to avoid a "Boil Over". Once you

achieved a boil, remove the brew pot from the heat source.

It is time to add the fermentables:

Fermentables:

Grains:

6 lbs Liquid Malt Extract Pale

Stir the extracts, and fermentables into the wort until it has all dissolved. It is important to make sure none of the extracts or fermentables are sitting on the bottom of the brew pot, as it will scorch when returned to the heat source. Return the wort to a rolling boil and follow Hop Schedule:

Hop & Additive Schedule	Ounces	Hop/Additives	Hop Addition	Boil Time (minutes)
	1	oz East Kent Goldings	Boil/Bittering	60

and preparing the fermentor

Cooling the wort Once the 60 minute boil is over, it is time to cool the wort. There are many ways to cool a wort, the AIH recommendation is a wort chiller. Cool the wort to approximately 100° F as quickly as possible.

> The fermenting equipment needs to be sanitized. This can be done while the wort is cooling. Be sure to clean and sanitize the fermenters, airlock, lid, hose, hydrometer and test jar and rubber stopper. Anything that may come into contact with the wort should be sanitary.

> Transfer the wort into the primary fermenting vessel, then top off with cold water until a total of 5.125 gallons is in the primary fermenter. Aerate the wort at this point. This can be accomplished with an aeration stone or simply by rocking the fermenter back and forth once the lid is in place.

Take the reading This is the time that you will want to take a specific gravity reading. Use a hydrometer and record the reading.

Pitch the yeast

Once the wort is cooled to 78° F, it is safe to pitch the yeast. Pitch according the proper procedures of the type of yeast you have. Seal the fermenter tight. Attach the sanitized airlock and stopper. Fill the airlock with water. Fermentation should begin within 24 - 48 hours. "Do Not Disturb' until fermentation is complete.

During the fermentation process, CO2 will begin to escape the airlock. Follow manufacturer's pitch instructions and recommended temperature for fermentation.

Suggested Yeast:

(Danstar)

White Labs 028 Edinburgh Ale Yeast Wyeast 1728 Scottish Ale Yeast Nottingham Ale Yeast

Fermenting -**Primary** Fermenting -

Secondary

Bottling

Once the Primary fermentation is complete, approximately 1 to 2 weeks, rack the beer into the secondary fermenter.

If the recipe calls for Dry Hops or additives that need to go into the secondary, add these now. The Secondary Fermentation should be complete within 1 to 2 weeks.

Siphon finished beer into a bottling bucket. If the recipe calls for any Bottling Additives to be added to the bottling bucket, add them

At this point, follow bottling or kegging procedures....Cheers!

Adventures in Homebrewing - www.HomeBrewing.org 313 - 277 - 2739 (BREW)