

Adventures in Homebrewing - www.HomeBrewing.org 313 - 277 - 2739 (BREW)

## Oatmeal Stout

		F	ull bodied stout, with big caramel, c	hocolate and roas	st character.	Original Gravity: 1.068
						Final Gravity: 1.017
	Extract Recipe K99-2955					Color SRM : 70.92
						Alcohol by Volume : 6.58
Procedure : Please read all the instructions before you begin brewing, to ensure you have all the ingredients and fully understand the process						IBU: 33.17
Clean	It is important to thoroughly clean and sanitize all of your brewing equipment.					
Steep	Begin by heating 2.5 gallons of water in your brew pot. Add speciality grains and tie a knot at one end of the "Grain Bag" leaving room for the grains to be loose in the bag. Place the Grain Bag in the water. Slowly raise the temperature to 150° to 160°F (max temp.). Steep your grains at this temperature for 20 minutes. After 20 minutes, remove the "Grain Bag" from the pot. Do not squeeze the bag, just let the liquid drain from the bag into the pot. The water is now "Wort" at this point.					Grains : 1 lbs Crystal Malt (120 °L+) 1 lbs Chocolate Malt 1 lbs Roasted Barley (300) 1 lbs Flaked Oats
Fermentables & Start of Boil - Begin 60 minutes of boiling	Bring the "Wort" to a boil. It should be a rolling boil, but be careful to avoid a "Boil Over". Once you achieved a boil, remove the brew pot from the heat source. It is time to add the fermentables :					Fermentables : 7 lbs Liquid Malt Extract Pale
	Stir the extracts, and fermentables into the wort until it has all dissolved. It is important to make sure none of the extracts or fermentables are sitting on the bottom of the brew pot, as it will scorch when returned to the heat source. Return the wort to a rolling boil and follow Hop Schedule :					·
Hop & Additive Schedule		Ounces	Hop/Additives	Hop Addition	Boil Time (minutes)	
			HBU Pack	Boil/Bittering	60	
			B HBU Pack	Boil/Bittering	60	_
		1 c	z East Kent Goldings Hop Pe	Aroma	5	
and preparing the fermentor	chiller. Cool the wort to approximately 100° F as quickly as possible. The fermenting equipment needs to be sanitized. This can be done while the wort is cooling. Be sure to clean and sanitize the fermenters, airlock, lid, hose, hydrometer and test jar and rubber stopper. Anything that may come into contact with the wort should b sanitary. Transfer the wort into the primary fermenting vessel, then top off with cold water until a total of 5.125 gallons is in the primary fermenter back and forth once the lid is in place.					
	fermenters, airloo sanitary. Transfer the word fermenter. Aerat	ck, lid, hose, hyd t into the primary te the wort at this	Irometer and test jar and rubb / fermenting vessel, then top	oer stopper. Ar	nything that may come in ater until a total of 5.125	nto contact with the wort should b gallons is in the primary
Take the reading	fermenters, airloo sanitary. Transfer the word fermenter. Aerat forth once the lid	ck, lid, hose, hyd t into the primary e the wort at this is in place.	Irometer and test jar and rubb / fermenting vessel, then top	per stopper. Ar off with cold wa ished with an a	nything that may come in ater until a total of 5.125 teration stone or simply	nto contact with the wort should b gallons is in the primary by rocking the fermenter back an
•	fermenters, airloo sanitary. Transfer the word fermenter. Aerat forth once the lid This is the time the Once the wort is of the type of yea Fill the airlock wit fermentation is co	ck, lid, hose, hyd t into the primary te the wort at this is in place. hat you will want cooled to 78° F, ast you have. Se th water. Ferme omplete.	formeter and test jar and rubt of fermenting vessel, then top is point. This can be accompled to take a specific gravity real it is safe to pitch the yeast. eaal the fermenter tight. Attack entation should begin within 2	ber stopper. Ar off with cold wa ished with an a ding. Use a hy Pitch according n the sanitized 24 - 48 hours. '	hything that may come in ater until a total of 5.125 eration stone or simply drometer and record the the proper procedures airlock and stopper. "Do Not Disturb' until	nto contact with the wort should b gallons is in the primary by rocking the fermenter back an e reading.
Pitch the yeast	fermenters, airloc sanitary. Transfer the wort fermenter. Aerat forth once the lid This is the time th Once the wort is of the type of yea Fill the airlock wit fermentation is co During the ferme instructions and	ck, lid, hose, hyd t into the primary te the wort at this is in place. hat you will want cooled to 78° F, ast you have. Se th water. Ferme omplete. ntation process, recommended te	Irometer and test jar and rubt y fermenting vessel, then top s point. This can be accompl to take a specific gravity rea it is safe to pitch the yeast. eal the fermenter tight. Attack entation should begin within 2 CO2 will begin to escape the emperature for fermentation.	oer stopper. Ar off with cold wa ished with an a ding. Use a hy Pitch according h the sanitized 24 - 48 hours. ' e airlock. Folloo	hything that may come in ater until a total of 5.125 iteration stone or simply adrometer and record the proper procedures airlock and stopper. "Do Not Disturb' until w manufacturer's pitch	nto contact with the wort should b gallons is in the primary by rocking the fermenter back an e reading. Suggested Yeast : British Ale Yeast 82-005 British Ale 67-1098 S-04 Safale S-04
Pitch the yeast	fermenters, airloc sanitary. Transfer the wort fermenter. Aerat forth once the lid This is the time th Once the wort is of the type of yea Fill the airlock wit fermentation is co During the ferme instructions and	ck, lid, hose, hyd t into the primary te the wort at this is in place. hat you will want cooled to 78° F, ast you have. Se th water. Ferme omplete. ntation process, recommended te	Irometer and test jar and rubt of fermenting vessel, then top is point. This can be accomplet to take a specific gravity real it is safe to pitch the yeast. eal the fermenter tight. Attack entation should begin within 2 CO2 will begin to escape the	oer stopper. Ar off with cold wa ished with an a ding. Use a hy Pitch according h the sanitized 24 - 48 hours. ' e airlock. Folloo	hything that may come in ater until a total of 5.125 iteration stone or simply adrometer and record the proper procedures airlock and stopper. "Do Not Disturb' until w manufacturer's pitch	nto contact with the wort should b gallons is in the primary by rocking the fermenter back an e reading. Suggested Yeast : British Ale Yeast 82-005 British Ale 67-1098 S-04 Safale S-04
Pitch the yeast Fermenting - Primary Fermenting -	fermenters, airloc sanitary. Transfer the word fermenter. Aerat forth once the lid This is the time th Once the wort is of the type of yea Fill the airlock wit fermentation is co During the ferme instructions and Once the Priman	ck, lid, hose, hyd t into the primary te the wort at this is in place. hat you will want cooled to 78° F, ast you have. Se th water. Ferme omplete. ntation process, recommended te y fermentation is	Irometer and test jar and rubb y fermenting vessel, then top s point. This can be accompl to take a specific gravity rea it is safe to pitch the yeast. eal the fermenter tight. Attack entation should begin within 2 CO2 will begin to escape the emperature for fermentation.	oer stopper. Ar off with cold wa ished with an a ding. Use a hy Pitch according h the sanitized 24 - 48 hours. ' e airlock. Follow o 2 weeks, rack	hything that may come in ater until a total of 5.125 iteration stone or simply adrometer and record the proper procedures airlock and stopper. "Do Not Disturb' until w manufacturer's pitch < the beer into the secor	nto contact with the wort should b gallons is in the primary by rocking the fermenter back an e reading. Suggested Yeast : British Ale Yeast 82-005 British Ale 67-1098 S-04 Safale S-04
Take the reading Pitch the yeast Fermenting - Primary Fermenting - Secondary Bottling	fermenters, airloc sanitary. Transfer the word fermenter. Aerat forth once the lid This is the time th Once the wort is of the type of yea Fill the airlock wit fermentation is co During the ferme instructions and the Once the Primary If the recipe calls complete within 2	ck, lid, hose, hyd t into the primary te the wort at this is in place. hat you will want cooled to 78° F, ast you have. Se th water. Ferme omplete. ntation process, recommended te y fermentation is for Dry Hops or 1 to 2 weeks.	Irometer and test jar and rubb y fermenting vessel, then top s point. This can be accompl t to take a specific gravity rea it is safe to pitch the yeast. eal the fermenter tight. Attack entation should begin within 2 CO2 will begin to escape the emperature for fermentation. complete, approximately 1 to additives that need to go into	per stopper. An off with cold wa ished with an a ding. Use a hy Pitch according h the sanitized 24 - 48 hours. ' e airlock. Follow to 2 weeks, rack to the secondary	hything that may come in ater until a total of 5.125 iteration stone or simply adrometer and record the g the proper procedures airlock and stopper. "Do Not Disturb' until w manufacturer's pitch < the beer into the secor y, add these now. The s	nto contact with the wort should b gallons is in the primary by rocking the fermenter back an e reading. Suggested Yeast : British Ale Yeast 82-005 British Ale 67-1098 S-04 Safale S-04

Adventures in Homebrewing - www.HomeBrewing.org 313 - 277 - 2739 (BREW)