## SAFETY DATA SHEET (SDS)

	TA SHEET (SDS)		
Section 1. Identification			
Product identifier CHEM-PU GLOSS A			
Other means of identification CHEM-PU GLOSS; CHEM-PU GLOSS PART A			
Recommended use and restrictions on use Floor Coating			
	Quebec; Canada; H7L 6B9 info@epoxych	emtec.com	
T 450-629-1717			
<b>Emergency telephone number/restriction on use</b> Canada – CAN	UTEC 24 hour number 613-996-6666		
Section 2. Haz	zard identification		
Classification of hazardous product (name of the category or subca	tegory of the hazard class)		
Flammable liquid (Category 3)			
Skin irritation (Category 2)			
Specific target organ toxicity - single exposure (Category 3), Central n	ervous system		
Germ Cell Mutagenicity (Category 1)			
Carcinogenicity (Category 1)			
Reproductive toxicity (Category 2)			
Specific target organ toxicity - repeated exposure (Category 2)			
Hazardous to the aquatic environment - Chronic (Category 4)			
Information elements (symbols, signal words, hazard statements an	nd precautionary statements of the categor	ry/subcategory)	
Danger			
H226 Flammable liquid and vapour.			
H315 Causes skin irritation.			
H336 May cause drowsiness or dizziness.			
H340 May cause genetic defects.			
H350 May cause cancer. H360 May damage fertility or the unborn child.			
H373 May cause damage to organs through prolonged or repeated expo	Selling		
H413 May cause long lasting harmful effects to aquatic life.	sure.		
P201 Obtain special instructions before use. P202 Do not handle until a	Il safety precautions have been read and und	larstood P210 Keep away from	
heat, hot surfaces, sparks, open flames and other ignition sources. No s			
Use explosion-proof equipment. P242 Use non-sparking tools. P243 Take action to prevent static discharges. P260 Do not breathe dust/fume/gas/mist/vapours/spray. P264 Wash hands/nails/face thoroughly after handling. P270 Do not eat, drink or smoke when using this product.			
P271 Use only outdoors or in a well-ventilated area. P280 Wear gloves/protective clothing/eye protection/face protection. P304 + P340 IF			
INHALED: Remove person to fresh air and keep comfortable for breathing. P312 Call a doctor if you feel unwell. P303 + P361 + P353 IF ON			
SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P302+P352 IF ON SKIN, Wash with plenty of water for			
several minutes. P333 + P313 IF SKIN irritation or rash occurs: Get medical attention. P362+P364 Take off contaminated clothing and wash it			
before reuse. P308 + P313 IF exposed or concerned: Get medical attention. P314 Get medical attention if you feel unwell. P370 + P378 In case of			
fire: Use carbon dioxide, chemical powder agent and appropriate foam to extinguish. P273 Avoid release to the environment. P391 Collect spillage. P403 + P233 + P235 Store in a well-ventilated place. Keep container tightly closed. Keep cool. P405 Store locked up. P501 Dispose of			
contents/container into safe container in accordance with local, regional or national regulations.			
Other hazards known None	i or national regulations.		
	information on incredients		
<b>*</b>	/information on ingredients	$C_{an approx}(0/)$	
Chemical name (common name/synonyms)	CAS number or other	Concentration (%)	
1-Methoxy-2-propanol acetate	108-65-6	10-30	
2-Heptanone	110-43-0	10-30	
Xylenes/Ethylbenzene	1330-20-7/100-41-4	< 3	
Heavy naphtha hydrotreated	64742-48-9	< 1	
Dibutyltin dilaurate	77-58-7	< 0.1	
* Statement - This safety data sheet provides concentration range	ge(s) instead of the actual concentration(s) conside	ered trade secret(s).	

	Section	4. First-aid measures	
Inhalation		l keep comfortable for breathing. Call a doctor if you feel unwell.	
Ingestion		r. DO NOT INDUCE VOMITING. NEVER give anything by mouth if victim is	
ingestion	rapidly losing consciousness, or is unconscious or convulsing. Rinse mouth thoroughly with water. Have victim drink two gla		
	of water. If vomiting occurs naturally, have vi		
Skin contact		20 minutes) IF SKIN irritation or rash occurs: Get medical attention. Take off	
	contaminated clothing and wash it before reus		
Eye contact		everal minutes (15-20). Remove contact lenses, if present and easy to do. Continue	
·	rinsing. If eye irritation persists: Get medical a		
Most important	symptoms and effects (acute or delayed)	Causes skin irritation.	
Indication of im	mediate medical attention/special treatment	In all cases, call a doctor. Do not forget this document.	
	Section 5.	Fire-fighting measures	
Specific hazards	of the hazardous product (hazardous combu	stion products)	
	d other irritant/toxic gases and fumes.		
	suitable extinguishing media		
In case of fire: U	se carbon dioxide, chemical powder agent and a	ppropriate foam to extinguish.	
	ve equipment and precautions for fire-fighters		
		. Do not enter fire area without proper protection. Firefighters should wear proper	
		ull facepiece. Shield personnel to protect from venting, rupturing or bursting cans.	
Move containers	from fire area if it can be done without risk. Wate	er spray may be useful in cooling equipment and cans exposed to heat and flame.	
	Section 6. Ac	ccidental release measures	
Personal precau	tions, protective equipment and emergency p	rocedures	
		up is conducted by trained personnel only. All persons dealing with clean-up should	
wear the appropri	ate protective equipment (See Section 8).		
Methods and ma	aterials for containment and cleaning up		
Ventilate area of	release. Stop the leak if it can be done safely. C	Contain and absorb any spilled liquid concentrate with inert absorbent material, the	
place material int	o a container for later disposal (see Section 13).	Contaminated absorbent material may pose the same hazards as the spilled product	
Notify the approp	riate authorities as required.		
		. Handling and storage	
Precautions for			
	ective clothing/eye protection/face protection.		
		are operating, and that protective equipment requirements and personal hygien	
		should be properly trained regarding its hazards and its safe use. Inspect container	
		re proper ventilation. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid	
		s and flame. Avoid generating high concentrations of dusts, vapours or mists. Keep	
Section 8.	npatible materials (Section 10). Keep containers	s closed when not in use. Empty containers are always dangerous. Refer also to	
	afe storage, including any incompatibilities		
		and share lasted up Store away from incompatible materials (Section 10)	
Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Store away from incompatible materials (Section 10) Inspect all incoming containers to make sure they are properly labelled and not damaged. Storage area should be clearly identified, clear of			
	ccessible only to trained personnel. Inspect period	odically for damage or leaks.	
obstruction and a	ccessible only to trained personnel. Inspect perio Section 8. Exposu	odically for damage or leaks. re controls/Personal protection	
obstruction and a	ccessible only to trained personnel. Inspect perio Section 8. Exposu ters (biological limit values or exposure limit	odically for damage or leaks. re controls/Personal protection values and source of those values)	
obstruction and a Control parame Exposure limits:	ccessible only to trained personnel. Inspect perio Section 8. Exposu ters (biological limit values or exposure limit CAS 110-43-0 ACGIH – TLV-TWA 50 ppm; C.	bdically for damage or leaks. <b>Tre controls/Personal protection</b> <b>values and source of those values</b> ) AS 1330-20-7 ACGIH – TLV-TWA 100 ppm (STEL 150 ppm) & PEL-TWA 100	
Control parame Exposure limits: ppm; CAS 100-4	ccessible only to trained personnel. Inspect perio Section 8. Exposu ters (biological limit values or exposure limit CAS 110-43-0 ACGIH – TLV-TWA 50 ppm; C. 1-4 ACGIH – TLV-TWA 20 ppm & PEL-TWA	bdically for damage or leaks. <b>Tre controls/Personal protection</b> <b>values and source of those values</b> ) AS 1330-20-7 ACGIH – TLV-TWA 100 ppm (STEL 150 ppm) & PEL-TWA 100	
Control parame Exposure limits: ppm; CAS 100-4 Appropriate eng	ccessible only to trained personnel. Inspect perior Section 8. Exposu ters (biological limit values or exposure limit CAS 110-43-0 ACGIH – TLV-TWA 50 ppm; C. 1-4 ACGIH – TLV-TWA 20 ppm & PEL-TWA gineering controls	bdically for damage or leaks. <b>Tre controls/Personal protection</b> <b>values and source of those values</b> ) AS 1330-20-7 ACGIH – TLV-TWA 100 ppm (STEL 150 ppm) & PEL-TWA 100 100 ppm; Dust – PEL-TWA 15 mg/m <sup>3</sup> (total dust) & 5 mg/m <sup>3</sup> (respirable fraction)	
Obstruction and a Control parame Exposure limits: ppm; CAS 100-4 Appropriate eng Use under well-v	ccessible only to trained personnel. Inspect perior Section 8. Exposu ters (biological limit values or exposure limit CAS 110-43-0 ACGIH – TLV-TWA 50 ppm; C. 1-4 ACGIH – TLV-TWA 20 ppm & PEL-TWA gineering controls entilated conditions. Local exhaust ventilation sy	bdically for damage or leaks. <b>Tre controls/Personal protection</b> <b>values and source of those values</b> ) AS 1330-20-7 ACGIH – TLV-TWA 100 ppm (STEL 150 ppm) & PEL-TWA 100 100 ppm; Dust – PEL-TWA 15 mg/m <sup>3</sup> (total dust) & 5 mg/m <sup>3</sup> (respirable fraction) vstem is recommended to maintain concentrations of contaminants below exposure	
Obstruction and a Control parame Exposure limits: ppm; CAS 100-4 Appropriate eng Use under well-v limits. Make eme	ccessible only to trained personnel. Inspect perior Section 8. Exposu ters (biological limit values or exposure limit CAS 110-43-0 ACGIH – TLV-TWA 50 ppm; C. 1-4 ACGIH – TLV-TWA 20 ppm & PEL-TWA gineering controls entilated conditions. Local exhaust ventilation sy regency eyewash stations, safety/quick-drench sh	bdically for damage or leaks. <b>Tre controls/Personal protection</b> <b>values and source of those values</b> ) AS 1330-20-7 ACGIH – TLV-TWA 100 ppm (STEL 150 ppm) & PEL-TWA 100 100 ppm; Dust – PEL-TWA 15 mg/m <sup>3</sup> (total dust) & 5 mg/m <sup>3</sup> (respirable fraction) restem is recommended to maintain concentrations of contaminants below exposure nowers, and washing facilities available in work area.	
obstruction and a Control parame Exposure limits: ppm; CAS 100-4 Appropriate eng Use under well-v limits. Make eme Individual prote	ccessible only to trained personnel. Inspect perio Section 8. Exposu ters (biological limit values or exposure limit CAS 110-43-0 ACGIH – TLV-TWA 50 ppm; C. 1-4 ACGIH – TLV-TWA 20 ppm & PEL-TWA gineering controls entilated conditions. Local exhaust ventilation sy argency eyewash stations, safety/quick-drench sh ection measures/personal protective equipment	bdically for damage or leaks. <b>Tre controls/Personal protection</b> <b>values and source of those values</b> ) AS 1330-20-7 ACGIH – TLV-TWA 100 ppm (STEL 150 ppm) & PEL-TWA 100 100 ppm; Dust – PEL-TWA 15 mg/m <sup>3</sup> (total dust) & 5 mg/m <sup>3</sup> (respirable fraction) vstem is recommended to maintain concentrations of contaminants below exposur- nowers, and washing facilities available in work area. <b>t</b>	
Control parame Exposure limits: ppm; CAS 100-4 Appropriate eng Use under well-v limits. Make eme Individual prote Respiratory prote	ccessible only to trained personnel. Inspect perior Section 8. Exposu ters (biological limit values or exposure limit CAS 110-43-0 ACGIH – TLV-TWA 50 ppm; C. 1-4 ACGIH – TLV-TWA 20 ppm & PEL-TWA gineering controls entilated conditions. Local exhaust ventilation sy ergency eyewash stations, safety/quick-drench sh ection measures/personal protective equipment ection is required if the concentrations are higher	bdically for damage or leaks. <b>Tre controls/Personal protection</b> <b>values and source of those values</b> ) AS 1330-20-7 ACGIH – TLV-TWA 100 ppm (STEL 150 ppm) & PEL-TWA 100 100 ppm; Dust – PEL-TWA 15 mg/m <sup>3</sup> (total dust) & 5 mg/m <sup>3</sup> (respirable fraction) restem is recommended to maintain concentrations of contaminants below exposure nowers, and washing facilities available in work area. <b>tt</b> than the exposure limits. Use a NIOSH approved respirators if the exposure limit	
obstruction and a Control parame Exposure limits: ppm; CAS 100-4 Appropriate eng Use under well-v limits. Make eme Individual prote Respiratory prote are unknown. Ch	ccessible only to trained personnel. Inspect perior Section 8. Exposu ters (biological limit values or exposure limit CAS 110-43-0 ACGIH – TLV-TWA 50 ppm; C. 1-4 ACGIH – TLV-TWA 20 ppm & PEL-TWA gineering controls entilated conditions. Local exhaust ventilation sy ergency eyewash stations, safety/quick-drench sh ection measures/personal protective equipment ection is required if the concentrations are higher emically protective gloves (impervious), and oth	bdically for damage or leaks. <b>Tre controls/Personal protection</b> <b>values and source of those values</b> ) AS 1330-20-7 ACGIH – TLV-TWA 100 ppm (STEL 150 ppm) & PEL-TWA 100 100 ppm; Dust – PEL-TWA 15 mg/m <sup>3</sup> (total dust) & 5 mg/m <sup>3</sup> (respirable fraction) restem is recommended to maintain concentrations of contaminants below exposure nowers, and washing facilities available in work area. <b>tt</b> than the exposure limits. Use a NIOSH approved respirators if the exposure limit er protective clothing to prevent prolonged or repeated skin contact, must be work	
Control parame Exposure limits: ppm; CAS 100-4 Appropriate eng Use under well-v limits. Make eme Individual prote Respiratory prote are unknown. Ch during all handlin	ccessible only to trained personnel. Inspect perior Section 8. Exposu ters (biological limit values or exposure limit CAS 110-43-0 ACGIH – TLV-TWA 50 ppm; C. 1-4 ACGIH – TLV-TWA 20 ppm & PEL-TWA gineering controls entilated conditions. Local exhaust ventilation sy ergency eyewash stations, safety/quick-drench sh extion measures/personal protective equipment extion is required if the concentrations are higher emically protective gloves (impervious), and oth ag operations. Wear protective chemical splash g	bdically for damage or leaks. <b>Tre controls/Personal protection</b> <b>values and source of those values</b> ) AS 1330-20-7 ACGIH – TLV-TWA 100 ppm (STEL 150 ppm) & PEL-TWA 100 100 ppm; Dust – PEL-TWA 15 mg/m <sup>3</sup> (total dust) & 5 mg/m <sup>3</sup> (respirable fraction) restem is recommended to maintain concentrations of contaminants below exposure nowers, and washing facilities available in work area. <b>tt</b> than the exposure limits. Use a NIOSH approved respirators if the exposure limits er protective clothing to prevent prolonged or repeated skin contact, must be work rouggles to prevent mists from entering the eyes. Wash hands/nails/face thoroughly	
Control parame Exposure limits: ppm; CAS 100-4 Appropriate eng Use under well-v limits. Make ence Individual prote Respiratory prote are unknown. Ch during all handling. E	ccessible only to trained personnel. Inspect perior Section 8. Exposu ters (biological limit values or exposure limit CAS 110-43-0 ACGIH – TLV-TWA 50 ppm; C. 1-4 ACGIH – TLV-TWA 20 ppm & PEL-TWA gineering controls entilated conditions. Local exhaust ventilation sy ergency eyewash stations, safety/quick-drench sh extion measures/personal protective equipment extion is required if the concentrations are higher emically protective gloves (impervious), and oth ag operations. Wear protective chemical splash g	bdically for damage or leaks. <b>Tre controls/Personal protection</b> <b>values and source of those values</b> ) AS 1330-20-7 ACGIH – TLV-TWA 100 ppm (STEL 150 ppm) & PEL-TWA 100 100 ppm; Dust – PEL-TWA 15 mg/m <sup>3</sup> (total dust) & 5 mg/m <sup>3</sup> (respirable fraction) restem is recommended to maintain concentrations of contaminants below exposure nowers, and washing facilities available in work area. <b>tt</b> than the exposure limits. Use a NIOSH approved respirators if the exposure limits er protective clothing to prevent prolonged or repeated skin contact, must be work	

Section 9. Physical and chemical properties		
Appearance, physical state/colour Liquid, clear	Vapour pressure     Not available	
Odour Characteristic	Vapour density Heavier than air   Platin double 1.05 1.10 (2000)	
Odour threshold Not available   pH Not available	Relative density 1.05-1.10 (20°C)	
	Solubility Not available	
	Partition coefficient - n-octanol/water     Not available       Auto-ignition temperature     Not available	
Flash point 37°C closed cup	Decomposition temperature Not available	
Evaporation rate     Not available       Flammability (solids and gases)     Not available	Viscosity     200-600 mPa.s(20°C)       VOC     Not available	
Upper and lower flammability/explosive limits Not available	Other None known	
Section 10. Stability	and reactivity	
Reactivity	1 1	
Does not react under the recommended storage and handling conditions prescri	lbed.	
Chemical stability		
Stable under the recommended storage and handling conditions prescribed.		
Possibility of hazardous reactions		
Accumulation of flammable/explosive vapours.		
Conditions to avoid (static discharge, shock or vibration)		
Keep away from heat, hot surfaces, sparks, open flames and other ignition so	ources. No smoking. Take action to prevent static discharges.	
Incompatible materials		
Oxidizing materials; etc.		
Hazardous decomposition products		
None known		
Section 11. Toxicolog		
Information on the likely routes of exposure (inhalation, ingestion, skin a	and eye contact)	
Causes skin irritation. May cause drowsiness or dizziness. May cause genetic	c defects. May cause cancer. May damage fertility or the unborn child.	
May cause damage to organs through prolonged or repeated exposure.		
Symptoms related to the physical, chemical and toxicological characteris	stics	
Skin irritation, redness, stinging, pain; Respiratory tract irritation, coughing,	shortness of breath, dizziness, drowsiness, nausea and headaches.	
Delayed and immediate effects (chronic effects from short-term and long		
Skin Sensitization - No data available; Respiratory Sensitization - No da	ta available; Germ Cell Mutagenicity - Possible; Carcinogenicity -	
Ingredient listed by IARC, ACGIH, NTP or OSHA Reproductive Toxicity - P	ossible; Specific Target Organ Toxicity — Single Exposure – Possible;	
Specific Target Organ Toxicity - Repeated Exposure - Possible; Aspiration	Hazard - No data available; Health Hazards Not Otherwise Classified	
– No data available.		
Numerical measures of toxicity (ATE; LD50 & LC50)		
CAS 77-58-7 LD50 Oral - Rat - 175 mg/kg; CAS 110-43-0 LD50 Oral - Rat -		
20-7 LD <sub>50</sub> Oral - Rat - 3523 mg/kg; LC <sub>50</sub> Inhalation - Rat - 4 h - 5000 ppm; 0	CAS 100-41-4 LD <sub>50</sub> Oral - Rat - 3500 mg/kg; LC <sub>50</sub> Inhalation - Rat - 4	
h – 4000 ppm;		
ATE not available in this document.		
Section 12. Ecologic	al information	
<b>Ecotoxicity (aquatic and terrestrial information)</b> No data available for		
Persistence and degradability No data available		
Bioaccumulative potential No data available		
Mobility in soil No data available		
Other adverse effects May cause long lasting harmful effects to aquatic	e life.	
Section 13. Disposal		
Information on safe handling for disposal/methods of disposal/contamin		
Dispose of contents/container into safe container in accordance with local, regional or national regulations.		
Section 14. Transport information		
UN number; Proper shipping name; Class(es); Packing group (PG) of the TDG Regulations		
UN1263; PAINT; Class 3; PG III		
UN number; Proper shipping name; Class(es); Packing group (PG) of the IMDG (maritime)		
UN1263; PAINT; Class 3; PG III		
UN number; Proper shipping name; Class(es); Packing group (PG) of the IATA (air)		
UN1263; PAINT; Class 3; PG III		
	IMITED QUANTITY in accordance with TDG.	
Special precautions (transport/conveyance)May also be shipped as a LiEnvironmental hazards (IMDG or other)NoneBulk transport (usually more than 450 L in capacity)Possible	IMITED QUANTITY in accordance with TDG.	

	Section 15. Regulatory information			
Safety/health C	anadian regulations specifics Refer to Section 2 for the appropriate classification. This product has been classified in accordance			
	with the hazard criteria of the Hazardous Products Regulations (HPR).			
Environmental	Canadian regulations specifics Refer to Section 3 for ingredient(s) of the DSL			
Safety/health/er	Safety/health/environmental outside regulations specifics			
United States OSHA information: This product is regulated according to OSHA (29 CFR).				
United States EPA (Environmental Protection Agency) information: 40 CFR Refer to the ingredients listed in Section 3 & Sections 12; 13 & 14.				
United States TCSA information: Refer to the ingredients listed in Section 3.				
	Section 16. Other information			
Date of the late	Date of the latest revision of the safety data sheet March 05, 2021 version 3 (NSS ENTREPRISE INC.)			
Corrections	Complete review			
References	Safety Data Sheets from manufacturer/supplier & from Canadian Centre for Occupational Health and Safety, CCOHS.			
Abbreviations				
ACGIH	American Conference of Governmental Industrial Hygienists			
ATE	Acute toxicity estimate			
CAS	Chemical Abstract Service			
DSL	Domestic Substance List			
IARC	International Agency for Research on Cancer			
IATA	International Air Transport Association			
IMDG	International Maritime Dangerous Goods Code			
LC	Lethal concentration			
LD	Lethal Dosage			
NIOSH	National Institute for Occupational Safety and Health			
NTP	National Toxicology Program (U.S.A.)			
OSHA	Occupational Safety and Health Administration (U.S.A.)			
PEL	Permissible Exposure Limit			
STEL	Short-term Exposure Limit			
TDG	Transport of dangerous goods in Canada			
TLV	Threshold Limit Value			
TSCA	Toxic Substances Control Act			
TWA WHMIS	Time Weighted Average			
	Workplace Hazardous Materials Information System			
	To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the			
	may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are			

the only hazards that exist.