



ML-GC-5584 **LED CANOPY LIGHT**

DESCRIPTION

This new LED Garage Canopy light provides the best in class visual comfort for customers while providing great lumens performance and psychometric performance as well. It is a great choice for customers who are looking to change from the traditional HID lights.



Specification Features



LISTING

UL and CUL listed for wet locations

OPTIONS

Optional 347V with adder

Optional clamp band and flat glass with adder

HOUSING

Superior heavy duty die cast aluminum construction
aluminum reflector top housing

Ordering information





Model No.	Nomina Watts	Input Voltage	CRI	Color Temp	Option	Finish	Starting Temp
ML-GC-5584-70WT-4K-UV	20/40/55/70W	120-277V	70+	4000K	10kv Surge Occupancy Sensor Photocontrol Smart Controller	Bronze White	-40 °C

* DISCLAIMER: This test report was produced in accordance with IES LM-79 photometric testing protocol for luminaires, using a single representative test fixture. Actual production units may vary from the values reported here by up to ±10%.

Product Description



Product Dimensions



Performance Data

Model No.	Nominal Watts	Lumens	Efficacy
ML-GC-5584-70WT-4K-UV	20/40/55/70W	9230 lm	132 lm/w

* DISCLAIMER: This test report was produced in accordance with IES LM-79 photometric testing protocol for luminaires, using a single representative test fixture. Actual production units may vary from the values reported here by up to ±10%.