

+44 (0)1928 599910

 sales@aquabond.co.uk Unit
5a Christleton Court Manor Park, Runcorn Cheshire, WA7 1ST

AB100 ECO - Gloss Product Information

General

'AB100 ECO Gloss' is a plasticiser free 100 micron white gloss top-coated polypropylene film with a grey permanent adhesive, and protected by a moisture stable stay-flat 140gsm PE Kraft liner. AB100 ECO is suitable for indoor and outdoor sign and display graphics.

Suitable for printing with with HP Latex and UV Inks.

Product is suitable for

- POS/General Signage
- Exhibition/Events
- Smooth surfaces
- Suitable for Over-Lamination
- HP Latex and UV Ink-Jet

Product Benefits are

- PVC-Free
- High quality Prints
- Vibrant colour performance
- High gloss finish
- + Good adhesion on a wide variety of substrates
- 4 year outdoor life depending on substrate
- Excellent dimensional stability
- Stay-flat liner

Product Features and Performance Data

This product has a 12 month shelf Life

Standard Sizes

Width: 1370mm

Length: 50m

Core Size: 3"

Face Material	White Gloss Polypropylene	100 μ m ± 10 Overall Thickness 310 μ m ± 10
Adhesive	Permanent Grey Acrylic	30 μm ± 2
Liner	PE Kraft	180 μm ± 10
Application temperature	10°C to 40°C	
Loop Tack/Initial Grab	15N/25mm	FTM9
Adhesive Data 23°C Peel 24H on glass	17N/25mm	FTM1



This information is given as a guideline and due to the wide variation in surface to which this product may be applied the end user MUST carry out suitable testing to satisfy themselves as to satisfactory performance. Due to the wide variation in potential surfaces Aquabond cannot accept any responsibility for the adhesive performance in the event of adhesion failure. It is the user responsibility to determine by prior testing the products suitability for the intended surface.

www.aquabond.co.uk