

Technical Specification



Simply Banner 440gsm Matt Laminated Frontlit

Item	Unit	Value	Test Method
Base Fabric	Denier	300 D x 500 D	Domestic yarn 100 percent PES
Construction	Weaving/inch	18 x 12	/
Weight of Fabric	Gsm/m ²	55+/- 5	DIN53352 BS3424 Method 5B
Weight of PVC	Gsm/m ²	385+/- 5%	DIN53352 BS3424 Method 5B
Total Weight	Gsm/m ²	440+/- 10	DIN53352 BS3424 Method 5A
Thickness	mm	0.34 +/-0.02	DIN EN ISO 2286-3
Width	cm	102-320	/
Tensile Strength	N/5cm	Warp 635 Weft 450	DIN53352 BS3424
Tearing Strength	N	Warp 125 Weft 107	DIN53356 BS3424
Adhesion	N/5cm	60	DIN53357 BS3425 Method 9B
Temperature Resistance	°C	-20~70	DIN53357 BS3425 Method 10
Flammability	Not Fire Rated as Standard		

Published information concerning Pyramid products is based upon research which the Company believes to be reliable although such information does not constitute a warranty.

Because of the variety of uses of Pyramid products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages.

All specifications are subject to change without prior notice.