

klöckner pentaplast

Pyramid Display Materials Ltd. Unit 5,Clarence Avenue Westpoint Ent Park,Trafford Park M17 1QS Manchester Great Britain

22.03.2023

Fire behaviour of products from rigid PVC

Pentaprint® PVC PR-M180/25-51/8800-674DC-ZZZ

Rigid PVC films and sheets are not spontaneous combustible and they are self-extinguishing outside the flame.

In our experiences the above mentioned rigid PVC products meet the fire classifications

- B2 acc. to the German standard DIN 4102,
- M3 acc. to the French standard NFP 92 501,
- **UL 94VTM-0** (thickness \leq 500 µm) or **UL 94V-0** (thickness > 500 µm) US-standard.

The above mentioned materials were not tested according to these methods. The details are based solely upon our experiences and therefore they do not absolve from tests by the user.

Yours sincerely, Klöckner Pentaplast Europe GmbH & Co. KG

i.V.

Michael Zuntner Group Regulatory Affairs and Material Technology Lead Pharma, Health & Protection and Durables

9. floghe - the i.A.

Michaela Glomptner-Hofmann Regulatory Affairs Expert Pharma, Health & Protection and Durables

Klöckner Pentaplast Group Europe: P.O. 1165, 56401 Montabaur Industriestraße 3-5, 56412 Heiligenroth Germany Phone: +49 2602 915-0 Fax: +49 2602 915-297 www.kpfilms.com kpinfo@kpfilms.com

Klöckner Pentaplast Group Americas: 3585 Klöckner Road Gordonsville, VA 22942 USA Phone: +1.540.832.3600 Fax: +1.540.832.5656 www.kpfilms.com kpainfo@kpfilms.com

Version: 00/21.02.2019 T:\MTE\Dokumente\BESCHEIN\BRAND\B2-M3-UL-PVC ohne Zert_E.docx

Klöckner Pentaplast Group Asia: 12 Xia Sheng Road Suzhou Industrial Park Suzhou 215126, P.R. China Phone: +86.(0).512.6260.9991 Fax: +86.(0).512.6260.9992 www.kpfilms.com kpinfo-CN@kpfilms.com