



Pyramid Display Materials Ltd.
Unit 5, Clarence Avenue
Westpoint Ent Park, Trafford Park
M17 1QS Manchester
Great Britain

20.03.2023

Fire behaviour of products from rigid PVC

Pentaprint® PVC PR-M180/09-09/9200-482D8-ZZZ
Pentaprint® PVC PR-M419/58-05/9450-493D0-ZZZ

Rigid PVC films and sheets are not spontaneous combustible and they are self-extinguishing outside the flame.

In our experiences the above mentioned rigid PVC products meet the fire classifications

- **B2** acc. to the German standard DIN 4102,
- **M3** acc. to the French standard NFP 92 501,
- **UL 94VTM-0** (thickness $\leq 500 \mu\text{m}$) or **UL 94V-0** (thickness $> 500 \mu\text{m}$) - US-standard.

The above mentioned materials were not tested according to these methods. The details are based solely upon our experiences and therefore they do not absolve from tests by the user.

Yours sincerely,
Klöckner Pentaplast Europe GmbH & Co. KG

i.V.
Michael Zuntner
Group Regulatory Affairs and Material
Technology Lead
Pharma, Health & Protection and Durables

i.A.
Michaela Glomptner-Hofmann
Regulatory Affairs Expert
Pharma, Health & Protection and Durables