

## ECO 60 - Gloss

### Product Information

#### General

'ECO 60 Gloss' is a plasticiser free 60 micron white gloss top-coated polypropylene film with a grey permanent adhesive, and protected by a 135gsm PE coated 'air flow' liner for easy installations. ECO 60 Gloss is suitable for indoor and outdoor sign and display graphics.

Suitable for printing with with HP Latex and UV Inks.

#### Product is suitable for

- POS/General Signage
- Exhibition/Events
- Smooth surfaces
- Suitable for Over-Lamination
- HP Latex and UV Ink-Jet

#### Product Benefits are

- PVC-Free
- High quality Prints
- Vibrant colour performance
- High gloss finish
- Good adhesion on a wide variety of substrates
- 4 year outdoor life depending on substrate
- Excellent dimensional stability
- Stay-flat 'air flow' liner

#### Standard Sizes

**Width:** 1370mm

**Length:** 50m

**Core Size:** 3"

**Advisory:** Mounting to PVC substrates can cause the adhesive to transfer residue **Pyramid advise to test compatibility prior to installation**

#### Product Features and Performance Data

This product has a 12 month shelf Life

Face Material	White Gloss Polypropylene	60 $\mu\text{m} \pm 10$ Overall Thickness 260 $\mu\text{m} \pm 10$
Adhesive	Permanent Grey Acrylic	30 $\mu\text{m} \pm 2$
Liner	Structured Air Release	170 $\mu\text{m} \pm 10$
Application temperature	10°C to 40°C	
Loop Tack/Initial Grab	15N/25mm	FTM9
Adhesive Data 23°C Peel 24H on glass	17N/25mm	FTM1



Part of the  
GRIMCO Family

This information is given as a guideline and due to the wide variation in surface to which this product may be applied the end user MUST carry out suitable testing to satisfy themselves as to satisfactory performance. Due to the wide variation in potential surfaces Pyramid cannot accept any responsibility for the adhesive performance in the event of adhesion failure. It is the user responsibility to determine by prior testing the products suitability for the intended surface.