


CANOE TRANSPORT BOAT 10M Ref: BTE33BURS/L

Description

Canoe-type utility boat for use in rivers and lagoons. The hull design allows a high load capacity and efficiency in the displacement. The boat is designed and built with materials endorsed by the Colombian technical standard (NTC-ISO-12215).

Technical Specifications

L.O.A.	10 m.	32,8'
B.O.A.	1.6 m.	5,25'
H.O.A.	0,55 m.	1,8'
Load	*1.500 kg.	3,306 Lb.
Мах. Нр.		**40 HP
Approx. weight	325 kg.	716.5 Lb.
Transom height	0.38 m.	15''
	0.51 m.	20"



^{*}The payload is made up of: engines, batteries, removable accessories, people and general cargo.

Standard Features

6 F.R.P. Rib frames.

1 F.R.P. Pilot bench.

1 F.R.P. Bow Deck.

1 Stern Tabique.

1 Aluminum transom protector.

1 F.R.P. Transom Protector.

1 1 ¼ drain plug.

3 3/8" stainless steel eyebolts.

Optional accessories

1 F.R.P. Removeable bench and supports.

16" Plastic cleats.

1 Name of boat per letter (Set of 2 letters).

1 Polyethylene Rubrail without aluminum insert.

•Built under ICONTEC standard norm NTC-ISO-12215

Warranty

12-month warranty for sports use (intended for recreational use or personal enjoyment, not for commercial purposes).

6-month warranty for commercial use (all those other than sports). *

Get in touch with a commercial adviser to know the conditions of the guarantee, availability of technical service and spare parts.

* The warranty validity period starts from the date the equipment is delivered and activated to the first owner / Final client.

Structural calculation under NTC ISO 12215 Manufacturing certified under ISO 9001: 2015 Certified manufacturing under BASC V5 standard

Eduardoño S.A.S can make improvements and/or Updates of its products and its technical sheet.





^{*}Maximum HP based on Yamaha 4-Stroke Outboard engines.