

SAFETY JOGGER

PROFESSIONAL

Heavy

BESTLIGHT1 OB

Ultra-light, universal clog

Upper	Expanded EVA
Footbed	SJ Basic 2
Outsole	EVA/Rubber
Safety standard	OB / SRC
Size range	EU 35-47 / UK 3.0-12.0 US 3.0-13.0 / CM 23.0-31.0
Sample weight	0.197 kg
Norms	EN ISO 20347:2012



BLK



WHT



Chemically & UV sterilizable
This shoe is chemically and UV sterilizable.



Washable 30°C
These shoes can be washed in a washing machine at 30°C.

SAFETY
JOGGER
WORKS

Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED
IN EUROPE

www.safetyjogger.com

Industries:

Catering, Chemical, Cleaning, Food & beverages, Medical

Environments:

Dry environment, Extreme slippery surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	Expanded EVA			
	Upper: permeability to water vapor	mg/cm ² /h	N/A	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	N/A	≥ 15
Footbed	SJ Basic 2			
	Footbed: abrasion resistance	cycles	N/A	≥ 400
Outsole	EVA/Rubber			
	Outsole abrasion resistance (volume loss)	mm ³	83.0	≤ 150
	Outsole slip resistance SRA: heel	friction	0.45	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.46	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.22	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.32	≥ 0.18
	Antistatic value	MegaOhm	N/A	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
Heel energy absorption	J	N/A	≥ 20	

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.