

# SAFETY JOGGER

PROFESSIONAL

Medium

## DUBLIN 02

breathable uniform shoe for professionals

Upper	Nappa Leather
Lining	Microsuede
Footbed	SJ foam footbed
Outsole	PU/Rubber
Safety standard	O2 / SRC
Size range	EU 39-47 / UK 6.0-12.0 US 6.5-13.0 / CM 25.5-31.0
Sample weight	0.429 kg
Norms	EN ISO 20347:2012 ASTM F2892:2018



BLK




### Removable insole

Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.



### Breathable leather upper

Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.



### Oxygrip / SJ Grip

Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.



### SJ Foam

Removable comfortable antistatic footbed providing fit, guidance and optimum shock absorption in heel and forefoot. Breathable and moisture absorbing.



### SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.

SAFETY JOGGER WORKS

Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

ENGINEERED IN EUROPE

www.safetyjogger.com

**Industries:**

Catering, Food &amp; beverages, Industry

**Environments:**

Dry environment, Wet environment

**Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
<b>Upper</b>	<b>Nappa Leather</b>			
	Upper: permeability to water vapor	mg/cm <sup>2</sup> /h	2.3	≥ 0.8
	Upper: water vapor coefficient	mg/cm <sup>2</sup>	20.3	≥ 15
<b>Lining</b>	<b>Microsuede</b>			
	Lining: permeability to water vapor	mg/cm <sup>2</sup> /h	55.9	≥ 2
	Lining: water vapor coefficient	mg/cm <sup>2</sup>	447.4	≥ 20
<b>Footbed</b>	<b>SJ foam footbed</b>			
	Footbed: abrasion resistance	cycles	400	≥ 400
<b>Outsole</b>	<b>PU/Rubber</b>			
	Outsole abrasion resistance (volume loss)	mm <sup>3</sup>	88.9	≤ 150
	Outsole slip resistance SRA: heel	friction	0.49	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.41	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.32	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.37	≥ 0.18
	Antistatic value	MegaOhm	17.2	0.1 - 1000
	ESD value	MegaOhm	NA	0.1 - 100
	Heel energy absorption	J	41.6	≥ 20

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.