



Medium

## DUNE OB

### High-cut all round desert boot

Dune is a comfortable and robust boot which forms an essential part of the equipment of soldiers on active duty. It adapts to the natural shape of your feet and ensures that you remain feeling fresh and comfortable, even after a long march. The outsole guarantees a firm foothold on surfaces such as sand, stones, snow or mud. This keeps your feet pleasantly cool on long working days.

Upper	Textile, Waterproof Suede
Lining	Mesh
Footbed	EVA
Outsole	Rubber
Safety standard	OB / SRA, FO, HRO
Size range	EU 38-47 / UK 5.0-12.0 US 5.5-13.0 / CM 25.0-31.0
Sample weight	0.650 kg
Norms	EN ISO 20347:2012



SND



#### Breathable upper

Increased moisture and temperature management for extended wearer comfort.



#### Antistatic

Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm



#### SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.

**Industries:**

Tactical

**Environments:**

Dry environment, Uneven surfaces

**Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
<b>Upper</b>	<b>Textile, Waterproof Suede</b>			
	Upper: permeability to water vapor	mg/cm <sup>2</sup> /h	6.0	≥ 0.8
	Upper: water vapor coefficient	mg/cm <sup>2</sup>	51	≥ 15
<b>Lining</b>	<b>Mesh</b>			
	Lining: permeability to water vapor	mg/cm <sup>2</sup> /h	49.6	≥ 2
	Lining: water vapor coefficient	mg/cm <sup>2</sup>	397	≥ 20
<b>Footbed</b>	<b>EVA</b>			
	Footbed: abrasion resistance	cycles	400	≥ 400
<b>Outsole</b>	<b>Rubber</b>			
	Outsole abrasion resistance (volume loss)	mm <sup>3</sup>	89	≤ 150
	Outsole slip resistance SRA: heel	friction	0.36	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.38	≥ 0.32
	Outsole slip resistance SRB: heel	friction	NA	≥ 0.13
	Outsole slip resistance SRB: flat	friction	NA	≥ 0.18
	Antistatic value	MegaOhm	NA	0.1 - 1000
	ESD value	MegaOhm	NA	0.1 - 100
Heel energy absorption	J	NA	≥ 20	

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.