



Heavy

## POSEIDON S4

Safety boot with PVC outsole

Upper	SJ PVC
Lining	Tricot
Footbed	N/A
Midsole	N/A
Outsole	PVC
Toecap	Steel
Safety standard	S4 / SRA
Size range	EU 36-47 / UK 3.5-12.0 US 4.0-13.0 / CM 23.5-31.0
Sample weight	1.040 kg
Norms	EN ISO 20345:2011 ASTM F2413:2018



WHT



### Oil & fuel resistant

The outsole is resistant against oil and fuel.



### Heel energy absorption

Heel energy absorption reduces the impact of jumps or running on the body of the wearer.



### Steel toecap

Robust metal support to protect the feet of the wearer against falling or rolling objects.



### Waterproof materials

Waterproof materials make you capable of escorting patients into the shower in a safe and hygienic way.



### Antistatic

Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm



### SRA slip resistance

Slip resistance is one of the most important features of safety and occupational footwear. SRA slip resistant soles are tested on a ceramic tile with dilute soap solution.

**Industries:**

Catering, Cleaning, Construction, Food &amp; beverages, Industry

**Environments:**

Dry environment, Uneven surfaces, Wet environment

**Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
<b>Upper</b>	<b>SJ PVC</b>			
	Upper: permeability to water vapor	mg/cm <sup>2</sup> /h	NA	≥ 0.8
	Upper: water vapor coefficient	mg/cm <sup>2</sup>	NA	≥ 15
<b>Lining</b>	<b>Tricot</b>			
	Lining: permeability to water vapor	mg/cm <sup>2</sup> /h	NA	≥ 2
	Lining: water vapor coefficient	mg/cm <sup>2</sup>	NA	≥ 20
<b>Footbed</b>	<b>N/A</b>			
	Footbed: abrasion resistance	cycles	NA	≥ 400
<b>Outsole</b>	<b>PVC</b>			
	Outsole abrasion resistance (volume loss)	mm <sup>3</sup>	196.3	≤ 150
	Outsole slip resistance SRA: heel	friction	0.40	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.40	≥ 0.32
	Outsole slip resistance SRB: heel	friction	NA	≥ 0.13
	Outsole slip resistance SRB: flat	friction	NA	≥ 0.18
	Antistatic value	MegaOhm	43.1	0.1 - 1000
	ESD value	MegaOhm	NA	0.1 - 100
	Heel energy absorption	J	21	≥ 20
<b>Toecap</b>	<b>Steel</b>			
	Impact resistance toecap (clearance after impact 100J)	mm	NA	NA
	Compression resistance toecap (clearance after compression 10kN)	mm	NA	NA
	Impact resistance toecap (clearance after impact 200J)	mm	23.0	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	22.5	≥ 14

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.