



Light

ROCKET81 S1P

Low-cut safety shoe with zone traction and tripguard

Upper	Nubuck Action Leather
Footbed	SJ foam footbed
Midsole	Anti-puncture Textile
Outsole	Phylon
Toecap	Composite
Safety standard	S1P / HRO, SRC
Size range	EU 37-48 / UK 4.0-13.0 US 4.5-13.5 / CM 24.0-31.5
Sample weight	0.590 kg
Norms	EN ISO 20345:2011 ASTM F2413:2018



BLK




Shoes For Crews

Shoes For Crews safety and occupational footwear provides enhanced traction, slip resistance when walking on different slippery surfaces and much more.



Antistatic

Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm



Metal free

Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.



S1P

You work in dry environments, no risk of water/liquid sprays, and you need protection for your toes, protection against perforation, and a good breathability? Then you need S1P safety footwear.



SRC slip resistance

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.

Industries:

Automotive, Catering, Cleaning, Food & beverages, Industry

Environments:

Dry environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Nubuck Action Leather			
	Upper: permeability to water vapor	mg/cm ² /h	3.6	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	33.2	≥ 15
Footbed	SJ foam footbed			
	Footbed: abrasion resistance	cycles	400	≥ 400
Outsole	Phylon			
	Outsole abrasion resistance (volume loss)	mm ³	92.7	≤ 150
	Outsole slip resistance SRA: heel	friction	0.48	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.48	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.41	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.46	≥ 0.18
	Antistatic value	MegaOhm	66.7	0.1 - 1000
	ESD value	MegaOhm	NA	0.1 - 100
	Heel energy absorption	J	35	≥ 20
Toecap	Composite			
	Impact resistance toecap (clearance after impact 100J)	mm	NA	NA
	Compression resistance toecap (clearance after compression 10kN)	mm	NA	NA
	Impact resistance toecap (clearance after impact 200J)	mm	18.5	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	21.5	≥ 14

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.