



Heavy

## SMOOTH OB

Closed model with great comfort

Upper	Expanded EVA
Lining	N/A
Footbed	N/A
Outsole	EVA/Rubber
Safety standard	OB / ESD, A, E, SRC
Size range	EU 35-10H / UK 3.0 US 3.0 / CM 23.0
Sample weight	0.220 kg
Norms	EN ISO 20347:2012 ASTM F2892:2018



WHT



BLK



EBL



EGN



FUX



LIC



NAV



### Chemically & UV sterilizeable

This shoe is chemically and UV sterilizeable.



### Washable 30°C

These shoes can be washed in a washing machine at 30°C.



### Waterproof materials

Waterproof materials make you capable of escorting patients into the shower in a safe and hygienic way.



### Electrostatic Discharge (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.

**Industries:**

Catering, Cleaning, Food &amp; beverages

**Environments:**

Dry environment, Extreme slippery surfaces, Wet environment

**Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
<b>Upper</b>	<b>Expanded EVA</b>			
	Upper: permeability to water vapor	mg/cm <sup>2</sup> /h	N/A	≥ 0.8
	Upper: water vapor coefficient	mg/cm <sup>2</sup>	N/A	≥ 15
<b>Lining</b>	<b>N/A</b>			
	Lining: permeability to water vapor	mg/cm <sup>2</sup> /h	N/A	≥ 2
	Lining: water vapor coefficient	mg/cm <sup>2</sup>	N/A	≥ 20
<b>Footbed</b>	<b>N/A</b>			
	Footbed: abrasion resistance	cycles	N/A	≥ 400
<b>Outsole</b>	<b>EVA/Rubber</b>			
	Outsole abrasion resistance (volume loss)	mm <sup>3</sup>	145	≤ 150
	Outsole slip resistance SRA: heel	friction	0.44	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.51	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.16	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.22	≥ 0.18
	Antistatic value	MegaOhm	158	0.1 - 1000
	ESD value	MegaOhm	1.3	0.1 - 100
	Heel energy absorption	J	39	≥ 20

Sample size: 38

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.