

# Medium

# TACTIC DB

### Mid-cut allround tactical boot

High-cut allround tactical leather boot made for tactical purposes. With it's 562 grams it's an extreme lightweight tactical boot.

Upper	Nappa Action Leather
Lining	Mesh
Footbed	SJ foam footbed
Outsole	Rubber
Safety standard	OB / FO, HRO, SRA
Size range	EU 36-47 / UK 3.5-12.0 US 4.0-13.0 / CM 23.5-31.0
Sample weight	0.632 kg
Norms	EN ISO 20347:2012
∰ C€	





#### Oil & fuel resistant

The outsole is resistant against oil and fuel.



Heat resistant outsole (HRO) The outsole resists high temperatures up to 300°C.



#### Breathable leather upper

Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.



SRA slip resistance

Slip resistance is one of the most important features of safety and occupational footwear. SRA slip resistant soles are tested on a ceramic tile with dilute soap solution.



# Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP



### Industries:

Tactical, Uniform

#### **Environments:**

Muddy environment, Uneven surfaces

### **Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347		
Upper	Nappa Action Leather					
	Upper: permeability to water vapor	mg/cm²/h	4.5	≥ 0.8		
	Upper: water vapor coefficient	mg/cm²	35	≥ 15		
Lining	Mesh					
	Lining: permeability to water vapor	mg/cm²/h	45	≥ 2		
	Lining: water vapor coefficient	mg/cm²	350	≥ 20		
Footbed	SJ foam footbed					
	Footbed: abrasion resistance	cycles	400	≥ 400		
Outsole	Rubber					
	Outsole abrasion resistance (volume loss)	mm³	85	≤ 150		
	Outsole slip resistance SRA: heel	friction	0.28	≥ 0.28		
	Outsole slip resistance SRA: flat	friction	0.32	≥ 0.32		
	Outsole slip resistance SRB: heel	friction	N/A	≥ 0.13		
	Outsole slip resistance SRB: flat	friction	N/A	≥ 0.18		
	Antistatic value	MegaOhm	N/A	0.1 - 1000		
	ESD value	MegaOhm	N/A	0.1 - 100		
	Heel energy absorption	J	N/A	≥ 20		

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.



# Solutions for every workplace

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

