



Light


TURBO S3

Fashionable low-cut safety shoe for active professionals

| | |
|-----------------|--|
| Upper | Nubuck Action Leather |
| Lining | 3D-Mesh |
| Footbed | SJ foam footbed |
| Midsole | Anti-puncture Textile |
| Outsole | PU/Rubber |
| Toecap | Composite |
| Safety standard | S3 / HRO, SRC |
| Size range | EU 35-47 / UK 3.0-12.0 US 3.0-13.0 / CM 23.0-31.0 |
| Sample weight | 0.600 kg |
| Norms | EN ISO 20345:2011 ASTM F2413:2018 |



094



Heat resistant outsole (HRO)
The outsole resists high temperatures up to 300°C.



Composite toecap
Metalfree and lightweight, no thermal or electrical conductivity



Antistatic
Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm



SJ Flex
Metalfree puncture resistant material, which is lighter and more flexible than steel. The material is not thermal conductive. Covers 100% of the surface of the last bottom.



S3
S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.



SRC slip resistance
Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.

Industries:

Automotive, Cleaning, Construction, Logistics, Industry

Environments:

Dry environment, Warm surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20345 |
|----------------|--|-----------------------|--------|--------------|
| Upper | Nubuck Action Leather | | | |
| | Upper: permeability to water vapor | mg/cm ² /h | 3.9 | ≥ 0.8 |
| | Upper: water vapor coefficient | mg/cm ² | 38.4 | ≥ 15 |
| Lining | 3D-Mesh | | | |
| | Lining: permeability to water vapor | mg/cm ² /h | 50.8 | ≥ 2 |
| | Lining: water vapor coefficient | mg/cm ² | 406.9 | ≥ 20 |
| Footbed | SJ foam footbed | | | |
| | Footbed: abrasion resistance | cycles | 400 | ≥ 400 |
| Outsole | PU/Rubber | | | |
| | Outsole abrasion resistance (volume loss) | mm ³ | 40 | ≤ 150 |
| | Outsole slip resistance SRA: heel | friction | 0.53 | ≥ 0.28 |
| | Outsole slip resistance SRA: flat | friction | 0.50 | ≥ 0.32 |
| | Outsole slip resistance SRB: heel | friction | 0.14 | ≥ 0.13 |
| | Outsole slip resistance SRB: flat | friction | 0.18 | ≥ 0.18 |
| | Antistatic value | MegaOhm | 0.32 | 0.1 - 1000 |
| | ESD value | MegaOhm | NA | 0.1 - 100 |
| | Heel energy absorption | J | 30 | ≥ 20 |
| Toecap | Composite | | | |
| | Impact resistance toecap (clearance after impact 100J) | mm | NA | NA |
| | Compression resistance toecap (clearance after compression 10kN) | mm | NA | NA |
| | Impact resistance toecap (clearance after impact 200J) | mm | 17.5 | ≥ 14 |
| | Compression resistance toecap (clearance after compression 15kN) | mm | 21.5 | ≥ 14 |

Sample size: 41

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.