



Heavy


## ULTIMA S3

Heavy duty mid-cut safety shoe with Coolmax® lining

Upper	Pull-up Leather
Lining	Mesh
Footbed	SJ foam footbed
Midsole	Anti-puncture Textile
Outsole	PU, Rubber
Safety standard	S3 / ESD, HRO, SRC
Size range	EU 37-48 / UK 4.0-13.0 US 4.5-13.5 / CM 24.0-31.5
Sample weight	0.870 kg
Norms	EN ISO 20345:2011 ASTM F2413:2018



053



**Heat resistant outsole (HRO)**  
The outsole resists high temperatures up to 300°C.



**Composite toecap**  
Metalfree and lightweight, no thermal or electrical conductivity



**S3**  
S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.



**SRC slip resistance**  
Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



**Electrostatic Discharge (ESD)**  
ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.

**Industries:**

Automotive, Chemical, Construction, Logistics, Mining, Oil & Gas, Industry, Tactical

**Environments:**

Muddy environment, Uneven surfaces, Warm surfaces, Wet environment

**Maintenance instructions:**

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
<b>Upper</b>	<b>Pull-up Leather</b>			
	Upper: permeability to water vapor	mg/cm <sup>2</sup> /h	5.2	≥ 0.8
	Upper: water vapor coefficient	mg/cm <sup>2</sup>	44.5	≥ 15
<b>Lining</b>	<b>Mesh</b>			
	Lining: permeability to water vapor	mg/cm <sup>2</sup> /h	57.2	≥ 2
	Lining: water vapor coefficient	mg/cm <sup>2</sup>	458.3	≥ 20
<b>Footbed</b>	<b>SJ foam footbed</b>			
	Footbed: abrasion resistance	cycles	400	≥ 400
<b>Outsole</b>	<b>PU, Rubber</b>			
	Outsole abrasion resistance (volume loss)	mm <sup>3</sup>	122.5	≤ 150
	Outsole slip resistance SRA: heel	friction	0.30	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.33	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.17	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.23	≥ 0.18
	Antistatic value	MegaOhm	NA	0.1 - 1000
	ESD value	MegaOhm	16.7	0.1 - 100
	Heel energy absorption	J	46	≥ 20

Sample size: 41

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.