## **Emergency Tank Shower 1400L with Single Piece Frame**

Enware's Emergency Tank Shower is compact and convenient for quick mobilisation of your workforce to remote site locations.

The simple, compact design provides the convenience to easily install and deploy when needed, without the need for expensive infrastructure.

Ideal for exploratory projects, shut down work, fracking or remote sites and harsh environments, anywhere.

#### **KEY FEATURES**

- Compact design
- Easily deployed and relocatable
- · Robust and reliable
- Integrated chiller (optional)
- Integrated pallet with forklift lift points for easy relocating and assembly
- Relocatable all terrain foot base no need for traditional cement base, saving time and cost
- 1400 litre thermally insulated tank with high UV resistance
- · Highly visible water level indicator
- Integrated overflow
- · Easily visible water temperature gauge
- Built-in Emergency signage
- Soft flow, low velocity shower rose provides maximum flushing performance
- Integral flow control delivers a consistent flow throughout a whole 15-minute flush duration
- Enware VERTECH Technology Eyewash

Due to ongoing Research and Development, specifications may change without notice. Component specifications may change on some export models.

Refer to warranty statement for warranty details - www.enware.com.au/warranty.



#### PRODUCT CODE

ET1400S Emergency Tank Shower 1400L with Single Piece Frame



# **Emergency Tank Shower 1400L with Single Piece Frame**

### **TECHNICAL DATA**

| Minimum Shower Flow Rate   | 75.7L/min                           |
|----------------------------|-------------------------------------|
| Maximum eye wash flow rate | 16 L/min                            |
| Tank storage capacity      | 1400 Litres                         |
| Inlet Connection           | 40mm Cam Lock / G1-1/2"(BSP)        |
| Estimated weight           | Water tank - 391kg<br>Frame - 200kg |







