

# Custodian 15mm Solenoid and Brass Body Housing

Enware Custodian 15mm solenoid and brass body housing for WMSSB-001

6VDC with KCC Connector

Used in conjunction with Custodian Smartboard

## KEY FEATURES

- 1/2" BSP MI Connections
- Brass Body
- KCC Connector



## INSTALLATION NOTE

- Installation shall be in accordance with the Plumbing Code of Australia (PCA), AS/NZS3500 and the manufacturer's instructions.
- Connect water supply to inlet and fixture line to the outlet, taking note of the direction of flow marked on the solenoid.
- Connect sensor cable to connector. Care should be taken with the position and orientation of the connectors. Align white markings on the connectors when connecting.

## PRODUCT CODE

WMS8206

Custodian 15mm Solenoid and Brass Body Housing



## TECHNICAL DATA

|                     |                              |
|---------------------|------------------------------|
| Operating Pressure  | 50 - 1000kPa                 |
| Maximum Temperature | 70°C                         |
| Operating Voltage   | 6VDC                         |
| Nominal Input       | 1.5W                         |
| Sealing Material    | EPDM                         |
| Shielding Class     | IP67                         |
| Connector to Sensor | KCC SK-2 Series Female 10 cm |

Products are to be installed in accordance with the Plumbing Code of Australia and AS/NZS3500. Reference should also be made to the Australasian Health Facility Guidelines (AHFG), ABCB and Local Government regulations when considering the choice of, and the installation of these products.

This product is compliant with the Lead Free requirements of NCC Volume Three.

Due to ongoing Research and Development, specifications may change without notice. Component specifications may change on some export models. Refer to warranty statement for warranty details - [www.enware.com.au/warranty](http://www.enware.com.au/warranty).

