



Silver, Golf, Diamond, Platinum
Interior Coating

Product Base composition. 8/01/21
Data Sheet Update 4/05/22

Formulation series 000QGSIDIGOPL

<p>DESCRIPTION: A liquid that is used with precious materials to create a bright ambiance. Dries bright and hard depending on how many coats are applied. The more applied the higher the luster.. Use on all paintable surfaces.</p> <p>Gain / Reflectance Value: 1.1 - 1.3 (1-2 coats) 1.3-1.6 (3-5 coats)</p> <p>Color / Appearance Color Specific. Smooth Sheen.</p> <p>Flash Point > 200 °F PMCC</p> <p>Extinguishing Media: Carbon Dioxide, Dry Chemical, Alcohol Foam</p> <p>STABILITY -Stable</p> <p>CONDITIONS TO AVOID -None known.</p> <p>INCOMPATIBILITY -None known.</p> <p>HAZARDOUS DECOMPOSITION PRODUCTS By Fire: -Carbon Dioxide, Carbon Monoxide HAZARDOUS POLYMERIZATION -Will not occur</p> <p>PRODUCT WEIGHT 8.53 lb/gal 1022 g/l</p> <p>SPECIFIC GRAVITY 1.03</p> <p>BOILING POINT 212 - 449 °F 100 - 231 °C</p> <p>MELTING POINT Not Available</p> <p>VOLATILE VOLUME Not Available</p> <p>EVAPORATION RATE Slower than ether</p> <p>VAPOR DENSITY Heavier than air</p> <p>SOLUBILITY IN WATER Dilutes</p> <p>pH > 2.0, < 11.5</p> <p>VOLATILE ORGANIC COMPOUNDS (VOC Theoretical - As Packaged) Rate Zero VOC</p> <p>PREPARING UNPAINTED SURFACES WALLBOARD - Joint compound must dry for two days before primer.</p> <p>WOOD - Set nails and fill holes with latex spackle. Sand lightly to a smooth surface, dust clean, then prime.</p> <p>CONCRETE, PLASTER AND MASONRY - Cure for 30 days before painting. "Slick poured" or pre-cast concrete needs chemical cleaning or a light sandblasting. Thoroughly rinse with water and allow to fully dry. Remove loose aggregate, and prime. For concrete block, fill with a latex block filler.</p> <p>STEEL, GALVANIZED METAL AND ALUMINUM - Clean off oils, then prime with an appropriate metal primer.</p>	<p>TECHNICAL DATA</p> <hr/> <p>BASE COMP</p> <hr/>																									
	<table border="0"> <tr> <td>Vehicle type</td> <td style="text-align: right;"><i>acrylic elastomeric</i></td> </tr> <tr> <td>Pigment type</td> <td style="text-align: right;"><i>top coating / proprietary formulation</i></td> </tr> <tr> <td>Volume Solids</td> <td style="text-align: right;">13% +/- 1%</td> </tr> <tr> <td>Practical Coverage</td> <td style="text-align: right;">400 sqft/gal</td> </tr> <tr> <td>Dry Time @ 77F/25C</td> <td style="text-align: right;">1 hour</td> </tr> <tr> <td>Recoat Time</td> <td style="text-align: right;">1 hour</td> </tr> <tr> <td>Flash Point</td> <td style="text-align: right;"><i>none</i></td> </tr> <tr> <td>Thin With</td> <td style="text-align: right;"><i>water</i></td> </tr> <tr> <td>Clean With</td> <td style="text-align: right;"><i>mild soap / water</i></td> </tr> <tr> <td>Weight Per Gallon</td> <td style="text-align: right;">8.53 lbs</td> </tr> <tr> <td>Storage Temperature</td> <td style="text-align: right;"><i>-min. 40F</i></td> </tr> <tr> <td>Storage Temperature</td> <td style="text-align: right;"><i>-max. 90F</i></td> </tr> <tr> <td>Shelf Life</td> <td style="text-align: right;"><i>1 year minimum - unopened</i></td> </tr> </table>	Vehicle type	<i>acrylic elastomeric</i>	Pigment type	<i>top coating / proprietary formulation</i>	Volume Solids	13% +/- 1%	Practical Coverage	400 sqft/gal	Dry Time @ 77F/25C	1 hour	Recoat Time	1 hour	Flash Point	<i>none</i>	Thin With	<i>water</i>	Clean With	<i>mild soap / water</i>	Weight Per Gallon	8.53 lbs	Storage Temperature	<i>-min. 40F</i>	Storage Temperature	<i>-max. 90F</i>	Shelf Life
Vehicle type	<i>acrylic elastomeric</i>																									
Pigment type	<i>top coating / proprietary formulation</i>																									
Volume Solids	13% +/- 1%																									
Practical Coverage	400 sqft/gal																									
Dry Time @ 77F/25C	1 hour																									
Recoat Time	1 hour																									
Flash Point	<i>none</i>																									
Thin With	<i>water</i>																									
Clean With	<i>mild soap / water</i>																									
Weight Per Gallon	8.53 lbs																									
Storage Temperature	<i>-min. 40F</i>																									
Storage Temperature	<i>-max. 90F</i>																									
Shelf Life	<i>1 year minimum - unopened</i>																									
	<p>APPLICATION: May Be Rolled - Recommend Spraying. Use a HVLP w/ 515 tip.</p> <p>Clean Up: Mild Soap and Water. Securely attach lid to any unused paint and store in cool dry place.</p> <p>WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear an NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.</p>																									