Marseille Fire Bowls

The Marseille Fire Bowls feature a low profile design and a wide opening to accommodate more and varied fire media. Handcrafted from glass fiber reinforced concrete (GFRC), these contemporary Fire Bowls come in a variety of different colors and textures. Fuel options include Natural Gas or Propane.

Three sizes are also available with a water spout to combine running water with dancing flames (plumbing must be locally supplied).



Feature Highlights

- Contemporary design
- Handcrafted from innovative Glass Fiber Reinforced Concrete (GFRC)
- 16" stainless steel burner
- Manual Flame Sensing Control System
- Optional 110V FyreStarter Bluetooth **Control** (Available on most fire bowls)
- Available for Natural Gas or Propane



48" Marseille Fire Bowl*

Model shown: 751-CB-11-M6xC // Finish: CB, Café Blanco

- Dimensions: 48" diameter x 101/2" h
- 16" star stainless steel burner
- Available with water spout

MODEL#	DESCRIPTION	NG (Btu)	LP (Btu)
751-xx-11-M6xC	Manual Flame Sensing	65,000	65,000
751-xx-80-M6xC	M.F.S.C.S. w/ water spout	65,000	65,000
751-xx-11-H6xC	FyreStarter Bluetooth†	100,000	100,000



40" Marseille Fire Bowl*

Model shown: 752-LB-80-M6xC // Finish: LB, Light Basalt

- Dimensions: 40" diameter x 11" h
- 16" star stainless steel burner
- Available with water spout

MODEL#	DESCRIPTION	NG (Btu)	LP (Btu)
752-xx-11-M6xC	Manual Flame Sensing	65,000	65,000
752-xx-80-M6xC	M.F.S.C.S. w/ water spout	65,000	65,000
752-xx-11-H6xC	FyreStarter Bluetooth [†]	100,000	100,000



32" Marseille Fire Bowl*

Model shown: **753-WA-11-M6xC** // Finish: WA, White Aspen

- Dimensions: 32" diameter x 81/2" h
- 16" star stainless steel burner
- Available with water spout

MODEL#	DESCRIPTION	NG (Btu)	LP (Btu)
753-xx-11-M6xC	Manual Flame Sensing	65,000	65,000
753-xx-80-M6xC	M.F.S.C.S. w/ water spout	65,000	65,000



24" Marseille Fire Bowl*

Model shown: 755-BA-11-M2xC // Finish: BA, Black Lava

- Dimensions: 24" diameter x 61/2" h
- 12" star stainless steel burner

MODEL#	DESCRIPTION	NG (Btu)	LP (Btu)
755-xx-11-M2xC	Manual Flame Sensing	60,000	60,000

^{*} Cannot accommodate a Propane tank inside the unit, see page 34 for matching tank housing options.

[†]Fire Bowls with FyreStarter Bluetooth Control require 120V AC power.