



ON | OFF CONTROLLER

FOR BROMIC GAS & ELECTRIC HEATER

MODEL NUMBER	BH3130010-2
POWER SUPPLY	110/230VAC, 31A max, Single Phase
NO OF CHANNELS	2
MAX OUTPUT POWER CHANNEL	3400W @ 230VAC 3400W @ 208VAC 1500W @ 110VAC
FUSE PROTECTION	32A (FWC high speed)
RECEPTION FREQUENCY	916MHz
OPERATING TEMPERATURE RANGE	-4° to 122°F
DIMENSIONS	8" x 5.7" x 3.3"
PROTECTION CLASS	IP54



DIMMER CONTROLLER

FOR BROMIC ELECTRIC HEATERS

MODEL NUMBER	BH3130011-2
POWER SUPPLY	208/240/277V 50/60Hz (29A,max)
MAX OUTPUT POWER CHANNEL	6800W @ 240VAC (29,5A) 6800W @ 277VAC (25,3A) 6000W @ 208VAC (29A)
FUSE PROTECTION	32A (FWC high speed)
CARRIER FREQUENCY	916MHz
OPERATING TEMPERATURE RANGE	-4° to 86°F
DIMENSIONS	9" x 7.9" x 2.95"
PROTECTION CLASS	IP54



ECLIPSE PENDANT CONTROLLER

FOR BROMIC ECLIPSE ELECTRIC PENDANT HEATERS ONLY

MODEL NUMBER	BH3230007-1
POWER SUPPLY	220/240VAC, 17A min, Single Phase
CHANNEL 1	Element 1 - 66% Heat Setting
CHANNEL 2	Element 2 - 33% Heat Setting
FUSE PROTECTION	20A (FWC high speed)
CARRIER FREQUENCY	916MHz
OPERATING TEMPERATURE RANGE	-4° to 122°F
DIMENSIONS	11.5" x 6.2" x 3.15"
PROTECTION CLASS	IP54



ECLIPSE WIRELESS MASTER REMOTE

COMPATIBLE WITH ECLIPSE CONTROLLERS ONLY


MODEL NUMBER	BH3623002-1
POWER SUPPLY	CR2450 battery (3V)
CARRIER FREQUENCY	916MHz
MODULATION	FSK
CONSUMPTION WHEN TRANSMITTING	10mA
WORKING TEMPERATURE	14° to +131°F
WIRELESS RANGE	100 ft



WIRELESS MASTER REMOTE

COMPATIBLE WITH BROMIC DIMMER CONTROLLERS ONLY

MODEL NUMBER	BH3130012-2
SUPPLY	CR2450 battery (3V)
CARRIER FREQUENCY	916 MHz
MODULATION	FSK
CONSUMPTION WHEN TRANSMITTING	10mA
WORKING TEMPERATURE	14° to 131°F
WIRELESS RANGE	100 ft



SMART-HEAT LINK HOME AUTOMATION PLUG-IN

COMPATIBLE WITH BROMIC CONTROLLERS

MODEL NUMBER	BH3130097-1
SUPPLY	+5VDC
CARRIER FREQUENCY	916 MHz
WORKING TEMPERATURE	14° to 131°F
WIRELESS RANGE	100 ft

