



With black door and brushed nickel faceplate trims

## WOOD INSERT

# SOLUTION 1.7

### # EB00057

The Enerzone team is once again innovating and living up to its reputation with the completely new **Solution 1.7**, which achieves incomparable performance of 1.26 g/h. This non-catalytic insert benefits from a state-of-the-art second combustion system.

The first-class materials, the arched cast iron door with delicate curves, the positioning of the silver grooves, the high density refractory bricks, the standard silent fan are all assets that make this unit an easy-to-operate insert that has this little extra. It gives its owner unparalleled comfort, increased durability and superior reliability.

*A faceplate extension is included with this unit for installation in most hearths.*

### FEATURES

- Recommended heating area: 500 to 1,800 sq. ft.
- Firebox volume: 1.9 cu. ft.
- Maximum heat output (dry cordwood): 65,000 BTU/h
- Maximum log length: 18"
- Exterior dimensions (excluding faceplate): 27 1/8" W x 22 3/8" D x 21 1/4" H
- Minimum hearth dimensions (masonry opening): 27 1/2" W x 12 3/4" D x 21 1/2" H
- Combustion technology: Non-catalytic
- Included: 144 CFM blower with variable speed control



### ◆ REQUIRED COMPONENTS

- Regular (29" H x 44" W)
- or large faceplate (32" H x 50" W)
- Black or brushed nickel faceplate trim kit

### ◆ OPTIONS

- Firescreen
- Fresh air intake kit
- Insulated fresh air intake pipe
- Fresh air intake register with airtight damper (5" diameter)
- Offset Liner Adapter

See complete technical data on pages 18 and 19.