



CHOICE OF LEGS

On black cast iron traditional legs

WOOD STOVE

SOLUTION 2.3

EB00063



◆ REQUIRED COMPONENTS

Pedestal or three models of legs (available in black or brushed nickel cast iron)

◆ OPTIONS

Firescreen

Air mate

130 CFM blower with variable speed control and thermodisc

Fresh air intake kit (5" diameter)

Insulated fresh air intake pipe

Fresh air intake register with airtight damper (5" diameter)

Experience moments of pure happiness in the comfort of your own home with the enhanced performance of the **Solution 2.3**. Thanks to our state-of-the-art technology, the combustion process offers a high thermal output of 75,000 BTU/h and low emissions of 1.54 g/h. This model proves to be the key for the informed consumer for whom wood heating has no secrets as well as for the new owner wishing to explore the comfort of alternative heating. The size of the firebox permits the easy positioning of logs in both depth and width. Despite its size, the **Solution 2.3** keeps a balanced design that gives it the look of a decorative appliance while providing powerful heating to the serious user.

Several versions of options are available to allow you to create a look that suits your needs. Choose from 3 leg models, in black or brushed nickel, and a pedestal, a variable speed 130 CFM fan, or a heat exchanger. The **Solution 2.3** is the perfect balance between security, performance and comfort.

FEATURES

- Recommended heating area: 500 to 2,100 sq. ft.
- Firebox volume: 2.4 cu. ft.
- Maximum heat output (dry cordwood): 75,000 BTU/h
- Maximum log length: 20"
- Exterior dimensions (pedestal): 27" W x 26 1/4" D x 32 3/4" H
- Combustion technology: Non-catalytic
- Included: Ash drawer with safety lid

See complete technical data on pages 10 and 11.