



# 1700

INSERT

OB01705

With brushed nickel door overlay and black faceplate trims.

Like its larger counterpart Osburn 2000, the 1700 insert offers a revamped version of perfect size to provide ambiance and warmth. Give yourself a real haven of peace with an eco-friendly device whose average particle emission rate is remarkably low at 1.26 g/h!

Inside and out, this insert is engineered from high quality materials that put you at the center of a heating experience for many years: high-density bricks, cast iron door and quiet blower for increased durability. Discover the different options to customize the look of your appliance, available in black or brushed nickel: door overlays and faceplate trims.

*A faceplate extension is included with this unit for installation in most hearths.*

**EMISSIONS:** 1.26 g/h

**RECOMMENDED HEATING AREA:** 500 - 1,800 sq. ft.

**MAXIMUM HEAT OUTPUT:** 65,000 BTU/h

**FIREBOX VOLUME:** 1.9 cu. ft.

**COMBUSTION TECHNOLOGY:** Non-catalytic

### REQUIRED ACCESSORIES

- > Black or brushed nickel door overlay
- > Faceplate kit  
Regular (29" x 44") or  
Large (32" x 50")
- > Black or brushed nickel  
faceplate trims

### OPTIONS

- > Offset liner adaptor
- > 5"Ø fresh air intake kit
- > 5"Ø fresh air intake register  
with airtight damper
- > Rigid firescreen

Black or brushed nickel faceplate trims



See the complete technical data on pages 22 and 23.