



With narrow faceplate (4-sided)

This wood insert will bring an unmatched modernism to your decor, in addition to perfectly combining functionality and comfort. The impeccable lines display a timeless style while guaranteeing reliability and durability. The Inspire 2000 will charm you as much by its aesthetics as its 77% optimal performance. With its particle emission rate as low as 1.54 g/h and its high-performance combustion system, environmentalists have never been as happy with wood heating. The Inspire Collection celebrates our past and embraces our future as our team is committed more than ever to our industry's contribution to sustainability. A dream opportunity on the latest trends!

**EMISSIONS:** 1.54 g/h

**RECOMMENDED HEATING AREA:** 500 - 2,100 sq. ft.

**MAXIMUM HEAT OUTPUT:** 75,000 BTU/h

**FIREBOX VOLUME:** 2.4 cu. ft.

**COMBUSTION TECHNOLOGY:** Non-catalytic

# INSPIRE 2000

INSERT

OB02045

## REQUIRED ACCESSORIES

- > Narrow, narrow U shape or cuttable faceplate (32" x 50")

## OPTIONS

- > Moulded refractory panel kit for insert
- > 5"Ø fresh air intake kit
- > 5"Ø fresh air intake register with airtight damper
- > Offset liner adaptor

Narrow faceplate  
(4-sided)



Narrow U shaped faceplate  
(3-sided)



Cuttable faceplate

