


ALUMINIUM NON-COMBUSTIBLE DECKING



Synergised subframe come in 3 heights to cover all your base needs.

Fully non-combustible aluminium decking system designed for both residential and commercial environments such as high-rise balconies, walkways, roof terraces, pubs, gardens and all other high-rise applications and public areas.

Available in 3 contemporary colours our deck boards are manufactured from structural grade 6063 T6 aluminium with 100 micron Qualicoat™ premium powder coating, making it the ideal decking solution for high footfall areas. The premium coating is low slip and provides low surface temperatures underfoot.



Synergised aluminium decking is a complete decking system, with one of the most advanced, high strength sub-frame systems available on the market. The subframe is available in 3 standard heights (120, 70 & 20mm) to cover all your requirements, and all joist options are the same width (40mm), and use the same unique fixing system, which dramatically cuts down on-site installation time.

SYNERGISED JOIST DATA SHEET

TECHINICAL DATA

	20mm Joist	70mm Joist	120mm Joist
Weight	0.99 kg/m	1.47 kg/m	1.87 kg/m
Material	Aluminium 6063 T6	Aluminium 6063 T6	Aluminium 6063 T6
Joist Height	20 mm	70 mm	120 mm
Joist Width	40 mm	40 mm	40 mm

LOADING DEFLECTION

