### **TECHNICAL DATA SHEET**

TDS ART GLITTER GLAZE EFFECT 06/18 V1



940 - 8

# ARTISAN SPECIAL EFFECTS PAINTS

## **GLITTER GLAZE EFFECT**

TYPE OF MATERIAL	Artisan Glitter Glaze is a water based transparent coating containing Glitter particles to give a highly decorative glitter effect as a topcoat over matt emulsions. For use on interior surfaces.		
USES	An internal decorative effect Glitter finish used to create a stylish exciting sparkle in the home.		
COLOURS AVAILABLE	3 colours, Diamond Dust, Rose Gold, Starlight Silver.		
FINISH	Sheen – Glitter	TYPE REFERENCE No.	940-8
NUMBER OF COMPONENTS	One	MIXING RATIO	N/A
METHOD OF APPLICATION	Foam Roller recommended. Can be sprayed.		
AVAILABLE PACKS	100ml, 250ml. all colours & 750ml in Starlight silver only		
SHEEN LEVEL	A Glitter sparkle effect finish.		
PRACTICAL COVERAGE PER LITRE	Approx. 2.0 Sqm / 100ml, 4.0 Sqm / 250ml, 12.0 Sqm / 750ml		
FLASH POINT	N/A Water based.		
DRYING TIMES: SURFACE RECOAT	2-4 Hours 4 Hours		
PREPARATION	Remove loose or flaking paint, fill cracks or holes with filler and sand smooth. Abrade any silk, satin or glossy surfaces before painting over. Treat any mould with scouring pad and bleach solution (1part to 3 with water).leave on surface for 15minutes then wash with clean water and dry. Surfaces must be clean and dry and free from grease oil or dirt or flaking coatings before painting. New dry plaster, or porous surfaces should be primed with a coat of Craig & Rose Primer Undercoat or other suitable primer.		

THIS INFORMATION IS GIVEN IN GOOD FAITH, BUT BECAUSE OF VARIATIONS IN APPLICATION AND USE, NO WARRANTY IS GIVEN OR IMPLIED REGARDING THE RESULTS OBTAINED. USERS SHOULD SATISFY THEMSELVES OF THE SUITABILITY FOR THEIR PURPOSE AND USE.

### **TECHNICAL DATA SHEET**

TDS ART GLITTER GLAZE EFFECT 06/18 V1



940 - 8

## ARTISAN SPECIAL EFFECTS PAINTS

## **GLITTER GLAZE EFFECT**

APPLICATION INSTRUCTIONS	Select and apply your chosen contrasting base colour in a Matt emulsion such as 1829 Chalky Emulsion. Mask off areas or stripes on walls to create a contrasting and interesting pattern on the walls. Stir the Glitter glaze thoroughly prior to use. Before you begin, practice your chosen scheme on a large piece of board to get familiar with the product. Use a small foam roller to apply, pour glitter into a tray and load the roller as normal – you must remove the excess glitter by rolling onto some old newspapers until the roller is almost dry – then apply in even vertical strokes over the area being painted.  Do not overload roller.  For small objects use a brush in a random manner to apply.  Do not apply over Silk or Satin finishes.  Can be sprayed with Air assisted spray – do not thin- just adjust fan and pressure with gun to get an even fan. Mask off areas and use broad spraying strokes to apply.	
RESTRICTIONS ON APPLICATION AND OVERCOATING INSTRUCTIONS	Ensure the previous coat has fully dried for 4 hrs before over coating. Do not apply in temperatures near freezing as this will seriously slow down the drying and may destroy the structure of the paint. Store in a frost-free place and do not allow the paint to freeze. Do not apply to highly absorbant surfaces.	
CLEANING	Remove as much paint as possible from equipment before cleaning with water. Clean hands with warm soapy water.	
SAFETY PRECAUTIONS	Ensure good ventilation during application and drying. After contact with skin, wash immediately with plenty of soap and water. In case of contact with the eyes, rinse immediately with plenty of water and seek medical advice. See can label for full instructions. Safety Data Sheets are available on request.	
VOC CONTENT (VOLATILE ORGANIC COMPOUNDS)	2004/42 EU Limit value for this product ( Cat A/I : 200g/L) This product contains Max : 2g/L VOC.	
DISPOSAL & ENVIRONMENT	Please dispose of unused paint and container responsibly. Do not empty into drains or watercourses. Some local authorities have special facilities for the disposal of paint.	

THIS INFORMATION IS GIVEN IN GOOD FAITH, BUT BECAUSE OF VARIATIONS IN APPLICATION AND USE, NO WARRANTY IS GIVEN OR IMPLIED REGARDING THE RESULTS OBTAINED. USERS SHOULD SATISFY THEMSELVES OF THE SUITABILITY FOR THEIR PURPOSE AND USE.

### **TECHNICAL DATA SHEET**

TDS ART GLITTER GLAZE EFFECT 06/18 V1



940 - 8

# ARTISAN SPECIAL EFFECTS PAINTS

GLITTER GLAZE EFFECT		

This information is given in good faith, but because of variations in application and use, no warranty is given or implied regarding the results obtained. Users should satisfy themselves of the suitability for their purpose and use.