



Product Data Sheet

1045T-N

Industrial surface mount magnetic contact

Industrial Surface Mount Contact

The Sentrol 1045T series features a wider make distance, which permits faster installation, accommodates greater misalignment and works better on steel without time-consuming brackets. A wider break distance helps prevent false alarms caused by loose fitting doors. Sentrol-specified contacts keep the 1045 series from sticking or freezing on seldom-used doors.

Applications

The contacts are used to protect openings such as metal entry/exit doors, overhead doors, roof hatches or hinged skylights.

Durability and dependability

The Sentrol high performance magnetic contacts have been designed to facilitate installation and ensure durability and dependability. Most are conservatively rated at 10,000,000 cycles, guaranteeing a long life. Every reed connection is hand soldered and each magnetic contact is tested before they leave the factory, 100% of the time.



Standard Features


- Designed for commercial and industrial applications
- Can be used on steel without brackets
- Rugged construction
- Mounting screws
- Concealed terminals resist tampering and inadvertent shorting

1045T-N

Industrial surface mount magnetic contact

Specifications

Gap distance (max)	32 mm
Connections	Screw terminals
Contact	NC
Supervised loop	No
Dimensions (L x W x H)	99 x 15 x 18 mm
Color	White
Remarks	



Ordering Information

Part No.	Description
1045T-N	Industrial surface mount magnetic contact, white

