



DOYLE VACUUM SYSTEMS



Quality. Performance. Reliability.

# Free Use Power Vac



## Ideal for...

- Fleet Maintenance Facilities
- Quick-Lubes
- Car and Truck Rental Facilities
- Automotive Dealerships and Repair Facilities
- Car Washes
- Gas Stations & Convenience Stores
- Other...

**Several models to choose from, depending on your specific application needs...**

### Model 210000

- No Switch or Timer (For Remote Switch)

### Model 210100

- ON/OFF Toggle Switch

### Model 210200

- Push Button Switch with Timer

### Available Motor Options:

(2) Standard Motors	120 Volts / 16 Amps
(2) High-Performance Motors	120 Volts / 24 Amps
(2) High-Performance Motors	240 Volts / 13 Amps

### Standard Features:

- Stainless steel construction
- Black, Polyethylene Dome (Stainless Optional)
- **3-Chamber vacuum tank** with separate dirt intake and collection chambers
- **Two pleated cartridge filters provide 16 ft<sup>2</sup> of filter surface area – with expanded-PTFE surface membrane, filters are 99.7% efficient at 0.3 microns**
- 5-Gallon bucket for dirt compartment
- Low voltage (24-Volt) control circuit
- Fuse Protected

**Dimensions:** 20.0" Wide x 24.0" Deep x 53.0" Tall

**Weight:** Approximately 135 lbs.