



DOYLE VACUUM SYSTEMS



Quality. Performance. Reliability.

# Wall Mount Power Vac



## Ideal for...

- Central Vacuum
- Garages & Workshops
- Fleet Maintenance Facilities
- Quick-Lubes
- Car and Truck Rental Facilities
- Automotive Dealerships and Repair Facilities
- Car Washes
- Other...

## Two Models to Choose From:

### Model 510000

- ON/OFF Toggle Switch
- By-Pass Cooled Motor
- 110-120 Volts / 12.0 amps
- 490 Air Watts
- 112 CFM / 123" H<sub>2</sub>O

### Model 510500

- ON/OFF Toggle Switch
- By-Pass Cooled Motor
- 220-240 Volts / 7.0 amps
- 560 Air Watts
- 117 CFM / 135" H<sub>2</sub>O

## Standard Features:

- Solid Steel Construction
- Zinc Powder Undercoat
- Baked on Powder Coat Finish (Satin Black)
- Long Life Motor Brushes (~1200 hours) – Increases Standard Motor Life by ~50%
- Pleated Cartridge Filter Provides 8 ft<sup>2</sup> of Filter Surface Area – with Expanded-PTFE Surface Membrane, Filter is 99.7% Efficient at 0.3 microns – HEPA grade (NOT HEPA CERTIFIED)
- Filter is Semi-Permanent and Washable
- 6 ft. Power Cord
- 1.5 inch (I.D.) x 25 ft. (Long) Vacuum Hose
- Upholstery Tool and Crevice Tool
- Wall-Mounted Hose Hanger

## Optional Features:

- Push-Button Switch w/ Timer Optional
- Remote, Low-Voltage Switching Optional
- 1.5 inch (I.D.) x 50 ft. (Long) Vacuum Hose
- Custom Powder Coat Colors

## Dimensions / Weights:

Vacuum: 16 1/4" Wide x 12 3/8" Deep x 35" Tall  
Approximately 55 lbs.

Shipping: 21" x 21" x 41"  
Approximately 65 lbs.