

TECHNICAL DATA SHEET



Suitable for all type of kegs 20L, 30L and 50L

Measurements: 1200 x 800 x 163,5 mm

Material: HDPE or PP (virgin or recycled)

Weight: 18 kg (incl. rubber plugs and taps)

Static load<sup>(2)</sup>: 10.000 kg

Dynamic load (3): 2000 kg

Racking load<sup>(4)</sup>: 750 kg

Colour: Black (other colours on demand)

Openings: 4 way entry pallet

Stacking: 10 pallets high (with 501/301)







Load: Different values may be obtained when used under different conditions, such as load type, ambient temperature and standing time. Specific requirements can be identified upon request.

 $<sup>\</sup>overset{(2)}{\sim}$  Static load: compression strength with level floor contact and evenly distributed load at 20°C

<sup>(3)</sup> Dynamic load: on the forklift with selected, evenly distributed load at 20°C

<sup>(4)</sup> Racking: evenly distributed load along the longitudinal sides resting on two supports at 20°C



TECHNICAL DATA SHEET

# **Keg Pallet**

1200 x 800 x 163,5 mm



### **Features**







Reinforced corners
Especially designed to
strengthen the pallet and
protect against fork lift
impact




Mechanical anti-slip
16 rubber plugs in the
upper deck provide antislip for crates on the deck
and for the pallet on the
fork lift tynes



**Customized**Possibility to put the company logo on the pallet

## **PP Taps**

Replaceable PP taps. Taps are locked into the pallet to secure the kegs on the pallet during handling, transport and storage. There exists a configuration for 20I, 30I and 50I kegs.



## **Option**



#### **RFID-transponder or tag**

Possibility to introduce a RFID nail transponder or tag into the pallet for an errorless, automated inventory and traceability management.