



## Castrol ATF Dex II Multivehicle

Automatic Transmission Fluid

### Description

Castrol ATF Dex II Multivehicle is an Automatic Transmission Fluid which may be used in automatic transmissions and power steering units of many types of vehicle where Dexron IID or Mercon performance is required. It is also approved for use in many European heavy duty automatic transmissions and Mercedes Benz manual transmissions.

### Advantages

- Multiple approvals provide wide ranging use.
- Ensures efficient operation of power steering units under all conditions.
- High thermal stability protects against deposits and oil thickening prolonging the life of components and lubricant.
- Enhanced friction characteristics and wear protection maintain effective operation of equipment.
- Effective seal compatibility reduces the risk of leakages

### Typical Characteristics

Name	Method	Units	ATF Dex II Multivehicle
Density @ 20C, Relative	ASTM D4052	g/ml	0.870
Colour	Visual	-	red
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	40
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	7.5
Viscosity Index	ASTM D2270	None	159
Viscosity, Brookfield @ -40C	ASTM D2983	mPa.s (cP)	46600
Pour Point	ASTM D97	°C	-45
Flash Point, COC	DIN ISO 2592	°C	203

## Product Performance Claims

Approved  
ZF -TE-ML 04D, 11A, 14A  
MAN 339 V1  
MAN 339 Z1  
MAN 339 L2  
MB-Approval 236.6  
Voith H55.6335.xx  
Meets Ford Mercon®, Dexron®-IID

## Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol ATF Dex II Multivehicle  
01 Sep 2017  
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW  
Orders/Enquiries: 0845 6008125 Technical Enquiries: 0845 082 1719 BP (Ireland) Ireland Orders/Enquiries: 1850 930 3942 Ireland Technical Enquiries: 1800 509 353  
[www.castrol.com/uk](http://www.castrol.com/uk)