



Castrol Classic XL 30

Oil for Classic Vehicles

Description

Castrol Classic XL 30 is a high quality traditional monograde engine oil of low detergency.

Low detergency can be essential for any unrestored (or unknown condition) engines where deposits may be sealing the engine. Removing these deposits may cause oil leaks and potential oilway blocking.

Castrol Classic XL 30 contains selected additives to control high temperature "varnish", give good anti-wear performance and help prevent the build up of low temperature "sludge".

It is useful for cold temperature starting in these vehicles and creates improved oil pressure at high operating temperatures.

Application

Castrol Classic XL 30 is primarily for pre-1950 veteran, vintage and classic cars requiring an SAE 30 lubricant.

It is suitable for use in automotive gasoline engines where an API SB performance level is recommended.

It is also applicable to a number of manually operated gearboxes, including Wilson pre-selects, fitted to vintage and classic cars.

Advantages

Castrol Classic XL 30 is formulated for:

Cars

- Summer use in petrol engines
- Winter use in engines which would otherwise have high oil consumption
- Some manually operated gearboxes

Motor Cycles

- Summer use in twin-cylinder 4-stroke engines
- Certain motorcycle gearboxes

Typical Characteristics

Name	Method	Units	Castrol Classic XL 30
Density @ 15C, Relative	ASTM D4052	g/ml	0.888
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	11.1
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	99
Viscosity Index	ASTM D2270	None	97
Pour Point	ASTM D97	°C	-21
Flash Point, PMCC	ASTM D93	°C	226
SAE Viscosity Grade	J300		30

Product Performance Claims

API SB

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Classic XL 30

18 Dec 2015

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

Orders/Enquiries: 0345 6008125 Technical Enquiries: 0345 082 1719 BP (Ireland) Ireland Orders/Enquiries: 1850 930 3942 Ireland Technical Enquiries: 1800 509 353

www.castrol.com/uk