## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 6/16/2023 Revision date: 6/16/2023 Version: 1.0

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture

Product name : BANANA & GINGER LILY #EU48594F

UFI : 61KA-C4K3-C00U-6X30

Product code : EU48594F

Type of product : Perfumes, fragrances
Product group : Trade product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

### 1.2.1. Relevant identified uses

Main use category : Professional use, Industrial use

Industrial/Professional use spec : Industrial

For professional use only Perfumes, fragrances

Use of the substance/mixture : Perfumes, frag Function or use category : Odour agents

#### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Craftastik Limited Unit 11 Swift Business Park Creek Way, Rainham, RM13 8LE

T 44-203 305 6486

#### 1.4. Emergency telephone number

Emergency number : 1-800-255-3924; +01-813-248-0585; China:+400-120-0751; Mexico:+01-800-099-0731;

Brazil: +0-800-591-6042; India: +000-800-100-4086

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2 H315
Skin sensitisation, Category 1 H317
Hazardous to the aquatic environment – Chronic Hazard, Category 3 H412

Full text of H- and EUH-statements: see section 16

#### Adverse physicochemical, human health and environmental effects

Causes skin irritation. Harmful to aquatic life with long lasting effects. May cause an allergic skin reaction.

#### 2.2. Label elements

Signal word (CLP)

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



· \Marp

Contains : Citral; d-Limonene; Linalool; Eugenol; Orange oil ; Triplal (Vertocitral); Rosemary Oil; Ginger

oil; COUMARIN

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazard statements (CLP) : H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H412 - Harmful to aquatic life with long lasting effects.

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

Precautionary statements (CLP) : P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 - Wash hands, forearms and face thoroughly after handling.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P302+P352 - IF ON SKIN: Wash with plenty of water.

Extra phrases : For professional users only.

#### 2.3. Other hazards

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

### **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Isoamyl acetate substance with national workplace exposure limit(s) (AT, BE, BG, CY, DE, DK, EE, ES, FI, FR, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, TR); substance with a Community workplace exposure limit	CAS-No.: 123-92-2 EC-No.: 204-662-3 EC Index-No.: 607-130-00-2 REACH-no: 01-2119548408- 32	3 – 5.9998	Flam. Liq. 3, H226
Citral substance with national workplace exposure limit(s) (BE, ES, IE, PL, PT)	CAS-No.: 5392-40-5 EC-No.: 226-394-6 EC Index-No.: 605-019-00-3 REACH-no: 01-2119462829- 23	2.5 – 4.9999	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
d-Limonene substance with national workplace exposure limit(s) (DE, ES, FI, SI, NO, CH)	CAS-No.: 5989-27-5 EC-No.: 227-813-5 EC Index-No.: 601-029-00- 7;601-096-00-2 REACH-no: 01-2119493353- 35	2 – 3.9999	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1B, H317 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 3, H412
Benzyl acetate substance with national workplace exposure limit(s) (BE, DK, ES, IE, LT, LV, PT, RO)	CAS-No.: 140-11-4 EC-No.: 205-399-7 REACH-no: 01-2119638272- 42	1 – 1.9999	Aquatic Chronic 3, H412
Benzyl alcohol substance with national workplace exposure limit(s) (BG, CZ, DE, FI, LT, LV, PL, SI, CH)	CAS-No.: 100-51-6 EC-No.: 202-859-9 EC Index-No.: 603-057-00-5 REACH-no: 01-2119492630-	1 – 1.9999	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319

# Safety Data Sheet

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Linalool	CAS-No.: 78-70-6 EC-No.: 201-134-4 EC Index-No.: 603-235-00-2 REACH-no: 01-2119474016-	1 – 1.9999	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317
Amyl salicylate	CAS-No.: 2050-08-0 EC-No.: 218-080-2 REACH-no: 01-2119969444- 27	1 – 1.9999	Acute Tox. 4 (Oral), H302 Aquatic Chronic 1, H410
Terpinyl acetate	CAS-No.: 80-26-2 EC-No.: 201-265-7	0.8 – 1.5	Aquatic Chronic 2, H411
Eugenol	CAS-No.: 97-53-0 EC-No.: 202-589-1 REACH-no: 01-2119971802- 33	0.5 – 1	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 Skin Sens. 1B, H317
Isobutyl acetate substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, ES, FI, FR, GB, GR, HR, HU, IE, IT, LT, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH)	CAS-No.: 110-19-0 EC-No.: 203-745-1 EC Index-No.: 607-026-00-7	0.5 – 1	Flam. Liq. 2, H225 STOT SE 3, H336
Orange oil	CAS-No.: 8008-57-9 EC-No.: 232-433-8 REACH-no: 01-2119493353- 35	0.5 – 1	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Sandela	CAS-No.: 66068-84-6 EC-No.: 266-100-3	0.4 – 0.7	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Triplal (Vertocitral)	CAS-No.: 68039-49-6 EC-No.: 268-264-1	0.3 – 0.61	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 3, H412
Undecavertol	CAS-No.: 81782-77-6 EC-No.: 279-815-0	0.3 – 0.6	Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Rosemary Oil	CAS-No.: 8000-25-7 EC-No.: 283-291-9	0.1 – 0.2	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1B, H317 STOT SE 2, H371 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
zingiber officinale (ginger) root oil	CAS-No.: 8007-08-7 EC-No.: 283-634-2	0.1 – 0.2	Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
COUMARIN	CAS-No.: 91-64-5 EC-No.: 202-086-7 REACH-no: 01-2119943756- 26	0.1 – 0.1531	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Skin Sens. 1, H317 Aquatic Chronic 2, H411

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
.betaPinene substance with national workplace exposure limit(s) (BE, EE, ES, LT, PT, SE, NO)	CAS-No.: 127-91-3 EC-No.: 204-872-5	≤ 0.06	Flam. Liq. 3, H226
Dipropylene glycol monomethyl ether substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 34590-94-8 EC-No.: 252-104-2	≤ 0.0496	Not classified
.alphaPinene substance with national workplace exposure limit(s) (BE, EE, ES, LT, PT, SE, NO)	CAS-No.: 80-56-8 EC-No.: 201-291-9	≤ 0.004	Flam. Liq. 3, H226

Full text of H- and EUH-statements: see section 16

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

4.1. Description of first aid measures	
First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see Get medical advice/attention. on this label). If skin irritation occurs: Get medical advice/attention. Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists. Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Call a poison center or a doctor if you feel unwell.

## 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use. Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.

## 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Suitable extinguishing media : Sand. Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

#### 5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire fighting water from entering the environment.

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Protection during firefighting

: Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

**Emergency procedures** 

: Ventilate spillage area. Evacuate unnecessary personnel. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

#### 6.1.2. For emergency responders

Protective equipment

**Emergency procedures** 

: Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure

: Ventilate area.

# 6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

controls/personal protection".

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Other information

: Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

: Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

See Section 8. Exposure controls and personal protection. For further information refer to section 13.

#### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Precautions for safe handling

: Ensure good ventilation of the work station. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing dust/fume/gas/mist/vapours/spray.

Hygiene measures

: Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Keep only in the original container in a cool, well ventilated place away from : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container closed when not in use. Store in a well-ventilated place. Keep cool.

Incompatible products Incompatible materials

: Strong bases. Strong acids.: Sources of ignition. Direct sunlight.

Storage temperature : 25 °C

Storage area : Store in a well-ventilated place. Store away from heat.

Special rules on packaging : Store in a closed container.

Packaging materials : Do not store in corrodable metal.

#### 7.3. Specific end use(s)

No additional information available

6/16/2023 (Revision date) EN (English) 5/31

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

# SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

### 8.1.1 National occupational exposure and biological limit values

Isoamyl acetate (123-92-2)		
EU - Indicative Occupational Exposure Limit (IOEL)		
IOEL TWA	270 mg/m³	
IOEL TWA [ppm]	50 ppm	
IOEL STEL	540 mg/m³	
IOEL STEL [ppm]	100 ppm	
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	270 mg/m³ (Pentyl acetate (all isomers))	
MAK (OEL TWA) [ppm]	50 ppm (Pentyl acetate (all isomers))	
MAK (OEL STEL)	540 mg/m³ (Pentylacetate)	
MAK (OEL STEL) [ppm]	100 ppm (Pentylacetate)	
Belgium - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	540 mg/m³	
OEL STEL [ppm]	100 ppm	
Bulgaria - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	540 mg/m³	
OEL STEL [ppm]	100 ppm	
Croatia - Occupational Exposure Limits		
GVI (OEL TWA) [1]	270 mg/m³	
GVI (OEL TWA) [2]	50 ppm	
KGVI (OEL STEL)	540 mg/m³	
KGVI (OEL STEL) [ppm]	100 ppm	
Cyprus - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	540 mg/m³	
OEL STEL [ppm]	100 ppm	
Denmark - Occupational Exposure Limits		
OEL TWA [1]	271 mg/m³ (Amyl acetate, all isomers)	
OEL TWA [2]	50 ppm (Amyl acetate, all isomers)	
Estonia - Occupational Exposure Limits		
OEL TWA	270 mg/m³	

# Safety Data Sheet

Isoamyl acetate (123-92-2)			
OEL TWA [ppm]	50 ppm		
OEL STEL	540 mg/m³		
OEL STEL [ppm]	100 ppm		
Finland - Occupational Exposure Limits			
HTP (OEL TWA) [1]	270 mg/m³ (Pentyl acetate)		
HTP (OEL TWA) [2]	50 ppm (Pentyl acetate)		
HTP (OEL STEL)	540 mg/m³		
HTP (OEL STEL) [ppm]	100 ppm		
France - Occupational Exposure Limits			
VME (OEL TWA)	270 mg/m³ (restrictive limit)		
VME (OEL TWA) [ppm]	50 ppm (restrictive limit)		
VLE (OEL C/STEL)	540 mg/m³ (restrictive limit)		
VLE (OEL C/STEL) [ppm]	100 ppm (restrictive limit)		
Germany - Occupational Exposure Limits (TRGS 90	0)		
AGW (OEL TWA) [1]	270 mg/m³		
AGW (OEL TWA) [2]	50 ppm		
Gibraltar - Occupational Exposure Limits			
OEL TWA	270 mg/m³		
OEL TWA [ppm]	50 ppm		
OEL STEL	540 mg/m³		
OEL STEL [ppm]	100 ppm		
Greece - Occupational Exposure Limits			
OEL TWA	530 mg/m³		
OEL TWA [ppm]	100 ppm		
OEL STEL	800 mg/m³		
OEL STEL [ppm]	150 ppm		
Hungary - Occupational Exposure Limits	Hungary - Occupational Exposure Limits		
AK (OEL TWA)	270 mg/m³		
CK (OEL STEL)	540 mg/m³		
Ireland - Occupational Exposure Limits			
OEL TWA [1]	260 mg/m³		
OEL TWA [2]	50 ppm		
OEL STEL	520 mg/m³		
OEL STEL [ppm]	100 ppm		
Italy - Occupational Exposure Limits			
OEL TWA	270 mg/m³		
OEL TWA [ppm]	50 ppm		
OEL STEL	540 mg/m³		
OEL STEL [ppm]	100 ppm		

# Safety Data Sheet

Isoamyl acetate (123-92-2)		
Latvia - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA [ppm]	50 ppm	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	270 mg/m³	
IPRV (OEL TWA) [ppm]	50 ppm	
TPRV (OEL STEL)	540 mg/m³	
TPRV (OEL STEL) [ppm]	100 ppm	
Luxembourg - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	540 mg/m³	
OEL STEL [ppm]	100 ppm	
Malta - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	540 mg/m³	
OEL STEL [ppm]	100 ppm	
Netherlands - Occupational Exposure Limits		
TGG-15min (OEL STEL)	530 mg/m³	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	250 mg/m³	
NDSCh (OEL STEL)	500 mg/m³	
Portugal - Occupational Exposure Limits		
OEL TWA	270 mg/m³ (indicative limit value)	
OEL TWA [ppm]	50 ppm (indicative limit value)	
OEL STEL	540 mg/m³ (indicative limit value)	
OEL STEL [ppm]	100 ppm (indicative limit value, regulated under Pentyl acetate, all isomers)	
Romania - Occupational Exposure Limits		
OEL TWA	270 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	540 mg/m³	
OEL STEL [ppm]	100 ppm	
Slovakia - Occupational Exposure Limits		
NPHV (OEL TWA) [1]	270 mg/m³	
NPHV (OEL TWA) [2]	50 ppm	
NPHV (OEL C)	540 mg/m³	
Slovenia - Occupational Exposure Limits		
OEL TWA	270 mg/m³	

# Safety Data Sheet

Isoamyl acetate (123-92-2)		
OEL TWA [ppm]	50 ppm	
OEL STEL	540 mg/m³	
OEL STEL [ppm]	100 ppm	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	270 mg/m³ (indicative limit value)	
VLA-ED (OEL TWA) [2]	50 ppm (indicative limit value)	
VLA-EC (OEL STEL)	540 mg/m³	
VLA-EC (OEL STEL) [ppm]	100 ppm	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	270 mg/m³ (Pentyl acetates)	
NGV (OEL TWA) [ppm]	50 ppm (Pentyl acetates)	
KTV (OEL STEL)	540 mg/m³ (Pentyl acetates)	
KTV (OEL STEL) [ppm]	100 ppm (Pentyl acetates)	
Norway - Occupational Exposure Limits		
Grenseverdi (OEL TWA) [1]	260 mg/m³	
Grenseverdi (OEL TWA) [2]	50 ppm	
Korttidsverdi (OEL STEL)	325 mg/m³ (value calculated)	
Korttidsverdi (OEL STEL) [ppm]	75 ppm (value calculated)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA [ppm]	50 ppm (Pentyl acetate, all isomers)	
ACGIH OEL STEL [ppm]	100 ppm (Pentyl acetate, all isomers)	
Citral (5392-40-5)		
Belgium - Occupational Exposure Limits		
OEL TWA	32 mg/m³ (vapor and aerosol)	
OEL TWA [ppm]	5 ppm (vapor and aerosol)	
OEL chemical category	Skin	
Ireland - Occupational Exposure Limits		
OEL TWA [2]	5 ppm	
OEL STEL [ppm]	15 ppm (calculated)	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	27 mg/m³	
NDSCh (OEL STEL)	54 mg/m³	
Portugal - Occupational Exposure Limits		
OEL TWA [ppm]	5 ppm	
OEL chemical category	Sensitizer, A4 - Not Classifiable as a Human Carcinogen, skin - potential for cutaneous exposure	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [2]	5 ppm (inhalable fraction and vapor)	
OEL chemical category	Sensitizer, skin - potential for cutaneous absorption	

# Safety Data Sheet

Citral (5392-40-5)		
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA [ppm]	5 ppm (inhalable fraction and vapor)	
ACGIH chemical category	Not Classifiable as a Human Carcinogen, Skin - potential significant contribution to overall exposure by the cutaneous route, dermal sensitizer	
d-Limonene (5989-27-5)		
Finland - Occupational Exposure Limits		
HTP (OEL TWA) [1]	140 mg/m³	
HTP (OEL TWA) [2]	25 ppm	
HTP (OEL STEL)	280 mg/m³	
HTP (OEL STEL) [ppm]	50 ppm	
Germany - Occupational Exposure Limits (TRGS 90	0)	
AGW (OEL TWA) [1]	28 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)	
AGW (OEL TWA) [2]	5 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)	
Chemical category	Skin notation, Skin sensitization	
Slovenia - Occupational Exposure Limits		
OEL TWA	28 mg/m³	
OEL TWA [ppm]	5 ppm	
OEL STEL	112 mg/m³	
OEL STEL [ppm]	20 ppm	
OEL chemical category	Potential for cutaneous absorption	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	168 mg/m³	
VLA-ED (OEL TWA) [2]	30 ppm	
OEL chemical category	Sensitizer, skin - potential for cutaneous absorption	
Norway - Occupational Exposure Limits		
Grenseverdi (OEL TWA) [1]	140 mg/m³	
Grenseverdi (OEL TWA) [2]	25 ppm	
Korttidsverdi (OEL STEL)	175 mg/m³ (value calculated)	
Korttidsverdi (OEL STEL) [ppm]	37.5 ppm (value calculated)	
OEL chemical category	Allergenic substance	
Switzerland - Occupational Exposure Limits		
MAK (OEL TWA) [1]	40 mg/m³	
MAK (OEL TWA) [2]	7 ppm	
KZGW (OEL STEL)	80 mg/m³	
KZGW (OEL STEL) [ppm]	14 ppm	
OEL chemical category	Sensitizer	

# Safety Data Sheet

Parried and the (440 44 A)		
Benzyl acetate (140-11-4)		
Belgium - Occupational Exposure Limits		
OEL TWA	62 mg/m³	
OEL TWA [ppm]	10 ppm	
Denmark - Occupational Exposure Limits		
OEL TWA [1]	61 mg/m³	
OEL TWA [2]	10 ppm	
Ireland - Occupational Exposure Limits		
OEL TWA [2]	10 ppm	
OEL STEL [ppm]	30 ppm (calculated)	
Latvia - Occupational Exposure Limits		
OEL TWA	5 mg/m³	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	5 mg/m³	
Portugal - Occupational Exposure Limits		
OEL TWA [ppm]	10 ppm	
OEL chemical category	A4 - Not Classifiable as a Human Carcinogen	
Romania - Occupational Exposure Limits		
OEL TWA	50 mg/m³	
OEL TWA [ppm]	8 ppm	
OEL STEL	80 mg/m³	
OEL STEL [ppm]	13 ppm	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	62 mg/m³	
VLA-ED (OEL TWA) [2]	10 ppm	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA [ppm]	10 ppm	
ACGIH chemical category	Not Classifiable as a Human Carcinogen	
Benzyl alcohol (100-51-6)		
Bulgaria - Occupational Exposure Limits		
OEL TWA	5 mg/m³	
Czech Republic - Occupational Exposure Limits		
PEL (OEL TWA)	40 mg/m³	
Finland - Occupational Exposure Limits		
HTP (OEL TWA) [1]	45 mg/m³	
HTP (OEL TWA) [2]	10 ppm	
Germany - Occupational Exposure Limits (TRGS 900)		
AGW (OEL TWA) [1]	22 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)	

# Safety Data Sheet

Benzyl alcohol (100-51-6)	
AGW (OEL TWA) [2]	5 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Chemical category	Skin notation
Latvia - Occupational Exposure Limits	
OEL TWA	5 mg/m³
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	5 mg/m³
OEL chemical category	Skin notation
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	240 mg/m³
Slovenia - Occupational Exposure Limits	
OEL TWA	22 mg/m³
OEL TWA [ppm]	5 ppm
OEL STEL	44 mg/m³
OEL STEL [ppm]	10 ppm
OEL chemical category	Potential for cutaneous absorption
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA) [1]	22 mg/m³ (aerosol, vapour)
MAK (OEL TWA) [2]	5 ppm (aerosol, vapour)
OEL chemical category	Skin notation
Isobutyl acetate (110-19-0)	
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	240 mg/m³ (Butyl acetates)
MAK (OEL TWA) [ppm]	50 ppm (Butyl acetates)
MAK (OEL STEL)	480 mg/m³ (Butyl acetate)
MAK (OEL STEL) [ppm]	100 ppm (Butyl acetate)
Belgium - Occupational Exposure Limits	
OEL TWA	238 mg/m³
OEL TWA [ppm]	50 ppm
OEL STEL	712 mg/m³
OEL STEL [ppm]	150 ppm
Bulgaria - Occupational Exposure Limits	
OEL TWA	241 mg/m³
OEL TWA [ppm]	50 ppm
OEL STEL	723 mg/m³
OEL STEL [ppm]	150 ppm
Croatia - Occupational Exposure Limits	
GVI (OEL TWA) [1]	241 mg/m³
GVI (OEL TWA) [2]	50 ppm

# Safety Data Sheet

Isobutyl acetate (110-19-0)		
KGVI (OEL STEL)	723 mg/m³	
KGVI (OEL STEL) [ppm]	150 ppm	
Cyprus - Occupational Exposure Limits		
OEL TWA	241 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	723 mg/m³	
OEL STEL [ppm]	150 ppm	
Czech Republic - Occupational Exposure Limits		
PEL (OEL TWA)	241 mg/m³	
Denmark - Occupational Exposure Limits		
OEL TWA [1]	241 mg/m³ (Butyl acetate, all isomers)	
OEL TWA [2]	50 ppm (Butyl acetate, all isomers)	
Finland - Occupational Exposure Limits		
HTP (OEL TWA) [1]	240 mg/m³ (Butyl acetate)	
HTP (OEL TWA) [2]	50 ppm (Butyl acetate)	
HTP (OEL STEL)	725 mg/m³ (Butyl acetate)	
HTP (OEL STEL) [ppm]	150 ppm (Butyl acetate)	
France - Occupational Exposure Limits		
VME (OEL TWA)	710 mg/m³	
VME (OEL TWA) [ppm]	150 ppm	
VLE (OEL C/STEL)	940 mg/m³	
VLE (OEL C/STEL) [ppm]	200 ppm	
Germany - Occupational Exposure Limits (TRGS 90	0)	
AGW (OEL TWA) [1]	300 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)	
AGW (OEL TWA) [2]	62 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)	
Greece - Occupational Exposure Limits		
OEL TWA	241 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	723 mg/m³	
OEL STEL [ppm]	150 ppm	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	241 mg/m³	
CK (OEL STEL)	723 mg/m³	
OEL chemical category	Sensitizer	
Ireland - Occupational Exposure Limits		
OEL TWA [1]	241 mg/m³	
OEL TWA [2]	50 ppm	
OEL STEL	723 mg/m³ (calculated)	

# Safety Data Sheet

Isobutyl acetate (110-19-0)		
OEL STEL [ppm]	150 ppm (calculated)	
Italy - Occupational Exposure Limits		
OEL TWA	241 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	723 mg/m³	
OEL STEL [ppm]	150 ppm	
Latvia - Occupational Exposure Limits		
OEL TWA	241 mg/m³	
OEL TWA [ppm]	50 ppm	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	241 mg/m³	
IPRV (OEL TWA) [ppm]	50 ppm	
TPRV (OEL STEL)	723 mg/m³	
TPRV (OEL STEL) [ppm]	150 ppm	
Malta - Occupational Exposure Limits		
OEL TWA	241 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	723 mg/m³	
OEL STEL [ppm]	150 ppm	
Netherlands - Occupational Exposure Limits		
TGG-8u (OEL TWA)	241 mg/m³	
TGG-15min (OEL STEL)	723 mg/m³	
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	240 mg/m³	
NDSCh (OEL STEL)	720 mg/m³	
Portugal - Occupational Exposure Limits		
OEL TWA	241 mg/m³ (indicative limit value)	
OEL TWA [ppm]	50 ppm (indicative limit value)	
OEL STEL	723 mg/m³ (indicative limit value)	
OEL STEL [ppm]	150 ppm (indicative limit value)	
Romania - Occupational Exposure Limits		
OEL TWA	715 mg/m³	
OEL TWA [ppm]	150 ppm	
OEL STEL	950 mg/m³	
OEL STEL [ppm]	200 ppm	
Slovakia - Occupational Exposure Limits		
NPHV (OEL TWA) [1]	480 mg/m³	
NPHV (OEL TWA) [2]	100 ppm	
NPHV (OEL C)	700 mg/m³	

# Safety Data Sheet

Slovenis - Occupational Exposure Limits	Isobutyl acetate (110-19-0)		
OEL TWA [ppm]         50 ppm           OEL STEL         723 mg/m²           OEL STEL [ppm]         150 ppm           Spain - Occupational Exposure Limits         VLA-ED (OEL TWA) [r]         724 mg/m²           VLA-ED (OEL TWA) [r]         150 ppm           Sweden - Occupational Exposure Limits         NGV (OEL TWA)         241 mg/m² (Butyl acetates)           NGV (OEL TWA) [ppm]         50 ppm (Butyl acetates)           KTV (OEL STEL)         723 mg/m² (Butyl acetates)           KTV (OEL STEL) [ppm]         150 ppm (Butyl acetates)           WEL TWA (OEL TWA) [r]         724 mg/m²           WEL TWA (OEL TWA) [r]         724 mg/m²           WEL TWA (OEL TWA) [r]         150 ppm           WEL STEL (OEL STEL) [ppm]         187 ppm           Norway - Occupational Exposure Limits         724 mg/m²           Grenseverdi (OEL TWA) [r]         241 mg/m²           Grenseverdi (OEL TWA) [r]         241 mg/m²           Kortidsverdi (OEL STEL) [ppm]         150 ppm (value from the regulation)           Kortidsverdi (OEL STEL) [ppm]         150 ppm (value from the regulation)           Switzerland - Occupational Exposure Limits         MAK (OEL TWA) [r]           KZGW (OEL STEL) [ppm]         150 ppm (Butyl acetates, all isomers)           KZGW (OEL STEL) [ppm]         50 ppm </td <td colspan="3">Slovenia - Occupational Exposure Limits</td>	Slovenia - Occupational Exposure Limits		
DEL STEL   T23 mg/m²   150 ppm   1	OEL TWA	241 mg/m³	
DEL STEL [ppm]   150 ppm   150 ppm   Spain - Occupational Exposure Limits   724 mg/m²   VLA-ED (OEL TWA) [1]   724 mg/m²   VLA-ED (OEL TWA) [2]   150 ppm   Sweden - Occupational Exposure Limits   NGV (OEL TWA) [ppm]   50 ppm (Bulyl acetates)   NGV (OEL TWA) [ppm]   50 ppm (Bulyl acetates)   NGV (OEL STEL) [ppm]   150 ppm   NGV (OEL STEL) [ppm]   187 ppm   NGV (OEL STEL) [ppm]   187 ppm   NGV (OEL STEL) [ppm]   187 ppm   NGV (OEL STEL) [ppm]   NGV (OEL STEL) [ppm]   187 ppm   NGV (OEL STEL) [ppm]   150 ppm   NGV (OEL STEL) [ppm]   150 ppm (value from the regulation)   NGV (OEL STEL) [ppm]   150 ppm (value from the regulation)   NGV (OEL STEL) [ppm]   150 ppm (value from the regulation)   NGV (OEL STEL) [ppm]   150 ppm (value from the regulation)   NGV (OEL STEL) [ppm]   150 ppm   NGV (OEL STEL) [ppm]   150 ppm (NGV (OEL STEL) [ppm]	OEL TWA [ppm]	50 ppm	
Spain - Occupational Exposure Limits	OEL STEL	723 mg/m³	
VLA-ED (OEL TWA) [1]         724 mg/m²           VLA-ED (OEL TWA) [2]         150 ppm           Sweden - Occupational Exposure Limits         NGV (OEL TWA) [ppm]         50 ppm (Butyl acetates)           NGV (OEL TWA) [ppm]         50 ppm (Butyl acetates)         (KTV (OEL STEL) [ppm]         150 ppm (Butyl acetates)           KTV (OEL STEL) [ppm]         150 ppm (Butyl acetates)         (KTV (OEL STEL) [ppm]         150 ppm (Butyl acetates)           United Kingdom - Occupational Exposure Limits         WEL TWA (OEL TWA) [1]         724 mg/m²         (WEL TWA) (OEL TWA) [2]         150 ppm           WEL STEL (OEL STELL)         903 mg/m²         (WEL STEL) (OEL STELL) [ppm]         187 ppm           Norway - Occupational Exposure Limits         Grenseverdi (OEL TWA) [1]         241 mg/m²           Grenseverdi (OEL TWA) [2]         50 ppm           Kortidoverdi (OEL STEL) [ppm]         150 ppm (value from the regulation)           Switzerland - Occupational Exposure Limits         MAK (OEL TWA) [1]         240 mg/m²           MAK (OEL TWA) [2]         50 ppm           KZGW (OEL STEL) [ppm]         150 ppm (Butyl acetates, all isomers)           ACGIH OEL STEL [ppm]         50 ppm (Butyl acetates, all isomers)           ACGIH OEL TWA [ppm]         50 ppm (Butyl acetates, all isomers)           Dipropylene glycol monomethyl other (34590-94-8)         EU - Indic	OEL STEL [ppm]	150 ppm	
VLA-ED (OEL TWA) [2]   150 ppm	Spain - Occupational Exposure Limits		
Sweden - Occupational Exposure Limits  NGV (OEL TWA)	VLA-ED (OEL TWA) [1]	724 mg/m³	
NGV (OEL TWA)         241 mg/m² (Butyl acetates)           NGV (OEL TWA) [ppm]         50 ppm (Butyl acetates)           KTV (OEL STEL)         723 mg/m² (Butyl acetates)           KTV (OEL STEL) [ppm]         150 ppm (Butyl acetates)           United Kingdom - Occupational Exposure Limits           WEL TWA (OEL TWA) [1]         724 mg/m²           WEL TWA (OEL TWA) [2]         150 ppm           WEL STEL (OEL STEL) [ppm]         187 ppm           Norway - Occupational Exposure Limits         41 mg/m²           Grenseverdi (OEL TWA) [1]         241 mg/m²           Grenseverdi (OEL TWA) [2]         50 ppm           Kortidosverdi (OEL STEL) [ppm]         150 ppm (value from the regulation)           Kortidosverdi (OEL STEL) [ppm]         150 ppm (value from the regulation)           Switzerland - Occupational Exposure Limits         420 mg/m²           MAK (OEL TWA) [1]         240 mg/m²           MAK (OEL TWA) [2]         50 ppm           KZGW (OEL STEL) [ppm]         150 ppm (Butyl acetates, all isomers)           LZGW (OEL STEL) [ppm]         50 ppm (Butyl acetates, all isomers)           Dipropylene glycol monomethyl ether (34590-94-8)         50 ppm (Butyl acetates, all isomers)           USeL TWA [ppm]         50 ppm (Butyl acetates, all isomers)           LOEL TWA [ppm]         50 ppm <td>VLA-ED (OEL TWA) [2]</td> <td>150 ppm</td>	VLA-ED (OEL TWA) [2]	150 ppm	
NGV (OEL TWA) [ppm]         50 ppm (Butyl acetates)           KTV (OEL STEL)         723 mg/m² (Butyl acetates)           KTV (OEL STEL) [ppm]         150 ppm (Butyl acetates)           United Kingdom - Occupational Exposure Limits           WEL TWA (OEL TWA) [1]         724 mg/m²           WEL TWA (OEL TWA) [2]         150 ppm           WEL STEL (OEL STEL)         903 mg/m²           WEL STEL (OEL STEL) [ppm]         187 ppm           Norway - Occupational Exposure Limits         723 mg/m²           Grenseverdi (OEL TWA) [1]         241 mg/m³           Grenseverdi (OEL TWA) [2]         50 ppm           Korttidsverdi (OEL STEL)         723 mg/m² (value from the regulation)           Korttidsverdi (OEL STEL) [ppm]         150 ppm (value from the regulation)           Switzerland - Occupational Exposure Limits         AK (OEL TWA) [1]           MAK (OEL TWA) [1]         240 mg/m²           MAK (OEL TWA) [2]         50 ppm           KZGW (OEL STEL)         720 mg/m²           KZGW (OEL STEL) [ppm]         50 ppm (Butyl acetates, all isomers)           ACGIH OEL STEL [ppm]         50 ppm (Butyl acetates, all isomers)           ACGIH OEL STEL [ppm]         50 ppm (Butyl acetates, all isomers)           Dipropylene glycol monomethyl ether (34590-94-8)         EU - Indicative Occupational Exposure Limit (IOEL	Sweden - Occupational Exposure Limits		
KTV (OEL STEL)   723 mg/m³ (Butyl acetates)	NGV (OEL TWA)	241 mg/m³ (Butyl acetates)	
Mark   Coll   Stell	NGV (OEL TWA) [ppm]	50 ppm (Butyl acetates)	
United Kingdom - Occupational Exposure Limits  WEL TWA (OEL TWA) [1] 724 mg/m³  WEL TWA (OEL TWA) [2] 150 ppm  WEL STEL (OEL STEL) 903 mg/m³  WEL STEL (OEL STEL) 903 mg/m³  WEL STEL (OEL STEL) [ppm] 187 ppm  Norway - Occupational Exposure Limits  Grenseverdi (OEL TWA) [1] 241 mg/m³  Grenseverdi (OEL TWA) [2] 50 ppm  Kortidsverdi (OEL STEL) [ppm] 150 ppm (value from the regulation)  Kortidsverdi (OEL STEL) [ppm] 150 ppm (value from the regulation)  Switzerland - Occupational Exposure Limits  MAK (OEL TWA) [1] 240 mg/m³  MAK (OEL TWA) [2] 50 ppm  KZGW (OEL STEL) [ppm] 150 ppm  USA - ACGIH - Occupational Exposure Limits  ACGIH OEL TWA [ppm] 50 ppm (Butyl acetates, all isomers)  ACGIH OEL STEL [ppm] 150 ppm (Butyl acetates, all isomers)  Dipropylene glycol monomethyl ether (34590-94-8)  EU - Indicative Occupational Exposure Limit (IOEL)  IOEL TWA [ppm] 50 ppm  Remark Possibility of significant uptake through the skin  Austria - Occupational Exposure Limits  MAK (OEL TWA) 307 mg/m³ (mixed isomers)	KTV (OEL STEL)	723 mg/m³ (Butyl acetates)	
WEL TWA (OEL TWA) [1]         724 mg/m³           WEL TWA (OEL TWA) [2]         150 ppm           WEL STEL (OEL STEL)         903 mg/m³           WEL STEL (OEL STEL) [ppm]         187 ppm           Norway - Occupational Exposure Limits         Grenseverdi (OEL TWA) [1]         241 mg/m³           Grenseverdi (OEL TWA) [2]         50 ppm           Korttidsverdi (OEL STEL)         723 mg/m³ (value from the regulation)           Korttidsverdi (OEL STEL) [ppm]         150 ppm (value from the regulation)           Switzerland - Occupational Exposure Limits         MAK (OEL TWA) [1]         240 mg/m³           MAK (OEL TWA) [2]         50 ppm           KZGW (OEL STEL)         720 mg/m³           KZGW (OEL STEL) [ppm]         150 ppm           USA - ACGIH - Occupational Exposure Limits         ACGIH OEL TWA [ppm]         50 ppm (Butyl acetates, all isomers)           ACGIH OEL TWA [ppm]         50 ppm (Butyl acetates, all isomers)           Dipropylene glycol monomethyl ether (34590-94-8)         EU - Indicative Occupational Exposure Limit (IOEL)           IOEL TWA         308 mg/m³           IOEL TWA [ppm]         50 ppm           Remark         Possibility of significant uptake through the skin           Austria - Occupational Exposure Limits           MAK (OEL TWA)         307 mg/m³ (mixed isomers)	KTV (OEL STEL) [ppm]	150 ppm (Butyl acetates)	
WEL TWA (OEL TWA) [2]         150 ppm           WEL STEL (OEL STEL)         903 mg/m³           WEL STEL (OEL STEL) [ppm]         187 ppm           Norway - Occupational Exposure Limits           Grenseverdi (OEL TWA) [1]         241 mg/m³           Grenseverdi (OEL TWA) [2]         50 ppm           Korttidsverdi (OEL STEL)         723 mg/m³ (value from the regulation)           Korttidsverdi (OEL STEL) [ppm]         150 ppm (value from the regulation)           Switzerland - Occupational Exposure Limits         MAK (OEL TWA) [1]           MAK (OEL TWA) [2]         50 ppm           KZGW (OEL STEL)         720 mg/m³           KZGW (OEL STEL) [ppm]         150 ppm           USA - ACGIH - Occupational Exposure Limits         ACGIH OEL TWA [ppm]         50 ppm (Butyl acetates, all isomers)           ACGIH OEL STEL [ppm]         150 ppm (Butyl acetates, all isomers)         Dipropylene glycol monomethyl ether (34590-94-8)           EU - Indicative Occupational Exposure Limit (IOEL)         IOEL TWA         308 mg/m³           IOEL TWA [ppm]         50 ppm           Remark         Possibility of significant uptake through the skin           Austria - Occupational Exposure Limits           MAK (OEL TWA)         307 mg/m³ (mixed isomers)	United Kingdom - Occupational Exposure Limits		
WEL STEL (OEL STEL) 9903 mg/m³  WEL STEL (OEL STEL) [ppm] 187 ppm  Norway - Occupational Exposure Limits  Grenseverdi (OEL TWA) [1] 241 mg/m³  Grenseverdi (OEL TWA) [2] 50 ppm  Korttidsverdi (OEL STEL) 723 mg/m³ (value from the regulation)  Korttidsverdi (OEL STEL) [ppm] 150 ppm (value from the regulation)  Switzerland - Occupational Exposure Limits  MAK (OEL TWA) [1] 240 mg/m³  MAK (OEL TWA) [2] 50 ppm  KZGW (OEL STEL) [ppm] 150 ppm  LZGW (OEL STEL) [ppm] 150 ppm  USA - ACGIH - Occupational Exposure Limits  ACGIH OEL TWA [ppm] 50 ppm (Butyl acetates, all isomers)  ACGIH OEL STEL [ppm] 150 ppm (Butyl acetates, all isomers)  Dipropylene glycol monomethyl ether (34590-94-8)  EU - Indicative Occupational Exposure Limit (IOEL)  IOEL TWA [ppm] 50 ppm  Remark Possibility of significant uptake through the skin  Austria - Occupational Exposure Limits  MAK (OEL TWA) 307 mg/m³ (mixed isomers)	WEL TWA (OEL TWA) [1]	724 mg/m³	
WEL STEL (OEL STEL) [ppm] 187 ppm  Norway - Occupational Exposure Limits  Grenseverdi (OEL TWA) [1] 241 mg/m³  Grenseverdi (OEL TWA) [2] 50 ppm  Korttidsverdi (OEL STEL) 723 mg/m³ (value from the regulation)  Korttidsverdi (OEL STEL) [ppm] 150 ppm (value from the regulation)  Switzerland - Occupational Exposure Limits  MAK (OEL TWA) [1] 240 mg/m³  MAK (OEL TWA) [2] 50 ppm  KZGW (OEL STEL) [ppm] 150 ppm  USA - ACGIH - Occupational Exposure Limits  ACGIH OEL TWA [ppm] 50 ppm (Butyl acetates, all isomers)  ACGIH OEL STEL [ppm] 150 ppm (Butyl acetates, all isomers)  Dipropylene glycol monomethyl ether (34590-94-8)  EU - Indicative Occupational Exposure Limit (IOEL)  IOEL TWA 308 mg/m³  Remark Possibility of significant uptake through the skin  Austria - Occupational Exposure Limits  MAK (OEL TWA) 307 mg/m³ (mixed isomers)	WEL TWA (OEL TWA) [2]	150 ppm	
Norway - Occupational Exposure Limits  Grenseverdi (OEL TWA) [1] 241 mg/m³  Grenseverdi (OEL TWA) [2] 50 ppm  Korttidsverdi (OEL STEL) 723 mg/m³ (value from the regulation)  Korttidsverdi (OEL STEL) [ppm] 150 ppm (value from the regulation)  Switzerland - Occupational Exposure Limits  MAK (OEL TWA) [1] 240 mg/m³  MAK (OEL TWA) [2] 50 ppm  KZGW (OEL STEL) 720 mg/m³  KZGW (OEL STEL) [ppm] 150 ppm  USA - ACGIH - Occupational Exposure Limits  ACGIH OEL TWA [ppm] 50 ppm (Butyl acetates, all isomers)  ACGIH OEL STEL [ppm] 150 ppm (Butyl acetates, all isomers)  Dipropylene glycol monomethyl ether (34590-94-8)  EU - Indicative Occupational Exposure Limit (IOEL)  IOEL TWA [ppm] 50 ppm  Remark 9ossibility of significant uptake through the skin  Austria - Occupational Exposure Limits  MAK (OEL TWA) 307 mg/m³ (mixed isomers)	WEL STEL (OEL STEL)	903 mg/m³	
Grenseverdi (OEL TWA) [1] 241 mg/m³  Grenseverdi (OEL TWA) [2] 50 ppm  Korttidsverdi (OEL STEL) 723 mg/m³ (value from the regulation)  Korttidsverdi (OEL STEL) [ppm] 150 ppm (value from the regulation)  Switzerland - Occupational Exposure Limits  MAK (OEL TWA) [1] 240 mg/m³  MAK (OEL TWA) [2] 50 ppm  KZGW (OEL STEL) 720 mg/m³  KZGW (OEL STEL) [ppm] 150 ppm  USA - ACGIH - Occupational Exposure Limits  ACGIH OEL TWA [ppm] 50 ppm (Butyl acetates, all isomers)  ACGIH OEL STEL [ppm] 150 ppm (Butyl acetates, all isomers)  Dipropylene glycol monomethyl ether (34590-94-8)  EU - Indicative Occupational Exposure Limit (IOEL)  IOEL TWA 308 mg/m³  IOEL TWA [ppm] 50 ppm  Remark Possibility of significant uptake through the skin  Austria - Occupational Exposure Limits  MAK (OEL TWA) 307 mg/m³ (mixed isomers)	WEL STEL (OEL STEL) [ppm]	187 ppm	
Grenseverdi (OEL TWA) [2] 50 ppm  Korttidsverdi (OEL STEL) 723 mg/m³ (value from the regulation)  Korttidsverdi (OEL STEL) [ppm] 150 ppm (value from the regulation)  Switzerland - Occupational Exposure Limits  MAK (OEL TWA) [1] 240 mg/m³  MAK (OEL TWA) [2] 50 ppm  KZGW (OEL STEL) 720 mg/m³  KZGW (OEL STEL) [ppm] 150 ppm  USA - ACGIH - Occupational Exposure Limits  ACGIH OEL TWA [ppm] 50 ppm (Butyl acetates, all isomers)  ACGIH OEL STEL [ppm] 150 ppm (Butyl acetates, all isomers)  Dipropylene glycol monomethyl ether (34590-94-8)  EU - Indicative Occupational Exposure Limit (IOEL)  IOEL TWA 308 mg/m³  IOEL TWA [ppm] 50 ppm  Remark Possibility of significant uptake through the skin  Austria - Occupational Exposure Limits  MAK (OEL TWA) 307 mg/m³ (mixed isomers)	Norway - Occupational Exposure Limits		
Korttidsverdi (OEL STEL) [ppm] 150 ppm (value from the regulation)  Switzerland - Occupational Exposure Limits  MAK (OEL TWA) [1] 240 mg/m³  MAK (OEL TWA) [2] 50 ppm  KZGW (OEL STEL) [ppm] 150 ppm  WSA - ACGIH - Occupational Exposure Limits  ACGIH OEL TWA [ppm] 50 ppm (Butyl acetates, all isomers)  ACGIH OEL STEL [ppm] 150 ppm (Butyl acetates, all isomers)  Dipropylene glycol monomethyl ether (34590-94-8)  EU - Indicative Occupational Exposure Limit (IOEL)  IOEL TWA [ppm] 50 ppm  Remark Possibility of significant uptake through the skin  Austria - Occupational Exposure Limits  MAK (OEL TWA) 307 mg/m³ (mixed isomers)	Grenseverdi (OEL TWA) [1]	241 mg/m³	
Korttidsverdi (OEL STEL) [ppm] 150 ppm (value from the regulation)  Switzerland - Occupational Exposure Limits  MAK (OEL TWA) [1] 240 mg/m³  MAK (OEL TWA) [2] 50 ppm  KZGW (OEL STEL) 720 mg/m³  KZGW (OEL STEL) 150 ppm 150 ppm  USA - ACGIH - Occupational Exposure Limits  ACGIH OEL TWA [ppm] 50 ppm (Butyl acetates, all isomers)  ACGIH OEL STEL [ppm] 150 ppm (Butyl acetates, all isomers)  Dipropylene glycol monomethyl ether (34590-94-8)  EU - Indicative Occupational Exposure Limit (IOEL)  IOEL TWA 308 mg/m³  IOEL TWA [ppm] 50 ppm  Remark Possibility of significant uptake through the skin  Austria - Occupational Exposure Limits  MAK (OEL TWA) 307 mg/m³ (mixed isomers)	Grenseverdi (OEL TWA) [2]	50 ppm	
Switzerland - Occupational Exposure Limits  MAK (OEL TWA) [1] 240 mg/m³  MAK (OEL TWA) [2] 50 ppm  KZGW (OEL STEL) 720 mg/m³  KZGW (OEL STEL) [ppm] 150 ppm  USA - ACGIH - Occupational Exposure Limits  ACGIH OEL TWA [ppm] 50 ppm (Butyl acetates, all isomers)  ACGIH OEL STEL [ppm] 150 ppm (Butyl acetates, all isomers)  Dipropylene glycol monomethyl ether (34590-94-8)  EU - Indicative Occupational Exposure Limit (IOEL)  IOEL TWA 308 mg/m³  IOEL TWA [ppm] 50 ppm  Remark Possibility of significant uptake through the skin  Austria - Occupational Exposure Limits  MAK (OEL TWA) 307 mg/m³ (mixed isomers)	Korttidsverdi (OEL STEL)	723 mg/m³ (value from the regulation)	
MAK (OEL TWA) [1]  MAK (OEL TWA) [2]  MAK (OEL TWA) [2]  EXEGW (OEL STEL)  MAK (OEL TWA [ppm]  MAK (OEL TWA)	Korttidsverdi (OEL STEL) [ppm]	150 ppm (value from the regulation)	
MAK (OEL TWA) [2] 50 ppm  KZGW (OEL STEL) 720 mg/m³  KZGW (OEL STEL) [ppm] 150 ppm  USA - ACGIH - Occupational Exposure Limits  ACGIH OEL TWA [ppm] 50 ppm (Butyl acetates, all isomers)  ACGIH OEL STEL [ppm] 150 ppm (Butyl acetates, all isomers)  Dipropylene glycol monomethyl ether (34590-94-8)  EU - Indicative Occupational Exposure Limit (IOEL)  IOEL TWA 308 mg/m³  IOEL TWA [ppm] 50 ppm  Remark Possibility of significant uptake through the skin  Austria - Occupational Exposure Limits  MAK (OEL TWA) 307 mg/m³ (mixed isomers)	Switzerland - Occupational Exposure Limits		
KZGW (OEL STEL) [ppm] 150 ppm  USA - ACGIH - Occupational Exposure Limits  ACGIH OEL TWA [ppm] 50 ppm (Butyl acetates, all isomers)  ACGIH OEL STEL [ppm] 150 ppm (Butyl acetates, all isomers)  Dipropylene glycol monomethyl ether (34590-94-8)  EU - Indicative Occupational Exposure Limit (IOEL)  IOEL TWA 308 mg/m³  IOEL TWA [ppm] 50 ppm  Remark Possibility of significant uptake through the skin  Austria - Occupational Exposure Limits  MAK (OEL TWA) 307 mg/m³ (mixed isomers)	MAK (OEL TWA) [1]	240 mg/m³	
KZGW (OEL STEL) [ppm] 150 ppm  USA - ACGIH - Occupational Exposure Limits  ACGIH OEL TWA [ppm] 50 ppm (Butyl acetates, all isomers)  ACGIH OEL STEL [ppm] 150 ppm (Butyl acetates, all isomers)  Dipropylene glycol monomethyl ether (34590-94-8)  EU - Indicative Occupational Exposure Limit (IOEL)  IOEL TWA 308 mg/m³  IOEL TWA [ppm] 50 ppm  Remark Possibility of significant uptake through the skin  Austria - Occupational Exposure Limits  MAK (OEL TWA) 307 mg/m³ (mixed isomers)	MAK (OEL TWA) [2]	50 ppm	
USA - ACGIH - Occupational Exposure Limits  ACGIH OEL TWA [ppm] 50 ppm (Butyl acetates, all isomers)  ACGIH OEL STEL [ppm] 150 ppm (Butyl acetates, all isomers)  Dipropylene glycol monomethyl ether (34590-94-8)  EU - Indicative Occupational Exposure Limit (IOEL)  IOEL TWA 308 mg/m³  IOEL TWA [ppm] 50 ppm  Remark Possibility of significant uptake through the skin  Austria - Occupational Exposure Limits  MAK (OEL TWA) 307 mg/m³ (mixed isomers)	KZGW (OEL STEL)	720 mg/m³	
ACGIH OEL TWA [ppm] 50 ppm (Butyl acetates, all isomers)  ACGIH OEL STEL [ppm] 150 ppm (Butyl acetates, all isomers)  Dipropylene glycol monomethyl ether (34590-94-8)  EU - Indicative Occupational Exposure Limit (IOEL)  IOEL TWA 308 mg/m³  IOEL TWA [ppm] 50 ppm  Remark Possibility of significant uptake through the skin  Austria - Occupational Exposure Limits  MAK (OEL TWA) 307 mg/m³ (mixed isomers)	KZGW (OEL STEL) [ppm]	150 ppm	
ACGIH OEL STEL [ppm] 150 ppm (Butyl acetates, all isomers)  Dipropylene glycol monomethyl ether (34590-94-8)  EU - Indicative Occupational Exposure Limit (IOEL)  IOEL TWA 308 mg/m³  IOEL TWA [ppm] 50 ppm  Remark Possibility of significant uptake through the skin  Austria - Occupational Exposure Limits  MAK (OEL TWA) 307 mg/m³ (mixed isomers)	USA - ACGIH - Occupational Exposure Limits		
Dipropylene glycol monomethyl ether (34590-94-8)  EU - Indicative Occupational Exposure Limit (IOEL)  IOEL TWA 308 mg/m³  IOEL TWA [ppm] 50 ppm  Remark Possibility of significant uptake through the skin  Austria - Occupational Exposure Limits  MAK (OEL TWA) 307 mg/m³ (mixed isomers)	ACGIH OEL TWA [ppm]	50 ppm (Butyl acetates, all isomers)	
EU - Indicative Occupational Exposure Limit (IOEL)  IOEL TWA 308 mg/m³  IOEL TWA [ppm] 50 ppm  Remark Possibility of significant uptake through the skin  Austria - Occupational Exposure Limits  MAK (OEL TWA) 307 mg/m³ (mixed isomers)	ACGIH OEL STEL [ppm]	150 ppm (Butyl acetates, all isomers)	
IOEL TWA 308 mg/m³  IOEL TWA [ppm] 50 ppm  Remark Possibility of significant uptake through the skin  Austria - Occupational Exposure Limits  MAK (OEL TWA) 307 mg/m³ (mixed isomers)	Dipropylene glycol monomethyl ether (34590-	94-8)	
IOEL TWA [ppm] 50 ppm  Remark Possibility of significant uptake through the skin  Austria - Occupational Exposure Limits  MAK (OEL TWA) 307 mg/m³ (mixed isomers)	EU - Indicative Occupational Exposure Limit (IOEL)		
Remark Possibility of significant uptake through the skin  Austria - Occupational Exposure Limits  MAK (OEL TWA) 307 mg/m³ (mixed isomers)	IOEL TWA	308 mg/m³	
Austria - Occupational Exposure Limits  MAK (OEL TWA)  307 mg/m³ (mixed isomers)	IOEL TWA [ppm]	50 ppm	
MAK (OEL TWA) 307 mg/m³ (mixed isomers)	Remark	Possibility of significant uptake through the skin	
	Austria - Occupational Exposure Limits		
MAK (OEL TWA) [ppm] 50 ppm (mixed isomers)	MAK (OEL TWA)	307 mg/m³ (mixed isomers)	
	MAK (OEL TWA) [ppm]	50 ppm (mixed isomers)	

# Safety Data Sheet

Dipropylene glycol monomethyl ether (34590-94-8)		
MAK (OEL STEL)	614 mg/m³ (isomers mixtures)	
MAK (OEL STEL) [ppm]	100 ppm (isomers mixtures)	
OEL chemical category	Skin notation	
Belgium - Occupational Exposure Limits		
OEL TWA	308 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL chemical category	Skin, Skin notation	
Bulgaria - Occupational Exposure Limits		
OEL TWA	308 mg/m³	
OEL TWA [ppm]	50 ppm	
Croatia - Occupational Exposure Limits		
GVI (OEL TWA) [1]	308 mg/m³	
GVI (OEL TWA) [2]	50 ppm	
OEL chemical category	Skin notation	
Cyprus - Occupational Exposure Limits		
OEL TWA	308 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL chemical category	Skin-potential for cutaneous absorption	
Czech Republic - Occupational Exposure Limits		
PEL (OEL TWA)	270 mg/m³	
OEL chemical category	Potential for cutaneous absorption	
Denmark - Occupational Exposure Limits		
OEL TWA [1]	309 mg/m³	
OEL TWA [2]	50 ppm	
OEL chemical category	Potential for cutaneous absorption	
Estonia - Occupational Exposure Limits		
OEL TWA	308 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL chemical category	Skin notation	
Finland - Occupational Exposure Limits		
HTP (OEL TWA) [1]	310 mg/m³	
HTP (OEL TWA) [2]	50 ppm	
OEL chemical category	Potential for cutaneous absorption	
France - Occupational Exposure Limits		
VME (OEL TWA)	308 mg/m³ (restrictive limit)	
VME (OEL TWA) [ppm]	50 ppm (restrictive limit)	
OEL chemical category	Risk of cutaneous absorption	
Germany - Occupational Exposure Limits (TRGS 90	0)	
AGW (OEL TWA) [1]	310 mg/m³ (isomer mixture)	

# Safety Data Sheet

Dipropylene glycol monomethyl ether (34590-94-8)		
AGW (OEL TWA) [2]	50 ppm (isomer mixture)	
Gibraltar - Occupational Exposure Limits		
OEL TWA	308 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL chemical category	Skin notation	
Greece - Occupational Exposure Limits		
OEL TWA	600 mg/m³	
OEL TWA [ppm]	100 ppm	
OEL STEL	900 mg/m³	
OEL STEL [ppm]	150 ppm	
OEL chemical category	skin - potential for cutaneous absorption	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	308 mg/m³	
Ireland - Occupational Exposure Limits		
OEL TWA [1]	308 mg/m³ ((2-Methoxymethylethoxy)propanol)	
OEL TWA [2]	50 ppm ((2-Methoxymethylethoxy)propanol)	
OEL STEL	924 mg/m³ (calculated (2-(2-Methoxypropoxy)-1-propanol)	
OEL STEL [ppm]	150 ppm (calculated (2-(2-Methoxypropoxy)-1-propanol)	
OEL chemical category	Potential for cutaneous absorption	
Italy - Occupational Exposure Limits		
OEL TWA	308 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL chemical category	skin - potential for cutaneous absorption	
Latvia - Occupational Exposure Limits		
OEL TWA	308 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL chemical category	skin - potential for cutaneous exposure	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	300 mg/m³ (2-(2-Methoxypropoxy)-propanol)	
IPRV (OEL TWA) [ppm]	50 ppm (2-(2-Methoxypropoxy)-propanol)	
TPRV (OEL STEL)	450 mg/m³ (2-(2-Methoxypropoxy)-propanol)	
TPRV (OEL STEL) [ppm]	75 ppm (2-(2-Methoxypropoxy)-propanol)	
OEL chemical category	Skin notation	
Luxembourg - Occupational Exposure Limits		
OEL TWA	308 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL chemical category	Possibility of significant uptake through the skin	
Malta - Occupational Exposure Limits		
OEL TWA	308 mg/m³	

# Safety Data Sheet

Dipropylene glycol monomethyl ether (34590-94-8)			
OEL TWA [ppm]	50 ppm		
OEL chemical category	Possibility of significant uptake through the skin		
Netherlands - Occupational Exposure Limits	Netherlands - Occupational Exposure Limits		
TGG-8u (OEL TWA)	300 mg/m³		
Poland - Occupational Exposure Limits			
NDS (OEL TWA)	240 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol and 2-(2-Methoxy-1-methylethoxy)propan-1-ol)		
NDSCh (OEL STEL)	480 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol)		
Portugal - Occupational Exposure Limits			
OEL TWA	308 mg/m³ (indicative limit value)		
OEL TWA [ppm]	50 ppm (indicative limit value)		
OEL STEL [ppm]	150 ppm		
OEL chemical category	skin - potential for cutaneous exposure indicative limit value		
Romania - Occupational Exposure Limits			
OEL TWA	308 mg/m³		
OEL TWA [ppm]	50 ppm		
OEL chemical category	Skin notation		
Slovakia - Occupational Exposure Limits			
NPHV (OEL TWA) [1]	308 mg/m³		
NPHV (OEL TWA) [2]	50 ppm		
OEL chemical category	Potential for cutaneous absorption		
Slovenia - Occupational Exposure Limits			
OEL TWA	308 mg/m³		
OEL TWA [ppm]	50 ppm		
OEL STEL	308 mg/m³		
OEL STEL [ppm]	50 ppm		
OEL chemical category	Potential for cutaneous absorption		
Spain - Occupational Exposure Limits			
VLA-ED (OEL TWA) [1]	308 mg/m³ (indicative limit value)		
VLA-ED (OEL TWA) [2]	50 ppm (indicative limit value)		
OEL chemical category	skin - potential for cutaneous absorption		
Sweden - Occupational Exposure Limits			
NGV (OEL TWA)	300 mg/m³		
NGV (OEL TWA) [ppm]	50 ppm		
KTV (OEL STEL)	450 mg/m³		
KTV (OEL STEL) [ppm]	75 ppm		
OEL chemical category	Skin notation		
United Kingdom - Occupational Exposure Limits			
WEL TWA (OEL TWA) [1]	308 mg/m³		

# Safety Data Sheet

Dipropylene glycol monomethyl ether (34590-94-8)		
WEL TWA (OEL TWA) [2]	50 ppm	
WEL STEL (OEL STEL)	924 mg/m³ (calculated)	
WEL STEL (OEL STEL) [ppm]	150 ppm (calculated)	
WEL chemical category	Potential for cutaneous absorption	
Norway - Occupational Exposure Limits		
Grenseverdi (OEL TWA) [1]	300 mg/m³	
Grenseverdi (OEL TWA) [2]	50 ppm	
Korttidsverdi (OEL STEL)	375 mg/m³ (value calculated)	
Korttidsverdi (OEL STEL) [ppm]	75 ppm (value calculated)	
OEL chemical category	Skin notation	
Switzerland - Occupational Exposure Limits		
MAK (OEL TWA) [1]	300 mg/m³ (aerosol, vapour)	
MAK (OEL TWA) [2]	50 ppm (aerosol, vapour)	
KZGW (OEL STEL)	300 mg/m³ (aerosol, vapour)	
KZGW (OEL STEL) [ppm]	50 ppm (aerosol, vapour)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA [ppm]	100 ppm	
ACGIH OEL STEL [ppm]	150 ppm	
ACGIH chemical category	Skin - potential significant contribution to overall exposure by the cutaneous route	
.alphaPinene (80-56-8)		
.alphaPinene (80-56-8)		
.alphaPinene (80-56-8)  Belgium - Occupational Exposure Limits		
	20 ppm	
Belgium - Occupational Exposure Limits	20 ppm	
Belgium - Occupational Exposure Limits OEL TWA [ppm]	20 ppm 150 mg/m³	
Belgium - Occupational Exposure Limits  OEL TWA [ppm]  Estonia - Occupational Exposure Limits		
Belgium - Occupational Exposure Limits  OEL TWA [ppm]  Estonia - Occupational Exposure Limits  OEL TWA	150 mg/m³	
Belgium - Occupational Exposure Limits  OEL TWA [ppm]  Estonia - Occupational Exposure Limits  OEL TWA  OEL TWA [ppm]	150 mg/m³ 25 ppm	
Belgium - Occupational Exposure Limits  OEL TWA [ppm]  Estonia - Occupational Exposure Limits  OEL TWA  OEL TWA [ppm]  OEL STEL	150 mg/m³ 25 ppm 300 mg/m³	
Belgium - Occupational Exposure Limits  OEL TWA [ppm]  Estonia - Occupational Exposure Limits  OEL TWA  OEL TWA [ppm]  OEL STEL  OEL STEL [ppm]	150 mg/m³ 25 ppm 300 mg/m³	
Belgium - Occupational Exposure Limits  OEL TWA [ppm]  Estonia - Occupational Exposure Limits  OEL TWA  OEL TWA [ppm]  OEL STEL  OEL STEL [ppm]  Lithuania - Occupational Exposure Limits	150 mg/m³ 25 ppm 300 mg/m³ 50 ppm	
Belgium - Occupational Exposure Limits  OEL TWA [ppm]  Estonia - Occupational Exposure Limits  OEL TWA  OEL TWA [ppm]  OEL STEL  OEL STEL [ppm]  Lithuania - Occupational Exposure Limits  IPRV (OEL TWA)	150 mg/m³ 25 ppm 300 mg/m³ 50 ppm  150 mg/m³	
Belgium - Occupational Exposure Limits  OEL TWA [ppm]  Estonia - Occupational Exposure Limits  OEL TWA  OEL TWA [ppm]  OEL STEL  OEL STEL [ppm]  Lithuania - Occupational Exposure Limits  IPRV (OEL TWA)  IPRV (OEL TWA) [ppm]	150 mg/m³ 25 ppm 300 mg/m³ 50 ppm  150 mg/m³ 25 ppm	
Belgium - Occupational Exposure Limits  OEL TWA [ppm]  Estonia - Occupational Exposure Limits  OEL TWA  OEL TWA [ppm]  OEL STEL  OEL STEL [ppm]  Lithuania - Occupational Exposure Limits  IPRV (OEL TWA)  IPRV (OEL TWA) [ppm]  TPRV (OEL STEL)	150 mg/m³ 25 ppm 300 mg/m³ 50 ppm  150 mg/m³ 25 ppm 300 mg/m³	
Belgium - Occupational Exposure Limits  OEL TWA [ppm]  Estonia - Occupational Exposure Limits  OEL TWA  OEL TWA [ppm]  OEL STEL  OEL STEL [ppm]  Lithuania - Occupational Exposure Limits  IPRV (OEL TWA)  IPRV (OEL TWA) [ppm]  TPRV (OEL STEL)  TPRV (OEL STEL) [ppm]	150 mg/m³ 25 ppm 300 mg/m³ 50 ppm  150 mg/m³ 25 ppm 300 mg/m³	
Belgium - Occupational Exposure Limits  OEL TWA [ppm]  Estonia - Occupational Exposure Limits  OEL TWA  OEL TWA [ppm]  OEL STEL  OEL STEL [ppm]  Lithuania - Occupational Exposure Limits  IPRV (OEL TWA)  IPRV (OEL TWA) [ppm]  TPRV (OEL STEL)  TPRV (OEL STEL)  TPRV (OEL STEL) [ppm]  Portugal - Occupational Exposure Limits	150 mg/m³ 25 ppm 300 mg/m³ 50 ppm  150 mg/m³ 25 ppm 300 mg/m³ 50 ppm	
Belgium - Occupational Exposure Limits  OEL TWA [ppm]  Estonia - Occupational Exposure Limits  OEL TWA  OEL TWA [ppm]  OEL STEL  OEL STEL [ppm]  Lithuania - Occupational Exposure Limits  IPRV (OEL TWA)  IPRV (OEL TWA) [ppm]  TPRV (OEL STEL)  TPRV (OEL STEL) [ppm]  Portugal - Occupational Exposure Limits  OEL TWA [ppm]	150 mg/m³ 25 ppm 300 mg/m³ 50 ppm  150 mg/m³ 25 ppm 300 mg/m³ 25 ppm 300 mg/m³ 50 ppm	
Belgium - Occupational Exposure Limits  OEL TWA [ppm]  Estonia - Occupational Exposure Limits  OEL TWA  OEL TWA [ppm]  OEL STEL  OEL STEL [ppm]  Lithuania - Occupational Exposure Limits  IPRV (OEL TWA)  IPRV (OEL TWA) [ppm]  TPRV (OEL STEL)  TPRV (OEL STEL) [ppm]  Portugal - Occupational Exposure Limits  OEL TWA [ppm]  OEL chemical category	150 mg/m³ 25 ppm 300 mg/m³ 50 ppm  150 mg/m³ 25 ppm 300 mg/m³ 25 ppm 300 mg/m³ 50 ppm	
Belgium - Occupational Exposure Limits  OEL TWA [ppm]  Estonia - Occupational Exposure Limits  OEL TWA  OEL TWA [ppm]  OEL STEL  OEL STEL [ppm]  Lithuania - Occupational Exposure Limits  IPRV (OEL TWA)  IPRV (OEL TWA) [ppm]  TPRV (OEL STEL)  TPRV (OEL STEL)  TPRV (OEL STEL) [ppm]  Portugal - Occupational Exposure Limits  OEL TWA [ppm]  OEL chemical category  Spain - Occupational Exposure Limits	150 mg/m³ 25 ppm 300 mg/m³ 50 ppm  150 mg/m³ 25 ppm 300 mg/m³ 25 ppm 300 mg/m³ 50 ppm  20 ppm (Turpentine and selected Monoterpenes) Sensitizer, A4 - Not Classifiable as a Human Carcinogen	

# Safety Data Sheet

.alphaPinene (80-56-8)		
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	150 mg/m³	
NGV (OEL TWA) [ppm]	25 ppm	
KTV (OEL STEL)	300 mg/m³	
KTV (OEL STEL) [ppm]	50 ppm	
OEL chemical category	Sensitizer	
Norway - Occupational Exposure Limits		
Grenseverdi (OEL TWA) [1]	140 mg/m³	
Grenseverdi (OEL TWA) [2]	25 ppm	
Korttidsverdi (OEL STEL)	175 mg/m³ (value calculated)	
Korttidsverdi (OEL STEL) [ppm]	37.5 ppm (value calculated)	
OEL chemical category	Skin notation	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA [ppm]	20 ppm (Turpentine and selected monoterpenes)	
ACGIH chemical category	Not Classifiable as a Human Carcinogen, dermal sensitizer	
.betaPinene (127-91-3)		
Belgium - Occupational Exposure Limits		
OEL TWA [ppm]	20 ppm	
Estonia - Occupational Exposure Limits		
OEL TWA	150 mg/m³	
OEL TWA [ppm]	25 ppm	
OEL STEL	300 mg/m³	
OEL STEL [ppm]	50 ppm	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	150 mg/m³	
IPRV (OEL TWA) [ppm]	25 ppm	
TPRV (OEL STEL)	300 mg/m³	
TPRV (OEL STEL) [ppm]	50 ppm	
Portugal - Occupational Exposure Limits		
OEL TWA [ppm]	20 ppm (Turpentine and selected Monoterpenes)	
OEL chemical category	Sensitizer, A4 - Not Classifiable as a Human Carcinogen	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	113 mg/m³	
VLA-ED (OEL TWA) [2]	20 ppm	
OEL chemical category	Sensitizer	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	150 mg/m³	
NGV (OEL TWA) [ppm]	25 ppm	
KTV (OEL STEL)	300 mg/m³	

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

.betaPinene (127-91-3)		
KTV (OEL STEL) [ppm]	50 ppm	
OEL chemical category	Sensitizer	
Norway - Occupational Exposure Limits		
Grenseverdi (OEL TWA) [1]	140 mg/m³	
Grenseverdi (OEL TWA) [2]	25 ppm	
Korttidsverdi (OEL STEL)	175 mg/m³ (value calculated)	
Korttidsverdi (OEL STEL) [ppm]	37.5 ppm (value calculated)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA [ppm]	20 ppm (Turpentine and selected monoterpenes)	
ACGIH chemical category	Not Classifiable as a Human Carcinogen, dermal sensitizer	

#### 8.1.2. Recommended monitoring procedures

No additional information available

#### 8.1.3. Air contaminants formed

No additional information available

#### 8.1.4. DNEL and PNEC

No additional information available

#### 8.1.5. Control banding

No additional information available

#### 8.2. Exposure controls

## 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

#### 8.2.2. Personal protection equipment

#### Personal protective equipment:

Avoid all unnecessary exposure.

#### Personal protective equipment symbol(s):





#### 8.2.2.1. Eye and face protection

#### Eye protection:

Chemical goggles or safety glasses. Safety glasses

#### 8.2.2.2. Skin protection

#### Skin and body protection:

Wear suitable protective clothing

#### Hand protection:

Wear protective gloves.

## 8.2.2.3. Respiratory protection

## Respiratory protection:

Wear appropriate mask

## 8.2.2.4. Thermal hazards

No additional information available

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

#### 8.2.3. Environmental exposure controls

#### **Environmental exposure controls:**

Avoid release to the environment.

#### Other information:

Do not eat, drink or smoke during use.

### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state : Liquid

Colour : light yellow. amber. Conforms to standard.

: Not applicable

Odour : characteristic. : Not available Odour threshold : Not applicable Melting point Freezing point : Not available : Not available Boiling point Flammability : Not applicable : Not available **Explosive limits** : Not available Lower explosion limit : Not available Upper explosion limit : 64 °C Flash point Auto-ignition temperature : Not available Decomposition temperature Not available : Not available рΗ Viscosity, kinematic : Not available Solubility : Not available Partition coefficient n-octanol/water (Log Kow) : Not available Vapour pressure : Not available Vapour pressure at 50°C : Not available Density : Not available Relative density · ≈ 0.93 Relative vapour density at 20°C : Not available

#### 9.2. Other information

Particle characteristics

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

## 9.2.2. Other safety characteristics

No additional information available

### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

#### 10.2. Chemical stability

Not established.

#### 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

#### 10.5. Incompatible materials

Strong acids. Strong bases.

# Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

## 10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

## **SECTION 11: Toxicological information**

44 .	4   1   6   1   1   1   1   1   1   1   1	المسمعا متم	-1	منا المحملة ما	Describéles	(EC) No.	4070/0000
11.	1. Information	on nazaro (	diasses as	s defined in	Redulation	(EC) NO	12/2/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Acute toxicity (dermal) : Acute toxicity (inhalation) :	Not classified  Not classified	
Citral (5392-40-5)		
LD50 oral rat	4960 mg/kg	
LD50 dermal rabbit	2250 mg/kg	
d-Limonene (5989-27-5)		
LD50 oral rat	4400 mg/kg	
LD50 dermal rabbit	> 5 g/kg	
Benzyl acetate (140-11-4)		
LD50 oral rat	2490 mg/kg	
LD50 oral	2490 mg/kg bodyweight	
LD50 dermal rabbit	> 5000 mg/kg	
Benzyl alcohol (100-51-6)		
LD50 oral rat	1230 mg/kg	
LD50 oral	1620 mg/kg bodyweight	
LD50 dermal	2500 mg/kg bodyweight	
Linalool (78-70-6)		
LD50 oral	2790 mg/kg bodyweight	
Amyl salicylate (2050-08-0)		
LD50 oral rat	4100 mg/kg	
LD50 oral	2000 mg/kg bodyweight	
LD50 dermal rabbit	> 5000 mg/kg	
Terpinyl acetate (80-26-2)		
LD50 oral rat	5075 mg/kg	
Eugenol (97-53-0)		
LD50 oral rat	1930 mg/kg	
LD50 oral	2500 mg/kg bodyweight	
Isobutyl acetate (110-19-0)		
LD50 oral rat	15400 mg/kg	
LD50 dermal rabbit	> 17400 mg/kg	
Orange oil (8008-57-9)		
LD50 oral rat	4400 mg/kg	
LD50 dermal rabbit	> 5000 mg/kg	

# Safety Data Sheet

Sandela (66068-84-6)			
LD50 dermal rat	> 2000 mg/kg		
LC50 Inhalation - Rat	> 5.27 mg/l/4h		
Triplal (Vertocitral) (68039-49-6)			
LD50 oral	3900 mg/kg bodyweight		
Dipropylene glycol monomethyl ether (34590-	94-8)		
LD50 oral rat	5.35 g/kg		
LD50 dermal rabbit	9500 mg/kg		
.alphaPinene (80-56-8)			
LD50 oral rat	3700 mg/kg		
LD50 oral	500 mg/kg bodyweight		
LD50 dermal rat	> 5000 mg/kg		
.betaPinene (127-91-3)			
LD50 oral rat	> 5000 mg/kg		
LD50 dermal rabbit	> 5000 mg/kg		
Rosemary Oil (8000-25-7)			
LD50 oral rat	5 g/kg		
zingiber officinale (ginger) root oil (8007-08-7)	zingiber officinale (ginger) root oil (8007-08-7)		
LD50 oral rat	> 5 g/kg		
COUMARIN (91-64-5)			
LD50 oral rat	> 5000 mg/kg		
LD50 oral	290 mg/kg bodyweight		
LD50 dermal rat	293 mg/kg		
	Causes skin irritation.  Not classified		
Serious eye damage/irritation : Respiratory or skin sensitisation :	May cause an allergic skin reaction.		
•	Not classified		
Carcinogenicity :	Not classified		
d-Limonene (5989-27-5)			
IARC group	3 - Not classifiable		
Benzyl acetate (140-11-4)			
IARC group	3 - Not classifiable		
Eugenol (97-53-0)			
IARC group	3 - Not classifiable		
COUMARIN (91-64-5)			
IARC group	3 - Not classifiable		
•	Not classified Not classified		
Isobutyl acetate (110-19-0)	THUL GIASSIIIGU		
STOT-single exposure	May cause drowsiness or dizziness.		
	<u> </u>		

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Rosemary Oil (8000-25-7)	
STOT-single exposure	May cause damage to organs.
STOT-repeated exposure :	Not classified
Aspiration hazard :	Not classified
Orange oil (8008-57-9)	
Hydrocarbon	Yes

### 11.2. Information on other hazards

#### 11.2.1. Endocrine disrupting properties

No additional information available

#### 11.2.2. Other information

Potential adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met

## **SECTION 12: Ecological information**

## 12.1. Toxicity

: Harmful to aquatic life with long lasting effects. Ecology - general

Hazardous to the aquatic environment, short-term : Not classified

Hazardous to the aquatic environment, long-term : Harmful to aquatic life with long lasting effects.

(chronic)		
Citral (5392-40-5)		
EC50 - Crustacea [1]	7 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
EC50 72h - Algae [1]	16 mg/l (Species: Desmodesmus subspicatus)	
EC50 96h - Algae [1]	19 mg/l (Species: Desmodesmus subspicatus)	
d-Limonene (5989-27-5)		
LC50 - Fish [1]	0.619 – 0.796 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])	
LC50 - Fish [2]	35 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)	
Benzyl alcohol (100-51-6)		
LC50 - Fish [1]	460 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])	
LC50 - Fish [2]	10 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])	
EC50 - Crustacea [1]	23 mg/l (Exposure time: 48 h - Species: water flea)	
Linalool (78-70-6)		
EC50 96h - Algae [1]	88.3 mg/l (Species: Desmodesmus subspicatus)	
Terpinyl acetate (80-26-2)		
LC50 - Fish [1]	> 11 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])	
Eugenol (97-53-0)		
LC50 - Fish [1]	13 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static])	
Isobutyl acetate (110-19-0)		
LC50 - Fish [1]	17 mg/l (Exposure time: 96 h - Species: Oryzias latipes)	
Dipropylene glycol monomethyl ether (34590-94-8)		
LC50 - Fish [1]	> 10000 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])	

# Safety Data Sheet

Dipropylene glycol monomethyl ether (34590-94-8)			
EC50 - Crustacea [1]	1919 mg/l (Exposure time: 48 h - Species: Daphnia magna)		
.alphaPinene (80-56-8)			
LC50 - Fish [1]	0.28 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])		
EC50 - Crustacea [1]	41 mg/l (Exposure time: 48 h - Species: Daphnia magna)		
12.2. Persistence and degradability			
BANANA & GINGER LILY #EU48594F			
Persistence and degradability	Not established.		
12.3. Bioaccumulative potential			
BANANA & GINGER LILY #EU48594F			
Bioaccumulative potential	Not established.		
Isoamyl acetate (123-92-2)			
Partition coefficient n-octanol/water (Log Pow)	2.7 (at 35 °C)		
Citral (5392-40-5)			
Partition coefficient n-octanol/water (Log Pow)	2.76 (at 25 °C)		
d-Limonene (5989-27-5)			
Partition coefficient n-octanol/water (Log Pow)	4.38 (at 37 °C (at pH 7.2)		
Benzyl acetate (140-11-4)			
Partition coefficient n-octanol/water (Log Pow)	1.96 (at 25 °C (at pH 7)		
Benzyl alcohol (100-51-6)			
Partition coefficient n-octanol/water (Log Pow)	1.05		
Amyl salicylate (2050-08-0)			
BCF - Fish [1]	(1170 dimensionless (whole body w.w.)		
Partition coefficient n-octanol/water (Log Pow)	4.5 (at 30 °C)		
Terpinyl acetate (80-26-2)			
Partition coefficient n-octanol/water (Log Pow)	4.4 (at 30 °C (at pH 7)		
Eugenol (97-53-0)			
Partition coefficient n-octanol/water (Log Pow)	1.83 (at 30 °C (at pH 5.5)		
Isobutyl acetate (110-19-0)			
BCF - Fish [1]	(no significant bioconcentration)		
Partition coefficient n-octanol/water (Log Pow)	2.3 (at 25 °C (at pH 7)		
Undecavertol (81782-77-6)			
Partition coefficient n-octanol/water (Log Pow)	3.9 (at 30 °C (at pH 7)		
Dipropylene glycol monomethyl ether (34590-94-8)			
Partition coefficient n-octanol/water (Log Pow)	0.35 (at 25 °C (at pH 7)		

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

.alphaPinene (80-56-8)	
Partition coefficient n-octanol/water (Log Pow)	4.1

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Results of PBT and vPvB assessment

No additional information available

## 12.6. Endocrine disrupting properties

No additional information available

#### 12.7. Other adverse effects

Additional information : Avoid release to the environment.

#### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Waste treatment methods
Product/Packaging disposal recommendations
Ecology - waste materials
HP Code

- : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- : Dispose in a safe manner in accordance with local/national regulations.
- : Avoid release to the environment.
- : HP3 "Flammable:"
  - flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and  $\leq$  75 °C;
  - flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;
  - flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;
  - flammable gaseous waste: gaseous waste which is flammable in air at 20  $^{\circ}\text{C}$  and a standard pressure of 101.3 kPa;
  - water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;
  - other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.

HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

### **SECTION 14: Transport information**

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID n	14.1. UN number or ID number			
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.2. UN proper shipping name				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
14.5. Environmental hazards				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available				

### 14.6. Special precautions for user

#### **Overland transport**

Not regulated

#### Transport by sea

Not regulated

#### Air transport

Not regulated

#### Inland waterway transport

Not regulated

#### Rail transport

Not regulated

## 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

#### **REACH Annex XVII (Restriction List)**

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(a)	Isoamyl acetate ; d- Limonene ; Isobutyl acetate ; Orange oil ; Rosemary Oil ; .alpha Pinene ; .betaPinene	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	BANANA & GINGER LILY #EU48594F; Citral; d- Limonene; Benzyl alcohol ; Isobutyl acetate; Amyl salicylate; Eugenol; Linalool; Orange oil; Rosemary Oil; zingiber officinale (ginger) root oil; Sandela; Triplal (Vertocitral)	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10

### Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(c)	BANANA & GINGER LILY #EU48594F; Benzyl acetate; d-Limonene; Amyl salicylate; Terpinyl acetate; Orange oil; Rosemary Oil; zingiber officinale (ginger) root oil; Sandela; Triplal (Vertocitral); Undecavertol	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
40.	Isoamyl acetate; d- Limonene; Isobutyl acetate; Orange oil; Rosemary Oil; .alpha Pinene; .betaPinene	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.

#### **REACH Annex XIV (Authorisation List)**

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

#### **REACH Candidate List (SVHC)**

Contains no substance(s) listed on the REACH Candidate List

#### **PIC Regulation (Prior Informed Consent)**

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

#### **POP Regulation (Persistent Organic Pollutants)**

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

#### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

#### **Explosives Precursors Regulation (2019/1148)**

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

#### **Drug Precursors Regulation (273/2004)**

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

#### 15.1.2. National regulations

#### Germany

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

**Netherlands** 

ABM category : A(2) - toxic for aquatic organisms, may have longterm hazardous effects in aquatic

environment

SZW-lijst van kankerverwekkende stoffen : Orange oil ,Sandela,Triplal (Vertocitral),Rosemary Oil,Ginger oil are listed

SZW-lijst van mutagene stoffen : Orange oil ,Sandela,Triplal (Vertocitral),Rosemary Oil,Ginger oil are listed

SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed

SZW-lijst van reprotoxische stoffen – : None of the components are listed Vruchtbaarheid

SZW-lijst van reprotoxische stoffen - Ontwikkeling

: None of the components are listed

**Denmark** 

Class for fire hazard : Class III-1 Store unit 50 liter

Classification remarks Flammable according to the Danish Ministry of Justice; Emergency management guidelines

for the storage of flammable liquids must be followed

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

Pregnant/breastfeeding women working with the product must not be in direct contact with

the product

**Switzerland** 

Storage class (LK) : LK 10/12 - Liquids

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## **SECTION 16: Other information**

Other information : None.

Full text of H- and EUH	Full text of H- and EUH-statements:		
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3		
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3		
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3		
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4		
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4		
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1		
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1		
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2		
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3		
Asp. Tox. 1	Aspiration hazard, Category 1		
Eye Dam. 1	Serious eye damage/eye irritation, Category 1		
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2		
Flam. Liq. 2	Flammable liquids, Category 2		
Flam. Liq. 3	Flammable liquids, Category 3		
H225	Highly flammable liquid and vapour.		
H226	Flammable liquid and vapour.		
H301	Toxic if swallowed.		
H302	Harmful if swallowed.		
H304	May be fatal if swallowed and enters airways.		
H311	Toxic in contact with skin.		
H315	Causes skin irritation.		
H317	May cause an allergic skin reaction.		
H318	Causes serious eye damage.		
H319	Causes serious eye irritation.		
H331	Toxic if inhaled.		
H332	Harmful if inhaled.		
H336	May cause drowsiness or dizziness.		
H371	May cause damage to organs.		
H400	Very toxic to aquatic life.		

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:		
H410	Very toxic to aquatic life with long lasting effects.	
H411	Toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
Skin Sens. 1	Skin sensitisation, Category 1	
Skin Sens. 1B	Skin sensitisation, category 1B	
STOT SE 2	Specific target organ toxicity – Single exposure, Category 2	
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis	

The classification complies with

: ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.