

# Bleed Block Primer

## Technical Product Data



### Product Use & Description

Marlin Bleed Block primer is a high quality, water based, single component, plasticizer free, primer that can be sprayed, brushed, or rolled. This product is formulated with bleed resistant materials that block the bleed through of asphaltic components that will discolor topcoats. It has excellent adhesion to most surfaces, including metal, single-ply, wood and concrete.

### Physical Properties

Solids by Weight ASTM D-1644	65(±3)%
Solids by Volume ASTM D-1653	52 (±3)%
VOC	<50 g/L
Flash Point	None
Viscosity	75 (±10) KU
Permeability ASTM D-1653	9 (±1)
Clean Up	Water
Shelf Life	12 Months

*The above information is based upon information reasonably available to Marlin Coatings, LLC at the time of publication. This is not to be constructed as a warranty or guarantee, expressed or implied.*

### Packing & Shelf Life

Available in 5 gallon pails. Gray is our standard color; custom colors are available at a premium.

The product should be stored in the original unopened container for up to 12 months from the manufacture date between the temperature range of 40-70 degrees Fahrenheit. Do NOT let the product freeze.

### Application Information

Proper preparation is imperative for the success of any roof coating project. Ensure that the application surface is completely clean, dry, and free of any loose particles. The product can be brush, sprayed, or roll applied with a medium nap roller. Before the application, the material should be mixed to ensure any settling during storage or shipping is evenly distributed throughout the product. If spray applying, ensure the product is at least 75°F, and apply at a rate of 1 gallon per square. Expect dry times to be 90 minutes at 50% humidity and 75°F ambient temperature. Do not apply when inclement weather is imminent.

# Bleed Block Primer

## Technical Product Data

---



### **Maintenance**

---

Maintenance is key to getting the most out of your roof. At a minimum, your roof should be inspected for damage twice a year, and immediately after any severe weather event. All repairs should be done with like materials.

### **Clean up**

---

Clean up of uncured products should be done with water.

### **Warranty**

---

Marlin Coatings offers a variety of warranties ranging from 5-20 years. Please reach out to [Christian@marlinroofcoatings.com](mailto:Christian@marlinroofcoatings.com) to discuss details.