

Rust Inhibiting Primer

Technical Product Data



Product Use & Description

Marlin Rust Inhibiting Primer is a high quality, water based, single component, rust inhibiting, primer that can be sprayed, brushed, or rolled. This product is designed to be used over rusted metal surfaces to prevent the spread of existing rust. Rust Inhibiting Primer can be brushed, sprayed or rolled.

Physical Properties

Weight/Gal.	10 lbs./gal (± 0.02)
Solids by Volume	42 (± 4) %
VOC	<65 g/L
Viscosity	800 (± 200) cP
Clean Up	Water
Shelf Life	12 Months

The above information is based upon information reasonably available to Marlin Coatings, LLC at the time of publication. This is not to be construed as a warranty or guarantee, expressed or implied.

Packing & Shelf Life

Available in 5 gallon pails. Dark Red is the only color available.

The product should be stored in the original unopened container for up to 12 months from the manufacture date between the temperature range of 40-70 degrees Fahrenheit. Do NOT let the product freeze.

Application Information

Proper preparation is imperative for the success of any roof coating project. Ensure that the application surface is completely clean, dry, and free of any loose particles. The product can be brush, sprayed, or roll applied with a medium nap roller. Before the application, the material should be mixed to ensure any settling during storage or shipping is evenly distributed throughout the product. If spray applying, ensure the product is at least 75°F, and apply at a rate of 1 gallon per 200 Square Feet. Expect dry times to be 2-3 hours at 75°F ambient temperature. Do not apply when inclement weather is imminent.

Maintenance

Maintenance is key to getting the most out of your roof. At a minimum, your roof should be inspected for damage twice a year, and immediately after any severe weather event. All repairs should be done with like materials.

Rust Inhibiting Primer Technical Product Data



Clean up

Clean up of uncured products should be done with water.

Warranty

Marlin Coatings offers a variety of warranties ranging from 5-20 years. Please reach out to Christian@marlinroofcoatings.com to discuss details.