

Silicone Gravel Leveler

Technical Product Data



Product Use & Description

Marlin Silicone Gravel Leveler is a 100% silicone coating that is red in color. This is a one component, moisture cured product designed to flow and level when poured over surfaces with gaps and voids. Although it could be used as a stand alone product, its intention is to be a base coat for areas described above. Depending on the amount of coating applied, the surface may not be entirely smooth after application. As a general rule of thumb, no rock should protrude more than 1/4" after installation.

This product also works well on many other substrates with irregularities, and should not be limited to only Gravel BUR roofs.

Physical Properties

| | |
|---------------------------------|-----------------|
| Solids by Volume ASTM 2697 | 96 (±3) |
| Weight | 10.3 lbs/gal |
| Permeance Rating ASTM D 1475 | 4.1 |
| VOC | <50 g/L |
| Viscosity ASTM D2196 | 3,000-5,000 cps |

The above information is based upon information reasonably available to Marlin Coatings, LLC at the time of publication. This is not to be constructed as a warranty or guarantee, expressed or implied.

Packing & Shelf Life

Available in 1 and 5 gallon pails. Red is the only color available for this product

The product should be stored in the original unopened container for up to 24 months from the manufacture date between the temperature range of 40-90 degrees Fahrenheit.

Application Information

This product can be applied using either a roller or sprayer. Depending on the size of existing surface texture, you will typically apply this product at a rate of 3-6 gallons per square. If rolling over gravel BUR, pour the coating onto the existing system and work it into cracks and voids using overlapping passes. Take special care not to knock embedded gravel loose. Remove any loose gravel from the system prior to the top coat application. Spray applications should be done using either a Graco GH 675 or GH 933 Hi Flo.

Silicone Gravel Leveler

Technical Product Data



Maintenance

Maintenance is key to getting the most out of your roof. At a minimum, your roof should be inspected for damage twice a year, and immediately after any severe weather event. All repairs should be done with like materials.

Clean up

Clean up of uncured products should be done using Naphtha VM&P or mineral spirits.

Warranty

Marlin Coatings offers a variety of warranties ranging from 5-20 years. Please reach out to Christian@marlinroofcoatings.com to discuss details.